



Email data object specification

Candidate Version 1.2 – 16 Mar 2006

Open Mobile Alliance

OMA-TS-DS_DataObjEmail-V1_2-20060316-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2006 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

Contents

1.	SCOPE	5
2.	REFERENCES	6
2.1	NORMATIVE REFERENCES	6
2.2	INFORMATIVE REFERENCES	6
3.	TERMINOLOGY AND CONVENTIONS	7
3.1	CONVENTIONS	7
3.2	DEFINITIONS	7
3.3	ABBREVIATIONS	7
4.	INTRODUCTION	8
5.	XML USAGE	9
5.1	INCLUDING EMAIL OBJECT IN OTHER XML DOCUMENTS	9
5.2	XML NAMESPACES	9
5.3	XML ATTRIBUTES	9
5.4	WBXML	9
6.	MIME USAGE	9
7.	DATA TYPES	10
7.1	DATETIME	10
7.2	BOOL	10
7.3	TEXT	11
7.4	INT	11
8.	MARK-UP LANGUAGE DESCRIPTION	13
8.1	EMAIL	13
8.2	READ	13
8.3	FORWARDED	13
8.4	REPLIED	13
8.5	RECEIVED	13
8.6	CREATED	14
8.7	MODIFIED	14
8.8	DELETED	14
8.9	FLAGGED	14
8.10	EMAILITEM	15
8.10.1	enc	15
8.11	EXTENSION FIELDS	16
8.11.1	Unique naming	16
8.11.2	Ext	16
8.11.3	XNam	16
8.11.4	XVal	17
9.	DTD	18
10.	SYNCML DATA SYNCHRONIZATION USAGE	20
10.1	CTCAP	20
10.1.1	enc	21
10.1.2	texttype	21
10.1.3	attachtype	21
10.2	DATA SYNC RECORD AND FIELD LEVEL FILTERING	22
10.2.1	Email Media Object Filter	22
10.3	EMAIL OBJECT REPLACE EXAMPLE	27
APPENDIX A. CHANGE HISTORY (INFORMATIVE)		29
A.1	APPROVED VERSION HISTORY	29
A.2	DRAFT/CANDIDATE VERSION 1.2 HISTORY	29

Tables

Table 1 enc attribute values15

1. Scope

The **email** data object is presented in this document. The content-specific aspects of synchronization (filtering keywords, etc...) are listed and clarified.

2. References

2.1 Normative References

- [DSREPU] “SyncML Representation Protocol, Data Synchronization Usage”, Open Mobile Alliance, “OMA-TS-DS_DataSyncRep-V1_2”, [URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [ISO 8601] "Data elements and interchange formats- Information interchange--Representation of dates and times ISO 8601-2000", International Organization for Standardization, June, 1988, [URL://www.iso.ch/iso/en/ISOOnline.openpage](http://www.iso.ch/iso/en/ISOOnline.openpage)
- [RFC1327] Hardcastle-Kille, S., "Mapping between X.400 (1988) / ISO 10021 and RFC 822", RFC 1327, May 1992. [URL:http://www.ietf.org/rfc/rfc1327.txt](http://www.ietf.org/rfc/rfc1327.txt)
- [RFC2045] “Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies”, N. Freed & N. Borenstein, November 1996, [URL:http://www.ietf.org/rfc/rfc2045.txt](http://www.ietf.org/rfc/rfc2045.txt)
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”. S. Bradner. March 1997. [URL:http://www.ietf.org/rfc/rfc2119.txt](http://www.ietf.org/rfc/rfc2119.txt)
- [RFC2234] “Augmented BNF for Syntax Specifications: ABNF”, D. Crocker, Ed., P. Overell, November 1997, [URL:http://www.ietf.org/rfc/rfc2234.txt](http://www.ietf.org/rfc/rfc2234.txt)
- [RFC2822] “Internet Message Format”. P. Resnick, Editor. April 2001 [URL:http://www.ietf.org/rfc/rfc2822.txt](http://www.ietf.org/rfc/rfc2822.txt)
- [DSDEVDTD] “OMA DS Device Information DTD”, Open Mobile Alliance,” OMA-TS-DS-DevInf-DTD-V1_2, [URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [WBXML] “WAP Binary XML Content Format Specification.” WAP Forum. [URL:http://www1.wapforum.org/tech/terms.asp?doc=WAP-192-WBXML-20010725-a.pdf](http://www1.wapforum.org/tech/terms.asp?doc=WAP-192-WBXML-20010725-a.pdf)
- [XML] “Extensible Markup Language (XML) 1.0”, World Wide Web Consortium Recommendation, [URL:http://www.w3.org/TR/REC-xml](http://www.w3.org/TR/REC-xml)

2.2 Informative References

3. Terminology and Conventions

3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

3.2 Definitions

Data type The schema used to represent a data object (e.g., text/calendar MIME content type for an iCalendar representation of calendar information or text/directory MIME content type for a vCard representation of contact information).

3.3 Abbreviations

OMA Open Mobile Alliance

4. Introduction

The email data object can be used to represent an interpersonal electronic mail object.

5. XML Usage

The **email** objects are represented in a mark-up language defined by [XML]. The **email** is an XML application. The **email** DTD (Document Type Definition) defines the XML document type used to represent **email** object. The **mail** DTD can be found in Section 9, but it is not necessary to read the DTD in order to understand it.

Email objects are specified using well-formed XML. However, the **email** need not be valid XML. That is, the **email** objects do not need to specify the XML declaration or prolog. They only need to specify the body of the XML document. This restriction allows for the **email** objects to be specified with greater terseness than well-formed, valid XML documents.

5.1 Including email object in other XML documents

When using the **email** object as content of another XML document element the mark-up characters MUST be properly escaped or the CDATA sections MUST be used. See [XML] specification for details on character escaping and usage of CDATA sections. See section 10.3 of this document for an example.

5.2 XML Namespaces

Email objects to date have no elements that may include elements of the other namespaces.

5.3 XML Attributes

In order to simplify the implementation of the **email** on small devices, the **email** objects have been intentionally designed to use the XML elements only. Currently no XML attributes are being defined for **email** objects.

5.4 WBXML

XML can be viewed as more verbose than alternative binary representations. This is often cited as a reason why it may not be appropriate for low bandwidth network protocols. In most cases, **email** uses shortened element type. This provides a minor reduction in verbosity.

Additionally, the **email** objects can be encoded in a tokenized, binary format defined by [WBXML]. The use of [WBXML] format is external to specification of the **email** and should be transparent to any application. The combination of the use of shortened element type names and an alternative binary format makes **email** competitive, from a compressed format perspective, with alternative, but private, binary representations.

6. MIME Usage

The [RFC2045] Internet standard provides an industry-accepted mechanism for identifying different content types. The **email** object is identified by a MIME media type. The **application/vnd.omads-email+xml** MIME content type MUST be used to indicate the **email** object wherever such indication is required.

7. Data types

The following basic data type definitions are provided for referencing from other parts of this document.

7.1 `datetime`

Usage: This value type is used to identify values that specify a precise calendar date and time of day.

Description:

The *datetime* data type is used to identify values that contain a precise calendar date and time of day. The format is based on the [ISO 8601] complete representation, basic format for a calendar date and time of day. The text format is a concatenation of the "date", followed by the LATIN CAPITAL LETTER T character (US-ASCII decimal 84) time designator, followed by the "time" format.

The *datetime* data type expresses time values in two forms:

The form of date and time with UTC offset **MUST NOT** be used. For example, the following is not valid for a date-time value:

```
...
<datefield>19980119T230000-0800</datefield> <!-- Invalid time format -->
...
```

FORM #1: DATE WITH LOCAL TIME

The date with local time form is simply a date-time value that does not contain the UTC designator nor does it reference a time zone. For example, the following represents January 18, 1998, at 11 PM:

```
...
<datefield>19980118T230000</datefield> <!-- January 18, 1998, 11 PM -->
...
```

This notation of *datetime* type is to be used by devices that have no knowledge of the time zone in which they operate. In this case, the *datetime* value that is being transferred is usually the same as the value that is being stored and shown to the user in the application UI.

FORM #2: DATE WITH UTC TIME

The date with UTC time, or absolute time, is identified by a LATIN CAPITAL LETTER Z suffix character (US-ASCII decimal 90), the UTC designator, appended to the time value. For example, the following represents January 19, 1998, at 0700 UTC:

```
...
<datefield>19980119T070000Z</datefield> <!-- January 19,1998,07:00 UTC -->
...
```

7.2 `bool`

Usage: To be used for Boolean type fields

Restrictions: A text value that MUST be either “true” to indicate Boolean “true” or “false” to indicate “false”. If the field is not present its value is assumed to be “false”.

Example:

```
...
<booleanfield>true</booleanfield> <!-- the field is set to "true" -->
...
```

7.3 text

Usage: To be used for textual fields

Restrictions: If the field is not present its value is assumed to be an empty string.

Example:

```
...
<textfield>Hello World!</textfield>
...
```

7.4 int

Usage: To be used for integer numeric fields.

Restrictions: The format for the integer values is defined here in an ABNF notation [RFC2234].

```
nonzero-digit = "1" / "2" / "3" / "4" / "5" / "6" / "7" / "8" / "9"

octal-digit = "0" / "1" / "2" / "3" / "4" / "5" / "6" / "7"

hexadecimal-digit = "0" / "1" / "2" / "3" / "4" / "5" / "6" / "7" / "8" / "9"
/
                    "a" / "b" / "c" / "d" / "e" / "f"
/
                    "A" / "B" / "C" / "D" / "E" / "F"

decimal-constant = nonzero-digit * ("0" / nonzero-digit)
hexadecimal-constant = ("0x" / "0X") 1*hexadecimal-digit
```

```
octal-constant = "0" 1*octal-digit
```

```
integer-value = *1("+ " / "-") (decimal-constant / hexadecimal-constant /  
octal-constant)
```

Example:

```
...  
<negativevalue>-1234</negativevalue>  
<positivevalue>1234</positivevalue>  
<anotherpositivevalue>+0xffffabc5</anotherpositivevalue>  
<octal>010</octal> <!-- octal value equivalent to decimal 8 -->  
...
```

8. Mark-up Language Description

8.1 Email

Usage: Indicates the beginning of the object

Parent elements: None

Content model:

```
Email (read?, forwarded?, replied?, received?, created?, modified?,
deleted?, flagged?, emailitem?, Ext*)
```

8.2 read

Usage: Specifies whether the email has been read

Parent elements: Email

Restrictions: *bool* type field as specified in section 7.2.

Content model:

```
read (#PCDATA)
```

8.3 forwarded

Usage: Specifies whether the email has been forwarded

Parent elements: Email

Restrictions: *bool* type field as specified in section 7.2.

Content model:

```
forwarded (#PCDATA)
```

8.4 replied

Usage: Specifies whether the email has been replied

Parent elements: Email

Restrictions: *bool* type field as specified in section 7.2.

Content model:

```
replied (#PCDATA)
```

8.5 received

Usage: Specifies the date and time when the email was received

Parent elements: Email

Restrictions: *datetime* type field as specified in section 7.1.

Content model:

```
received (#PCDATA)
```

8.6 created

Usage: Specifies the date and time when the email was created

Parent elements: Email

Restrictions: *datetime* type field as specified in section 7.1.

Content model:

```
created (#PCDATA)
```

8.7 modified

Usage: Specifies the date and time when any of the email object fields was last changed. Initially (after the draft item is created or a new message received) the *modified* date is equal to *created* date. As the state of the object changes (e.g. draft message gets submitted or unread message gets read) the *modified* field gets updated to reflect the date and time of the last state change.

Parent elements: Email

Restrictions: *Error! Reference source not found.* type field as specified in section 7.1.

Content model:

```
modified (#PCDATA)
```

8.8 deleted

Usage: Specifies whether the email has been scheduled for deletion

Parent elements: Email

Restrictions: *bool* type field as specified in section 7.2.

Content model:

```
deleted (#PCDATA)
```

8.9 flagged

Usage: Specifies whether the email has been flagged

Parent elements: Email

Restrictions: *bool* type field as specified in section 7.2.

Content model:

```
flagged (#PCDATA)
```

8.10 emailitem

Usage: contains the email header and body as specified in RFC822 / RFC2822

Parent elements: Email

Restrictions: The supporters MUST implement this property. If the field is not present within the object, the object is assumed to have an empty body.

Content model:

```
emailitem (#PCDATA)
```

8.10.1 enc

Usage: declares the mechanism used to encode the content of the element. This is used to avoid corrupting the XML content of the element with the presence of characters which do not belong to the valid ranges of characters as defined by the [XML]

Parent elements: emailitem

Restrictions: The following table lists standard `enc` values that MUST be understood by the conforming implementations.

Enc	Description
“quoted-printable”	The contents of the element is encoded using quoted-printable algorithm as specified by the section 6.7 of the [RFC2045]
“base64”	The contents of the element is encoded using quoted-printable algorithm as specified by the section 6.8 of the [RFC2045]

Table 1 enc attribute values

If the `enc` attribute is not present, the content is assumed to have no encoding.

The implementations SHOULD NOT use other `enc` attribute values than specified in the [Table 1]. In case of other `enc` values the usage of these encodings MUST conform to the rules defined by the [RFC2045] for Content-Transfer-Encoding.

Content model:

```
emailitem enc (CDATA #IMPLIED)
```

8.11 Extension fields

8.11.1 Unique naming

If an extension field is required, the following naming convention **MUST** be followed in order to prevent undesirable field name collisions.

```
x-name          = "x-" vendorid "-" 1*(ALPHA / DIGIT / "-")           ;field name
vendorid        = 3*(ALPHA / DIGIT)                                   ;Vendor identification
ALPHA           = %x41-5A / %x61-7A                                  ; A-Z / a-z
DIGIT           = %x30-39                                           ; 0-9
```

8.11.2 Ext

Usage: Specifies the non-standard, experimental extensions supported by the device. The extensions are specified in terms of the XML element type name and the value.

Parent Elements: Email

Restrictions: The Ext element type **MUST** specify the extension element name. It may also specify one or more enumerated values. Multiple non-standard extensions can be specified by specifying the Ext element type multiple times. This element type is optional.

Content Model:

```
Ext (XNam, XVal*)
```

Attributes: None.

Example: The following example specifies a non-standard extension, named "Cliver" for a fictitious company, Foo, which takes values of "5.0", "5.01" or "5.02".

```
<Ext>
  <XNam>x-Foo-Cliver</XNam>
  <XVal>5.0</XVal>
  <XVal>5.01</XVal>
  <XVal>5.02</XVal>
</Ext>
```

8.11.3 XNam

Usage: Specifies the name of one of the extension element types.

Parent Elements: Ext

Restrictions: The element type is required whenever an Ext element is present.

Content Model:

```
XNam (#PCDATA)
```

Attributes: None.

Example:

```
<Ext>
  <XNam>x-Foo-CliVer</XNam>
  <XVal>5.0</XVal>
  <XVal>5.01</XVal>
  <XVal>5.02</XVal>
</Ext>
```

8.11.4 XVal

Usage: Specifies one of the valid values for an extension element type.

Parent Elements: Ext

Restrictions:

Content Model:

```
XVal (#PCDATA)
```

Attributes: None.

Example:

```
<Ext>
  <XNam>x-Foo-CliVer</XNam>
  <XVal>5.0</XVal>
  <XVal>5.01</XVal>
  <XVal>5.02</XVal>
</Ext>
```

9. DTD

```
<!--
application/vnd.omads-email+xml V1.2 Document Type Definition

http://www.openmobilealliance.org/tech/DTD/OMA-DS-DataObjEmail-DTD-
V1_2.dtd

Copyright Open Mobile Alliance Ltd., 2002-2003
    All rights reserved
Terms and conditions of use are available from the
Open Mobile Alliance Ltd. web site at
http://www.openmobilealliance.org/useterms.html-->

<?xml version="1.0" encoding="UTF-8"?>
<!-- Root Element -->
<!ELEMENT Email (read?, forwarded?, replied?, received?, created?,
modified?, deleted?, flagged?, emailitem?, Ext*)>

<!ELEMENT read (#PCDATA)>
<!ELEMENT forwarded (#PCDATA)>
<!ELEMENT replied (#PCDATA)>
<!ELEMENT received (#PCDATA)>
<!ELEMENT created (#PCDATA)>
<!ELEMENT modified (#PCDATA)>
<!ELEMENT deleted (#PCDATA)>
<!ELEMENT flagged (#PCDATA)>
<!ELEMENT emailitem (#PCDATA)>
<!ATTLIST emailitem enc CDATA #IMPLIED>
<!ELEMENT Ext (XNam, XVal*)>
<!ELEMENT XNam (#PCDATA)>
<!ELEMENT XVal (#PCDATA)>
<!-- End of DTD Definition -->
```



10.SyncML Data Synchronization Usage

The following sections describe the content-specific recommendations for using the data synchronization [DSREPU] protocol with **email** data objects.

10.1 CTCap

Refer to [DSDEVDTD] for further details on the specification of the Device Information DTD.

```
<CTCap>
  <CTType> application/vnd.omads-email+xml</CTType>
  <Property>
    <PropName>read</PropName>
    <DataType>bool</DataType>
    <DisplayName>Read</DisplayName>
  </Property>
  <Property>
    <PropName>forwarded</PropName>
    <DataType>bool</DataType>
    <DisplayName>Forwarded</DisplayName>
  </Property>
  <Property>
    <PropName>replied</PropName>
    <DataType>bool</DataType>
    <DisplayName>Replied</DisplayName>
  </Property>
  <Property>
    <PropName>received</PropName>
    <DataType>datetime</DataType>
    <DisplayName>Date received</DisplayName>
  </Property>
  <Property>
    <PropName>created</PropName>
    <DataType>datetime</DataType>
    <DisplayName>Date created</DisplayName>
  </Property>
</CTCap>
```

```
</Property>
<Property>
  <PropName>emailitem</PropName>
  <DataType>bin</DataType>
  <DisplayName>emailitem</DisplayName>
  <PropParam>
    <ParamName>enc</ParamName>
    <ValEnum>base64</ValEnum>
    <ValEnum>quoted-printable</ValEnum>
  </PropParam>
  <PropParam>
    <ParamName>texttype</ParamName>
    <ValEnum>text/plain</ValEnum>
    <ValEnum>text/html</ValEnum>
  </PropParam>
  <PropParam>
    <ParamName>attachtype</ParamName>
    <ValEnum>image/jpeg</ValEnum>
    <ValEnum>image/tiff</ValEnum>
  </PropParam>
</Property>
</CTCap>
```

10.1.1 enc

The `PropParam` element type with the value of `enc` MUST utilise `ValEnum` element type to indicate the supported encoding algorithms. The example above (10.1) illustrates a section of `CTCap` that lists the standard encoding algorithms as supported.

10.1.2 texttype

This `PropParam` specifies which content types are recognized for textual part of the message. If no enumeration values specified, means that all types are allowed. If `texttype` is not present within the `CTCap`, means that textual information is not required by the sender. This particular case is useful for scenarios in which sender chooses to sync only limited information for the messages (e.g. [RFC2822] headers only).

10.1.3 attachtype

This `PropParam` specifies which content types are recognized for attached objects. If no enumeration values specified, means that all types are allowed. If `attachtype` is not present within the `CTCap`, means that attachment objects are not

required by the sender. This particular case is useful for scenarios in which sender chooses to sync only limited information for the messages (e.g. [RFC2822] headers only).

10.2 Data Sync Record and Field Level Filtering

10.2.1 Email Media Object Filter

Filtering for email objects can be specified using both `Record` and `Field` elements.

In the case of `Record` elements, the set of recommended keywords to support are as follows:

```
ct-filter-keyword = email-field | search-keyword
```

10.2.1.1 email-field

```
email-field = <Any field that is defined for the application/vnd.omads-email+xml content type in this document except for the emailitem field>
```

10.2.1.2 search-keyword

In addition to the actual email fields defined in this document, the following set of keywords is recommended to be supported so that they can be specified in a filtering query to limit the amount of items. The types of values to be used with these keywords are described in section 7.

Keyword	Interpretation	ct-filter-value Type
BCC	Contents of the [RFC2822] "Bcc:" destination address field	text
CC	Contents of the [RFC2822] "Cc:" destination address field	text
FROM	Contents of the [RFC2822] "From:" originator field	text
IMPORTANCE	The case-insensitive values "low", "normal" and "high" are allowed as specified by the [RFC1327].	text
NOATTACH	Item does not contain attachments	bool
NOBODY	Item does not contain [RFC2822] body (i.e. item is an empty message with only [RFC2822] header fields defined)	bool
SIZE	The number of octets in the content of <code>emailitem</code> field	int
SUBJECT	Contents of the [RFC2822] "Subject:" informational field	text

TO	Contents of the [RFC2822] "To:" destination address field	text
----	---	------

Table 2 search keywords

10.2.1.3 Example 1: Record filtering

In this scenario, the client wishes to synchronize e-mail messages whose internal date is within or later than June 1, 2003 and importance is either "normal" or "high"

1. During the initial sync, the client and server exchange their device info.
2. The client analyses the server's device info, and the client notes that the server supports receiving filters on the Email data store for queries using the "syncml:filtertype-cgi" grammar.
 - a. The server includes in its device info the Filter-Rx and FilterCap elements that it supports. This includes the "IMPORTANCE" and "created" keywords.
 - b. The client doesn't require filtering on any additional fields, so it determines that this server supports the filter it wishes to send.

```

<Datastore>
  <SourceRef>./email/inbox</SourceRef>
  <DisplayName>Email Inbox</DisplayName>
  ...
  <Filter-Rx>
    <CTType>syncml:filtertype-cgi</CTType>
    <VerCT>1.0</VerCT>
  </Filter-Rx>
  <CTCap>
    ...
  </CTCap>
  <FilterCap>
    <CTType>syncml:filtertype-cgi</CTType>
    <VerCT>1.0</VerCT>
    <FilterKeyword>IMPORTANCE</FilterKeyword>
    <FilterKeyword>created</FilterKeyword>
  </FilterCap>
</Datastore>

```

3. The client sends an Alert for the Email data store with a filter.

- a. It includes a `Filter Record` element with a `Meta Type` value of “`syncml:filtertype-cgi`” to indicate the grammar being used.
- b. The filter query in the `Item Data` element contains a value of “`created>20030601T000000Z&AND; IMPORTANCE&NE; low`” to constrain the items synchronized to those whose internal date is within or later than June 1, 2003 and importance is either “normal” or “high”.

```

<Alert>
  <Data>200</Data>
  <Item>
    <Target>
      <LocURI>./email/inbox</LocURI>
      <Filter>
        <Meta><Type>application/vnd.omads-email+xml</Type></Meta>
        <Record>
          <Item>
            <Meta><Type>syncml:filtertype-cgi</Type></Meta>
            <Data>
              created&GT;20030601T000000Z&AND; IMPORTANCE&NE; low
            </Data>
          </Item>
        </Record>
      </Filter>
    </Target>
    <Source>
      <LocURI>dev-inbox</LocURI>
    </Source>
  </Item>
</Alert>

```

4. The server receives the `Alert` with the `Filter Record` element.
 - a. It determines that it supports the filter operation for the data store, content type, filter grammar, and properties.
 - b. It replies with a status code of 200 for the `Alert`, indicating that it can satisfy the request to sync with filtering.
5. The synchronization process continues normally.

- a. The client sends all of its changes to the server (the filter constraint is not imposed on it in this scenario).
- b. The server sends changes only for items that satisfy the filter query.

10.2.1.4 Example 2: Content filtering

In this scenario, the client wishes to synchronize only plain text bodies with all attachments removed and truncate the resulting emailitem content to 2 kilobytes.

1. During the initial sync, the client and server exchange their device info.
2. The client sends an `Alert` for the Email data store with a filter. It includes a `Filter Field` element containing a `Property` element set to “emailitem” containing a `MaxSize` element set to 2048 (2K), specifying that only “text/plain” type parts of the text can be included.

```
<Alert>
  <Data>200</Data>
  <Item>
    <Target>
      <LocURI>./email/inbox</LocURI>
      <Filter>
        <Meta><Type>application/vnd.omads-email+xml</Type></Meta>
        <Field>
          <Item>
            <Meta><Type>application/vnd.syncml-devinf+xml</Type></Meta>
            <Data>
              <Property>
                <PropName>emailitem</PropName>
                <MaxSize>2048</MaxSize>
                <PropParam>
                  <ParamName>texttype</ParamName>
                  <ValEnum>text/plain</ValEnum>
                </PropParam>
              </Property>
            </Data>
          </Item>
        </Field>
      </Filter>
    </Target>
    <Source>
      <LocURI>dev-inbox</LocURI>
    </Source>
  </Item>
</Alert>
```

3. The server receives the Alert with the Filter Record element.
 - c. It determines that it supports the filter operation for the data store, content type, filter grammar, and properties.

- d. It replies with a status code of 200 for the `Alert`, indicating that it can satisfy the request to sync with filtering.
- 4. The synchronization process continues normally.
 - e. The client sends all of its changes to the server (the filter constraint is not imposed on it in this scenario).
 - f. Server recalculates the `emailitem` fields for the client to include only plain text. For the items that contain more than 2048 bytes in resulting `emailitem` field, the server truncates the field content.

10.3 Email object replace example

```

...
<Sync>
...
  <Replace>
    <CmdID>6</CmdID>
    <Meta>
      <Type xmlns='syncml:metinf'>application/vnd.omads-
email+xml</Type>
    </Meta>
    <Item>
      <Source>
        <LocURI>123</LocURI>
      </Source>
      ...
      <Data><![CDATA[
        <Email>
          <read>>false</read>
          <created>20030807T231830Z</created>
          <emailitem>
<!-- The content of the email as specified by the RFC 2822 -->
<![CDATA[From: <sender@mail.com>
To: <receiver@mail.com>
... ]]]>><![CDATA[
          </emailitem>
        </Email>]]>
      </Data>

```

```
</Item>  
</Replace>  
</Sync>
```

In this example the device that has previously indicated that it supports “created”, “read” and “emailitem” fields for the email object data type receives the update of the object.

Appendix A. Change History

(Informative)

A.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version –or- No previous version within OMA

A.2 Draft/Candidate Version 1.2 History

Document Identifier	Date	Sections	Description
Draft Versions OMA-SyncML-DataObjEmail-V1_2	19 Jan 04	Title page, p. 2	Changed dates and copyrights
	26 Jan 04	Last page	Removed page with empty appendix B
	01 Mar 04	TP, 2.1	Clerical changes from consistency review
	14 Apr 04	8.1, 8.7, 9	Added “modified” element to the “Email” parent element, “Email” content model updated, DTD updated.
		8.10, 9, 10.1	Added “enc” attribute for “mailitem” element, updated corresponding parts of CTCaps example and DTD; table numbers updated.
		10.2.1.3	Updated example description to match the example code.
		10.3	Fixed CDATA sections in email object replace example
	5.1, 6, 9, 10.2, 10.3	Added paragraph about CDATA in “XML Usage” section; updated MIME types.	
05 May 04	Title page	Changed date	
Candidate Version OMA-SyncML-DataObjEmail-V1_2	01 Jun 2004	n/a	Status changed to Candidate by TP TP ref # OMA-TP-2004-0178-DS-V1_2-for-candidate
Candidate Version OMA-TS-DS_DataObjEmail-V1_2	16 Mar 2006	7.2 8.11.2, 8.11.3, 8.11.4 Filename and name of specification updated	Incorporated CRs: DS-2006-0098 DS-2006-0099 DS-2006-0085