



# **Shared XDM Specification**

## **Candidate Version 1.0 – 18 Apr 2006**

---

**Open Mobile Alliance**  
OMA-TS-XDM\_Shared-V1\_0-20060418-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2006 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

# Contents

<b>1. SCOPE</b> .....	<b>4</b>
<b>2. REFERENCES</b> .....	<b>5</b>
<b>2.1 NORMATIVE REFERENCES</b> .....	<b>5</b>
<b>2.2 INFORMATIVE REFERENCES</b> .....	<b>5</b>
<b>3. TERMINOLOGY AND CONVENTIONS</b> .....	<b>6</b>
<b>3.1 CONVENTIONS</b> .....	<b>6</b>
<b>3.2 DEFINITIONS</b> .....	<b>6</b>
<b>3.3 ABBREVIATIONS</b> .....	<b>6</b>
<b>4. INTRODUCTION</b> .....	<b>7</b>
<b>5. SHARED XDM APPLICATION USAGES</b> .....	<b>8</b>
<b>5.1 URI LIST</b> .....	<b>8</b>
5.1.1 Structure.....	8
5.1.2 Application Unique ID.....	8
5.1.3 Default Namespace .....	8
5.1.4 XML Schema .....	8
5.1.5 MIME Type .....	9
5.1.6 Validation constraints .....	9
5.1.7 Data Semantics .....	9
5.1.8 Naming conventions .....	9
5.1.9 Global documents .....	10
5.1.10 Resource interdependencies.....	10
5.1.11 Authorization policies.....	10
<b>5.2 GROUP USAGE LIST</b> .....	<b>10</b>
5.2.1 Structure.....	10
5.2.2 Application Unique ID.....	11
5.2.3 Default Namespace .....	11
5.2.4 XML Schema .....	11
5.2.5 MIME Type .....	11
5.2.6 Validation constraints .....	11
5.2.7 Data Semantics .....	12
5.2.8 Naming conventions .....	12
5.2.9 Global documents .....	12
5.2.10 Resource interdependencies.....	12
5.2.11 Authorization policies.....	12
<b>6. SUBSCRIBING TO CHANGES IN THE XML DOCUMENTS</b> .....	<b>12</b>
<b>APPENDIX A. STATIC CONFORMANCE REQUIREMENTS (NORMATIVE)</b> .....	<b>13</b>
<b>A.1 SHARED XDM APPLICATION USAGES (SERVER)</b> .....	<b>13</b>
<b>A.2 SHARED XDM APPLICATION USAGES (CLIENT)</b> .....	<b>15</b>
<b>APPENDIX B. EXAMPLES (INFORMATIVE)</b> .....	<b>17</b>
<b>B.1 MANIPULATING URI LISTS</b> .....	<b>17</b>
B.1.1 Obtaining URI Lists.....	17
B.1.2 Obtaining Group Usage Lists.....	18
<b>APPENDIX C. CHANGE HISTORY (INFORMATIVE)</b> .....	<b>20</b>
<b>C.1 APPROVED VERSION HISTORY</b> .....	<b>20</b>
<b>C.2 DRAFT/CANDIDATE VERSION 1.0 HISTORY</b> .....	<b>20</b>

# 1. Scope

This specification describes the data format and XCAP application usage for the shared document, URI List, which can be used by all OMA enablers.

## 2. References

### 2.1 Normative References

- [XDM\_RD] “XML Document Management Requirements”, Candidate Version 1,0, Open Mobile Alliance™, OMA-RD-XDM-V1\_0, URL: <http://www.openmobilealliance.org/>
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997, URL:<http://www.ietf.org/rfc/rfc2119.txt>
- [RFC2234] “Augmented BNF for Syntax Specifications: ABNF”. D. Crocker, Ed., P. Overell. November 1997, URL:<http://www.ietf.org/rfc/rfc2234.txt>
- [XCAP] “The Extensible Markup Language (XML) Configuration Access protocol (XCAP)”, J. Rosenberg, March 21, 2006, URL: <http://www.ietf.org/internet-drafts/draft-ietf-simple-xcap-09.txt>  
Note: Work in progress
- [XCAP\_List] “Extensible Markup Language (XML) Formats for Representing Resource Lists”, J. Rosenberg, February 7, 2005, URL: <http://www.ietf.org/internet-drafts/draft-ietf-simple-xcap-list-usage-05.txt>  
Note: IETF Draft Work in progress
- [XDM\_Spec] “XML Document Management (XDM) Specification”, Version 1.0, Open Mobile Alliance™, OMA-TS-XDM\_Core-V1\_0, URL:<http://www.openmobilealliance.org/>

### 2.2 Informative References

- [PoC\_XDM] “PoC XDM Specification”, Version 1.0, Open Mobile Alliance™, OMA-TS-POC\_XDM-V1\_0, URL:<http://www.openmobilealliance.org/>
- [RLS\_XDM] “Resource List Service (RLS) XDM Specification”, Version 1.0, Open Mobile Alliance™, OMA-TS-Presence\_SIMPLE\_RLS\_XDM-V1\_0, URL:<http://www.openmobilealliance.org/>

## 3. Terminology and Conventions

### 3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

### 3.2 Definitions

<b>Global document</b>	A document placed under the XCAP global tree that applies to all users of that application usage.
<b>Global tree</b>	A URL that represents the parent for all global documents for a particular application usage within a particular XCAP root. (Source: [XCAP])
<b>XCAP Application Usage</b>	Detailed information on the interaction of an application with an XCAP server. (Source: [XCAP])
<b>XCAP Server</b>	An HTTP server that understands how to follow the naming and validation constraints defined in this specification. (Source: [XCAP])

### 3.3 Abbreviations

<b>AUID</b>	Application Unique ID
<b>HTTP</b>	Hypertext Transfer Protocol
<b>IETF</b>	Internet Engineering Task Force
<b>OMA</b>	Open Mobile Alliance
<b>TLS</b>	Transport Layer Security
<b>URI</b>	Uniform Resource Identifier
<b>XCAP</b>	XML Configuration Access Protocol
<b>XDM</b>	XML Document Management
<b>XML</b>	Extensible Markup Language

## 4. Introduction

This specification, which is a part of the XML Document Management enabler, describes a particular type of list, the URI List, which is a convenient way for a principal to group together a number of URIs (e.g., as “Friends”, “Family” etc.) or other resources, where such a list is expected to be reused for a number of different services. Such a list is not enabler-specific and can be re-used wherever a principal has a need to collectively refer to a group of other end users or resources. For example, the reference to a list of “Friends” can be an entry in a PoC Group member list (see [PoC\_XDM] for details), or be included in a Presence List (see [RLS\_XDM] for details).

This specification provides the data schema and application usage of a URI List and Group Usage List. It reuses the document structure “resource-lists” described in IETF [XCAP\_List].

## 5. Shared XDM Application Usages

### 5.1 URI list

#### 5.1.1 Structure

The URI List document SHALL conform to the structure of the “resource-lists” document described in [XCAP\_List] Section 3 with the following extension:

- The <appusages> child element of the <list> element defines the applications which use this list. The <appusages> element contains the node URI and the AUID value of those application usages referring to the <list> element.

Note: It is recommended that the <entry-ref> element defined in [XCAP\_List] not be used as it may create extra roundtrips between an XDM client and an XDM server when resolving a URI-list.

#### 5.1.2 Application Unique ID

The URI List SHALL conform to the AUID for “resource-lists” defined in [XCAP\_List] Section 3.4.1.

#### 5.1.3 Default Namespace

The default namespace SHALL conform to the default namespace “urn:ietf:params:xml:ns:resource-lists” for the “resource-lists” document described in [XCAP\_List].

#### 5.1.4 XML Schema

The URI List document SHALL conform to the XML schema for the “resource-lists” document described in [XCAP\_List] Section 3.4.3 with the following extension:

```
<?xml version="1.0" encoding="UTF-8"?>
  <xs:schema targetNamespace="urn:oma:params:xml:ns:resource-list:appusage"

    xmlns="urn:oma:params:xml:ns:resource-list:appusage"
    xmlns:xs="http://www.w3.org/2001/XMLSchema"

    elementFormDefault="qualified">

<!-- OMA specific extension: 'appusages' child element to the complex type 'listType' in IETF resource-lists namespace-->
  <xs:element name="appusages">
    <xs:complexType>
      <xs:sequence minOccurs="0" maxOccurs="unbounded">
        <xs:element name="nodeuri" >

        <xs:complexType>

          <xs:attribute name="uri" type="xs:anyURI" use="required"/>

          <xs:attribute name="auid" type="xs:string" use="required"/>

        </xs:complexType>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```



```
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

</xs:schema>
```

### 5.1.5 MIME Type

The URI List SHALL conform to the MIME type “application/resource-lists+xml” defined in [XCAP\_List] Section 3.4.2.

### 5.1.6 Validation constraints

In addition to the XML schema, the additional validation constraints on a URI List SHALL conform to those described in [XCAP\_List] Section 3.4.5, with the following clarifications:

The “name” attribute of the <list> element SHALL be present.

Therefore, if XDM Client proposes a creation of <list> element without its “name” attribute, an HTTP “409 Conflict” response SHALL be returned with the error condition identified by the <constraint-failure> element. If included, the “phrase” attribute of this element SHOULD be set “Name attribute is required.”

Note: It is noted that the value of the “name” attribute of <list> element shall also conform to the uniqueness constraints as specified in [XCAP\_List] Section 3.4.5.

The <appusages> element MAY be present as a child element to the <list> element. If present, the element SHALL be inserted after the child elements as defined by the resource-lists namespace as the place for its extension.

### 5.1.7 Data Semantics

The data semantics for a URI List SHALL conform to those described in [XCAP\_List] Section 3.4.5 with the following extension:

- The <appusages> element SHALL be used to store which other application usages that has a reference to this URI list. The <nodeuri> child element SHALL be used to store a reference to such an application usage. The attribute “uri” of this element SHALL contain a node URI as defined in [XCAP] to the document containing the reference. The attribute “auid” SHALL contain an Application Unique ID [XCAP] defined for the application usage that has the reference. XDM clients MAY insert a <nodeuri> element when inserting a reference to a URI List in any other application usage document.

Note: XDM clients that are using an application usage that has a reference to a URI list are recommended to check that the <appusages> element contains a <nodeuri> element with information about used application usage. If a client finds that such an element is not included the client is recommended to insert a <nodeuri> element with information about the application usage in order to keep the information up to date.

### 5.1.8 Naming conventions

The naming conventions for a URI List SHALL conform to those described in [XCAP\_List] Section 3.4.7.

The XDMC SHALL use a single file for all shared URI Lists for a particular user. The file name SHALL be “index”.

A XDMC may have a need to store a URI-List that has one well defined usage. A user can only have one list of this type. The “name” attribute of the <list> element is used to indicate the usage. The syntax used SHALL be a string of the format

“oma\_xyz” where xyz is a string containing letters a to z. The naming convention SHALL only be used in a <list> element that is a child element to the root element <resource-lists>. This specification defines the following name attributes:

- oma\_allcontacts : This name SHALL be used by an XDMC that has a need to store all users URI:s, that it knows about, in one list independent of how the URI:s are used.
- oma\_buddylist : This name SHALL be used by an XDMC that has a need to store all users URI:s, that it wants to use for all types of communication, in one list.
- oma\_pocbuddylist: This name SHALL be used by an XDMC that has a need to store users URI:s, that it wants to use for PoC communication, in one list.
- oma\_blockedcontacts. This name SHALL be used by a XDMC that has a need to store URI:s to users, that it wants to block/reject in a number of application usages, in one list.

Enablers that need to define other types of usage can do this in their enabler specification as long as they are following the syntax above and make sure that no other enabler is using the same “xyz” string.

**Editor’s Note: need to provide reference where those values are enumerated once OMNA has created the appropriate registry.**

The “name” attribute of a <list> element SHALL be present for referencing by other resources using <external> element. The value of “name” attribute of a <list> element SHALL be unique amongst all other <list> elements within the same parent element (as specified in [XCAP\_List] Section 3.1)

### 5.1.9 Global documents

This application usage defines no global documents.

### 5.1.10 Resource interdependencies

The value of “name” attribute of a <list> element SHOULD NOT be changed during the existence of the corresponding <list> element. A modification to the value of “name” attribute of the <list> element SHOULD be accompanied with all subsequent updates against wherever the <list> element is referred by other resources using <external> element. Otherwise, the reference would be broken.

### 5.1.11 Authorization policies

The authorization policies for manipulating a URI List SHALL conform to those described in [XDM\_Spec] Section 6.4.3.

## 5.2 Group Usage List

This section specifies a new application Group Usage List, a list of group names or service URIs that are known by the XCAP Client. The feature MAY be supported.

### 5.2.1 Structure

The URI List document SHALL conform to the structure of the “resource-lists” document described in [XCAP\_List] Section 3 with the following difference:

1. Extensions on “uriusage” element in <entry> element from “urn:oma:params.xml:ns:resource-list:oma-uriusage” –namespace defines used uri type. Element “uriusage” is an abstract type. The <uriusage> element is not application specific. Each application can define their specific uri usages in their specifications.

2. Prohibition of using <external> and <entry-ref> so as to avoid complexity.

## 5.2.2 Application Unique ID

The AUID SHALL be org.openmobilealliance.group-usage-list.

## 5.2.3 Default Namespace

The default namespace SHALL conform to the default namespace “urn:ietf:params:xml:ns:resource-lists” for the “resource-lists” document described in [XCAP\_List].

## 5.2.4 XML Schema

The URI List document SHALL conform to the XML schema for the “resource-lists” document described in [XCAP\_List] Section 3.4.3 with the following extension:

```
<?xml version="1.0" encoding="UTF-8"?>
  <xs:schema targetNamespace="urn:oma:params:xml:ns:resource-list:oma-uriusage"
    xmlns="urn:oma:params:xml:ns:resource-list:oma-uriusage"
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    elementFormDefault="qualified">

    <!-- OMA specific extension: "uriusage" child elements -->

    <xs:element name="uriusages">
      <xs:complexType>
        <xs:sequence>
          <xs:element ref="uriusage" minOccurs="0" maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>

    <xs:element name="uriusage" abstract="true"/>

  </xs:schema>
```

## 5.2.5 MIME Type

The MIME type SHALL be “application/vnd.oma.group-usage-list+xml”.

## 5.2.6 Validation constraints

In addition to the XML schema, the additional validation constraints on a Group Usage List SHALL conform to those described in [XCAP\_List] Section 3.4.4.

If the XDMC uses or adds an <entry-ref> or <external> element (specified in [XCAP\_List]) under the <list> element, to refer to any storage of a PoC Contact Address in the Shared XDMS, the PoC XDMS comply with this specification SHALL return an error code “409 **Conflict**” response which includes the XCAP error element <constraint-failure>. If included, the "phrase" attribute SHOULD be set to "Not allowed".

## 5.2.7 Data Semantics

The data semantics for a Group Usage List SHALL conform to those described in [XCAP\_List] Section 3.4.5 with the following extensions:

The <uriusage> element SHALL be used to indicate what that the “uri” attribute of the <entry> element is used for. The <uriusage> element is not application specific. Each application can define their specific uri usages in their specifications.

## 5.2.8 Naming conventions

The XDMC MAY use a single file for all group names or service URIs. Every group name or service URI is defined in each <list> element.

The "name" attribute of each <list> element SHALL be present and SHALL be unique amongst all <list> elements within the same parent element.

The XDMC MAY store all his service URI's in a single xml document. If so, the name of the file SHALL be "index".

## 5.2.9 Global documents

This application usage defines no global documents.

## 5.2.10 Resource interdependencies

This application usage defines no additional resource interdependencies.

## 5.2.11 Authorization policies

The owner XCAP Client SHALL has the authorization right to access and modify the document.

# 6. Subscribing to changes in the XML documents

The Shared XDMS SHALL support subscriptions to changes in the XML documents as defined by the procedures in section 6.2.2.1 step 2 to step 6 and 6.2.2.2 of the [XDM\_Spec].

# Appendix A. Static Conformance Requirements (Normative)

The SCR’s defined in the following tables include SCR for:

- Shared XDM Application Usages

Each SCR table identifies a list of supported features as:

**Item:** Identifier for a feature.

**Function:** Short description of the feature.

**Reference:** Section(s) of this specification with more details on the feature.

**Status:** Whether support for the feature is mandatory or optional. MUST use “M” for mandatory support and “O” for optional support in this column.

**Requirement:** This column identifies other features required by this feature. If no other features are required, this column is left empty.

This section describes the dependency grammar notation to be used in the Requirement column of the SCR and CCR tables using ABNF [RFC2234].

TerminalExpression = ScrReference / NOT TerminalExpression / TerminalExpression LogicalOperator  
TerminalExpression / (“ TerminalExpression “)”

ScrReference = ScrItem / ScrGroup

ScrItem = SpecScrName “-“ GroupType “-“ DeviceType “-“ NumericId / SpecScrName “-“ DeviceType  
“-“ NumericId

ScrGroup = SpecScrName “:” FeatureType / SpecScrName “-“ GroupType “-“ DeviceType “-“  
FeatureType

SpecScrName = 1\*Character;

GroupType = 1\*Character;

DeviceType = “C” / “S”; C – client, S – server

NumericId = Number Number Number

LogicalOperator = “AND” / “OR”; AND has higher precedence than OR and OR is inclusive

FeatureType = “MCF” / “OCF” / “MSF” / “OSF”; See Section A.1.6

Character = %x41-5A ; A-Z

Number = %x30-39 ; 0-9

## A.1 Shared XDM Application Usages (Server)

Item	Function	Reference	Status	Requirement
Shared_XDM-AU-S-001	URI list structure	5.1.1	M	
Shared_XDM-AU-S-002	Application Unique ID in URI list	5.1.2	M	

Item	Function	Reference	Status	Requirement
Shared_XDM-AU-S-003	XML schema of URI list	5.1.4	M	
Shared_XDM-AU-S-004	URI list conforms to MIME type	5.1.5	M	
Shared_XDM-AU-S-005	Validation constraints, in addition to the XML schema	5.1.6	M	
Shared_XDM-AU-S-006	Data semantics of URI list	5.1.7	M	
Shared_XDM-AU-S-007	Naming conventions for URI list	5.1.8	M	
Shared_XDM-AU-S-008	Authorization policies	5.1.11	M	XDM-XDMS-S-005
Shared_XDM-AU-S-009	Subscribing to changes in XML documents	6	M	
Shared_XDM-AU-S-010	Default name space for URI list and also Group Usage List	5.1.3, 5.2.3	M	
Shared_XDM-AU-S-011	Group Usage List document structure	5.2.1	O	
Shared_XDM-AU-S-012	Application Unique ID in Group Usage List document	5.2.2	O	
Shared_XDM-AU-S-013	XML schema of Group Usage List document	5.2.4	O	
Shared_XDM-AU-S-014	Group Usage List document conforms to MIME type	5.2.5	O	
Shared_XDM-AU-S-015	Validation constraints, in addition to the XML schema	5.2.6	O	
Shared_XDM-AU-S-016	Data semantics of Group Usage List	5.2.7	O	
Shared_XDM-AU-S-017	Naming conventions for Group Usage List	5.2.8	O	
Shared_XDM-AU-S-018	Authorization policies for Group Usage List	5.2.11	O	

## A.2 Shared XDM Application Usages (Client)

Item	Function	Reference	Status	Requirement
Shared_XDM-AU-C-001	URI list structure	5.1.1	M	
Shared_XDM-AU-C-002	Application Unique ID in URI list	5.1.2	M	
Shared_XDM-AU-C-003	XML schema of URI list	5.1.4	M	
Shared_XDM-AU-C-004	URI list conforms to MIME type	5.1.5	M	
Shared_XDM-AU-C-005	Validation constraints, in addition to the XML schema	5.1.6	M	
Shared_XDM-AU-C-006	Data semantics of URI list	5.1.7	M	
Shared_XDM-AU-C-007	Naming conventions for URI list	5.1.8	M	
Shared_XDM-AU-C-008	Default name space for URI list and also Group Usage List	5.1.3, 5.2.3	O	
Shared_XDM-AU-C-009	Group Usage List document structure	5.2.1	O	
Shared_XDM-AU-C-010	Application Unique ID in Group Usage List document	5.2.2	O	
Shared_XDM-AU-C-011	XML schema of Group Usage List document	5.2.4	O	
Shared_XDM-AU-C-012	Group Usage List document conforms to MIME type	5.2.5	O	
Shared_XDM-AU-C-013	Validation constraints, in addition to the XML schema	5.2.6	O	
Shared_XDM-AU-C-014	Data semantics of Group Usage List	5.2.7	O	

Item	Function	Reference	Status	Requirement
Shared_XDM-AU-C-015	Naming conventions for Group Usage List	5.2.8	O	



## Appendix B. Examples

(Informative)

### B.1 Manipulating URI Lists

#### B.1.1 Obtaining URI Lists

Figure B.1.1 describes how an XDM client obtains URI lists.




Figure B.1.1 XDM Client obtains URI lists

The details of the flows are as follows:

- 1) The user “sip:ronald.underwood@example.com” wants to obtain the document describing his URI Lists. For this purpose the XDMC sends a HTTP GET request to the Aggregation Proxy. Two main lists exist and one sublist. The sublist with the name “close-friends” is referenced from the poc group document “mypocgroup1” in the application usage org.openmobilealliance.poc-groups.

```

GET http://xcap.example.com/services/resource-lists/users/sip:ronald.underwood@example.com/index
/HTTP/1.1
...
Content-Length: 0
  
```

- 2) Based on the AUID, the Aggregation Proxy forwards the request to Shared XDMS.
- 3) After the Shared XDMS has performed the necessary authorisation checks on the request originator, the Shared XDMS sends an HTTP “200 OK” response including the requested document in the body.

```

HTTP/1.1 200 OK
Etag: "eti87"
...
Content-Type: application/resource-lists+xml

<?xml version="1.0" encoding="UTF-8"?>
<resource-lists xmlns="urn:ietf:params:xml:ns:resource-lists"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:oa="urn:oma:params:ns:resource-list:appusage">
  <list name="oma_buddylist">

    <list name="close-friends">
      <display-name>Close Friends</display-name>
      <entry uri="sip:hermione.blossom@example.com">
        <display-name>Hermione</display-name>
      </entry>
      <entry uri="tel:5678;phone-context="+43012349999"/>
      <oa:appusages>
        <oa:nodeuri oa:uri="http://xcap.example.com/service/org.openmobilealliance.poc-
groups/mypocgroup1/~/group/list/list-
service/list/external%5b@anchor=%22http://xcap.example.com/service/resource-
lists/users/sip:ronald.underwood@example.com/index/~/resource-
lists/list%5b@name=%22oma_buddylist%22%5d/list%5b@name=%22close-friends%22%5d%5d"
oa:auid="org.openmobilealliance.poc-groups"/>
      </oa:appusages>
    </list>
  </list>
  
```

```

<entry uri="sip:joe.blogs@example.com">
  <display-name>Joe</display-name>
</entry>

</list>
<list name="oma_blockedcontacts">
</list>
</resource-lists>

```

- 4) The Aggregation Proxy routes the response to the XDM Client.

## B.1.2 Obtaining Group Usage Lists

Figure B.1.2 describes how an XDM client obtains Group Usage lists.




Figure B.1.2 XDM Client obtains Group Usage lists

The details of the flows are as follows:

- 1) The user “sip:ronald.underwood@example.com” wants to obtain a document describing his Group Usage Lists. For this purpose the XDMC sends a HTTP GET request to the Aggregation Proxy.

```

GET http://xcap.example.com/services/org.openmobilealliance.group-usage-
list/users/sip:ronald.underwood@example.com/index/HTTP/1.1
...
Content-Length: 0

```

- 2) Based on the AUID, the Aggregation Proxy forwards the request to Shared XDMS.
- 3) After the Shared XDMS has performed the necessary authorisation checks on the request originator, the Shared XDMS sends an HTTP “200 OK” response including the requested document in the body.

```

HTTP/1.1 200 OK
Etag: "eti87"
...
Content-Type: application/vnd.oma.group-usage-list+xml

<?xml version="1.0" encoding="UTF-8"?>
<resource-lists xmlns="urn:ietf:params:xml:ns:resource-lists"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:ou="urn:oma:params:xml:ns:resource-list:oma-uriusage"
  xmlns:opu="urn:oma:params:xml:ns:oma-pocusage">
<list name="bookmarkedPoCGroups">
  <entry uri="sip:group1_joeblogs@example.com">
    <display-name>Joe's golf friends</display-name>
    <ou:uriusages>
      <opu:pocusage>chat</opu:pocusage>
    </ou:uriusages>
  </entry>
  <entry uri="sip:group1_bob@example.com">
    <display-name>Bob's ski friends</display-name>
    <ou:uriusages>
      <opu:pocusage>prearranged</opu:pocusage>
    </ou:uriusages>

```

```
</entry>
</list>
</resource-lists>
```

- 4) The Aggregation Proxy routes the response to the XDM Client.

## Appendix C. Change History

(Informative)

### C.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version

### C.2 Draft/Candidate Version 1.0 History

Document Identifier	Date	Sections	Description
Draft Version OMA-Shared_XDM_Specification-V1_0	27 Sept 2004	All	Initial version created
	08 Oct 2004	All	Incorporates OMA-PAG-2004-0515R01-Initial-text-for-Shared-XDM-Specification
	15 Oct 2004	Appendix B	Incorporated OMA-PAG-2004-0535-Shared-XDMS-MessageFlowExample
	15 Oct 2004	Section 5	Incorporated OMA-PAG-2004-0546-Changes-to-Section-5-of-the-Shared-XDM-Spec
	29 Oct 2004	3.2	Incorporated OMA-PAG-0594R01-XDM-Specs-Definition-of-Global-Documents
	29 Oct 2004	Appendix A	Incorporated OMA-PAG-2004-0619-Shared-XDM-SCR
	13 Nov 2004	Appendix B And Section 5	Incorporated OMA-PAG-2004- 0706-Shared-XDM-Remove-5.1and5.2
	15 Nov 2004	Appendix A	Incorporated OMA-PAG-2004-0729-Shared-XDM-Spec-SCR-changes
	17 Nov 2004	General	Editorial cleanup
	29 Jan 2005	XDM CONRR items	All agreed comments in XDM CONRR chapter 5 All editorial comments in XDM CONRR chapter 5 OMA-PAG-2005-0050R01 OMA-PAG-2005-0083R01
	31 Jan 2005	Chapt 4, fixed file name	OMA-PAG-2005-93,
	31 Jan 2005		Incorporated 0082R04
Candidate Version OMA-TS-XDM_Shared-V1_0	04 Feb 2004	n/a	Status changed to Candidate by TP: OMA-TP-2005-0060-XDM_1_0--for-candidate-approval
OMA-TS-XDM_Shared-V1_0	15 Apr 2005	2.1 and 5.1.3	Incorporated CR 2005-0192R01
OMA-TS-XDM_Shared-V1_0	31 May 2005	5.1.1 5.1.4 5.1.7	Incorporated CR 2005-0323R03
OMA-TS-XDM_Shared-V1_0	28 Jun 2005	2.1	Incorporated CR 2005-0364
OMA-TS-XDM_Shared-V1_0	30 Sep 2005	5.1.4	Incorporated CR 2005-0469
OMA-TS-XDM_Shared-V1_0	22 Nov 2005	2.1, 2.2, 4	Incorporated CR 2005-0569R01
OMA-TS-XDM_Shared-V1_0	22 Nov 2005	4, 5.1.1 5.1.4, 5.2 A.1, A.2	Incorporated CR 2005-0527R02
OMA-TS-XDM_Shared-V1_0	10 Jan 2006	A.1, A.2 5.1.1 5.2.4 5.2.1, 5.2.4 5.2.5, 5.2.6 5.2.7, B.1.2	Incorporated CR OMA-PAG-2005-0608 Incorporated CR OMA-PAG-2005-0627 Incorporated CR OMA-PAG-2005-0628 Incorporated CR OMA-PAG- 2005-0676
OMA-TS-XDM_Shared-V1_0	14 Feb 2006	5.1.6, 5.1.8 5.1.10	Incorporated CR OMA-PAG-2006-0008R03
OMA-TS-XDM_Shared-V1_0	18 Apr 2006	5.1.1, 5.1.4 5.1.6, 5.1.7 5.1.8, B.1.1 2.1	Inclusion of CR: OMA-PAG-2006-0097R05  OMA-PAG-2006-0203

