



# **File data object specification**

Approved Version 1.2 – 10 Jul 2006

---

**Open Mobile Alliance**  
OMA-TS-DS\_DataObjFile-V1\_2-20060710-A

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2006 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

# Contents

<b>1.</b>	<b>SCOPE</b>	<b>5</b>
<b>2.</b>	<b>REFERENCES</b>	<b>6</b>
2.1	NORMATIVE REFERENCES	6
2.2	INFORMATIVE REFERENCES	6
<b>3.</b>	<b>TERMINOLOGY AND CONVENTIONS</b>	<b>7</b>
3.1	CONVENTIONS	7
3.2	DEFINITIONS	7
3.3	ABBREVIATIONS	7
<b>4.</b>	<b>INTRODUCTION</b>	<b>8</b>
<b>5.</b>	<b>XML USAGE</b>	<b>9</b>
5.1	INCLUDING FILE OBJECT IN OTHER XML DOCUMENTS	9
5.2	XML NAMESPACES	9
5.3	XML ATTRIBUTES	9
5.4	WBXML	9
<b>6.</b>	<b>MIME USAGE</b>	<b>9</b>
<b>7.</b>	<b>DATA TYPES</b>	<b>10</b>
7.1	DATETIME	10
7.2	BOOL	10
7.3	TEXT	11
7.4	INT	11
<b>8.</b>	<b>MARK-UP LANGUAGE DESCRIPTION</b>	<b>13</b>
8.1	FILE	13
8.2	NAME	13
8.3	CREATED	13
8.4	MODIFIED	13
8.5	ACCESSED	13
8.6	ATTRIBUTES	14
8.6.1	h	14
8.6.2	s	14
8.6.3	a	14
8.6.4	d	14
8.6.5	w	15
8.6.6	r	15
8.6.7	x	15
8.7	CTTYPE	15
8.8	BODY	16
8.8.1	enc	16
8.9	SIZE	16
8.10	EXTENSION FIELDS	17
8.10.1	Unique naming	17
8.10.2	Ext	17
8.10.3	XNam	17
8.10.4	XVal	18
<b>9.</b>	<b>DTD</b>	<b>19</b>
<b>10.</b>	<b>SYNXML DATA SYNCHRONIZATION USAGE</b>	<b>21</b>
10.1	CTCAP	21
10.1.1	enc	23
10.2	DATA SYNC RECORD AND FIELD LEVEL FILTERING	23
10.2.1	File Media Object Filter	23

10.3 FILE OBJECT REPLACE EXAMPLE .....23  
APPENDIX A CHANGE HISTORY (INFORMATIVE).....25  
A.1 APPROVED VERSION HISTORY .....25

## Tables

Table 1 enc attribute values .....16

# 1. Scope

The **file** data object is presented in this document. The content-specific aspects of synchronization (filtering keywords, etc...) are listed and clarified.

## 2. References

### 2.1 Normative References

- [DSREPU] “SyncML Representation Protocol, Data Synchronization Usage”, Open Mobile Alliance, “OMA-TS-DS\_DataSyncRep-V1\_2”, [URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [ISO 8601] ISO 8601, "Data elements and interchange formats- Information interchange--Representation of dates and times", International Organization for Standardization, June, 1988.
- [RFC2045] “Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies”, N. Freed & N. Borenstein, November 1996, [URL:http://www.ietf.org/rfc/rfc2045.txt](http://www.ietf.org/rfc/rfc2045.txt)
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”. S. Bradner. March 1997. [URL:http://www.ietf.org/rfc/rfc2119.txt](http://www.ietf.org/rfc/rfc2119.txt)
- [RFC2234] “Augmented BNF for Syntax Specifications: ABNF”, D. Crocker, Ed., P. Overell, November 1997, [URL:http://www.ietf.org/rfc/rfc2234.txt](http://www.ietf.org/rfc/rfc2234.txt)
- [DSDEVDTD] “OMA DS Device Information DTD”, Open Mobile Alliance, “OMA-SUP-DS-DevInf-DTD-V1\_2”, [URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [WBXML] “WAP Binary XML Content Format Specification.” WAP Forum. [URL:http://www1.wapforum.org/tech/terms.asp?doc=WAP-192-WBXML-20010725-a.pdf](http://www1.wapforum.org/tech/terms.asp?doc=WAP-192-WBXML-20010725-a.pdf)
- [XML] “Extensible Markup Language (XML) 1.0”, World Wide Web Consortium Recommendation, [URL:http://www.w3.org/TR/REC-xml](http://www.w3.org/TR/REC-xml)

### 2.2 Informative References

## 3. Terminology and Conventions

### 3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

### 3.2 Definitions

**Data type**                      The schema used to represent a data object (e.g., text/calendar MIME content type for an iCalendar representation of calendar information or text/directory MIME content type for a vCard representation of contact information).

### 3.3 Abbreviations

OMA                      Open Mobile Alliance

## 4. Introduction

The file data object can be used to represent file which can be stored in various file systems such as FAT, HFS, UFS, etc.



## 5. XML Usage

The **file** objects are represented in a mark-up language defined by [XML]. The **file** is an XML application. The **file** DTD (Document Type Definition) defines the XML document type used to represent a **file** object. The **file** DTD can be found in Section 9, but it is not necessary to read the DTD in order to understand it.

**File** objects are specified using well-formed XML. However, the **file** need not be valid XML. That is, the **file** objects do not need to specify the XML declaration or prolog. They only need to specify the body of the XML document. This restriction allows for the **file** objects to be specified with greater terseness than well-formed, valid XML documents.

### 5.1 Including file object in other XML documents

When using the **file** object as content of another XML document element the mark-up characters MUST be properly escaped or the CDATA sections MUST be used. See [XML]specification for details on character escaping and usage of CDATA sections. See section 10.3 of this document for an example.

### 5.2 XML Namespaces

**File** objects to date have no elements that may include elements of the other namespaces.

### 5.3 XML Attributes

In order to simplify the implementation of the **file** in small devices, the **file** objects have been intentionally designed to use the XML elements only. Currently no XML attributes are being defined for **file** objects.

### 5.4 WBXML

XML can be viewed as more verbose than alternative binary representations. This is often cited as a reason why it may not be appropriate for low bandwidth network protocols. In most cases, **file** uses shortened element type. This provides a minor reduction in verbosity.

Additionally, the **file** objects can be encoded in a tokenized, binary format defined by [WBXML]. The use of [WBXML] format is external to specification of the **file** and should be transparent to any application. The combination of the use of shortened element type names and an alternative binary format makes **file** competitive, from a compressed format perspective, with alternative, but private, binary representations.

## 6. MIME Usage

The [RFC2045] Internet standard provides an industry-accepted mechanism for identifying different content types. The **file** object is identified by a MIME media type. The `application/vnd.omads-file+xml` MIME content type MUST be used to indicate the **file** Object wherever such indication is required.

## 7. Data types

The following basic data type definitions are provided for referencing from other parts of this document.

### 7.1 `datetime`

**Usage:** This value type is used to identify values that specify a precise calendar date and time of day.

**Description:**

The *datetime* data type is used to identify values that contain a precise calendar date and time of day. The format is based on the [ISO 8601] complete representation, basic format for a calendar date and time of day. The text format is a concatenation of the "date", followed by the LATIN CAPITAL LETTER T character (US-ASCII decimal 84) time designator, followed by the "time" format.

The *datetime* data type expresses time values in two forms:

The form of date and time with UTC offset **MUST NOT** be used. For example, the following is not valid for a date-time value:

```
...
<datefield>19980119T230000-0800</datefield> <!-- Invalid time format -->
...
```

#### FORM #1: DATE WITH LOCAL TIME

The date with local time form is simply a date-time value that does not contain the UTC designator nor does it reference a time zone. For example, the following represents January 18, 1998, at 11 PM:

```
...
<datefield>19980118T230000</datefield> <!-- January 18, 1998, 11 PM -->
...
```

This notation of *datetime* type is to be used by devices that have no knowledge of the time zone in which they operate. In this case, the *datetime* value that is being transferred is usually the same as the value that is being stored and shown to the user in the application UI.

#### FORM #2: DATE WITH UTC TIME

The date with UTC time, or absolute time, is identified by a LATIN CAPITAL LETTER Z suffix character (US-ASCII decimal 90), the UTC designator, appended to the time value. For example, the following represents January 19, 1998, at 0700 UTC:

```
...
<datefield>19980119T070000Z</datefield> <!-- January 19,1998,07:00 UTC -->
...
```

### 7.2 `bool`

**Usage:** To be used for Boolean type fields

**Restrictions:** A text value that MUST be either “true” to indicate Boolean “true” or “false” to indicate “false”. If the field is not present its value is assumed to be “false”.

**Example:**

```
...
<booleanfield>true</booleanfield> <!-- the field is set to "true" -->
...
```

## 7.3 text

**Usage:** To be used for textual fields

**Restrictions:** If the field is not present its value is assumed to be an empty string.

**Example:**

```
...
<textfield>Hello World!</textfield>
...
```

## 7.4 int

**Usage:** To be used for integer numeric fields.

**Restrictions:** The format for the integer values is defined here in an ABNF notation [RFC2234].

```
nonzero-digit = "1" / "2" / "3" / "4" / "5" / "6" / "7" / "8" / "9"

octal-digit = "0" / "1" / "2" / "3" / "4" / "5" / "6" / "7"

hexadecimal-digit = "0" / "1" / "2" / "3" / "4" / "5" / "6" / "7" / "8" / "9"
/
                    "a" / "b" / "c" / "d" / "e" / "f"
/
                    "A" / "B" / "C" / "D" / "E" / "F"

decimal-constant = nonzero-digit * ("0" / nonzero-digit)
hexadecimal-constant = ("0x" / "0X") 1*hexadecimal-digit
```

```
octal-constant = "0" 1*octal-digit

integer-value = *1("+" / "-") (decimal-constant / hexadecimal-constant /
octal-constant)
```

**Example:**

```
...
<negativevalue>-1234</negativevalue>
<positivevalue>1234</positivevalue>
<anotherpositivevalue>+0xffffabc5</anotherpositivevalue>
<octal>010</octal> <!-- octal value equivalent to decimal 8 -->
...
```

## 8. Mark-up Language Description

### 8.1 File

**Usage:** Indicates the beginning of the object

**Parent elements:** None

**Content model:**

```
File (name?, created?, modified?, accessed?, attributes?, ctype?, body?, size?, Ext*)
```

### 8.2 name

**Usage:** Specifies name of the file.

**Parent elements:** File

**Restrictions:** The supporters MUST support this property. The name does not include any location information (URL, path, etc.). The file name MUST NOT be an empty string.

**Content model:**

```
name (#PCDATA)
```

### 8.3 created

**Usage:** Specifies the date and time when the file was created

**Parent elements:** File

**Restrictions:** *datetime* type field as specified in section 7.1.

**Content model:**

```
created (#PCDATA)
```

### 8.4 modified

**Usage:** Specifies the date and time when the body of the file object was last changed.

**Parent elements:** File

**Restrictions:** *datetime* type field as specified in section 7.1.

**Content model:**

```
modified (#PCDATA)
```

### 8.5 accessed

**Usage:** Specifies the date and time when the body of the file object was last accessed.

**Parent elements:** File

**Restrictions:** *datetime* type field as specified in section 7.1.

**Content model:**

```
accessed (#PCDATA)
```

## 8.6 attributes

**Usage:** Specifies the state of the file system attributes of the file.

**Parent elements:** `File`

**Restrictions:**

**Content model:**

```
attributes (h?, s?, a?, d?, w?, r?, x?)
```

### 8.6.1 h

**Usage:** Specifies “hidden” attribute state.

**Parent elements:** `attributes`

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
h (#PCDATA)
```

### 8.6.2 s

**Usage:** Specifies “system” attribute state.

**Parent elements:** `attributes`

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
s (#PCDATA)
```

### 8.6.3 a

**Usage:** Specifies “archived” attribute state.

**Parent elements:** `attributes`

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
a (#PCDATA)
```

### 8.6.4 d

**Usage:** Specifies “delete” attribute state. When the “delete” attribute is set, the file can be deleted.

**Parent elements:** *attributes*

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
d (#PCDATA)
```

## 8.6.5 w

**Usage:** Specifies “writable” attribute state. If the “writable” attribute is set, the file can be written.

**Parent elements:** *attributes*

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
w (#PCDATA)
```

## 8.6.6 r

**Usage:** Specifies “readable” attribute state. If the “readable” attribute is set, it is possible to read the contents of the file.

**Parent elements:** *attributes*

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
r (#PCDATA)
```

## 8.6.7 x

**Usage:** Specifies “executable” attribute state. If the “executable” attribute is set, the contents of the file can be executed by the operating system.

**Parent elements:** *attributes*

**Restrictions:** *bool* type field as specified in section 7.2.

**Content model:**

```
x (#PCDATA)
```

## 8.7 ctype

**Usage:** Specifies the content type of the file as defined by [RFC2045].

**Parent Elements:** *File*

**Restrictions:**

**Content Model:**

```
ctype (#PCDATA)s
```

**Attributes:** *None.*

**Example:**

```
<cttype>text/plain</cttype>
```

## 8.8 body

**Usage:** contains the file body

**Parent elements:** File

**Restrictions:** The supporters MUST support this property

**Content model:**

```
body (#PCDATA)
```

### 8.8.1 enc

**Usage:** declares the mechanism used to encode the content of the element. This is used to avoid corrupting the XML content of the element with the presence of characters which do not belong to the valid ranges of characters as defined by the [XML]

**Parent elements:** body

**Restrictions:** The following table lists standard enc values that MUST be understood by the conforming implementations.

Enc	Description
“quoted-printable”	The contents of the element is encoded using quoted-printable algorithm as specified by the section 6.7 of the [RFC2045]
“base64”	The contents of the element is encoded using quoted-printable algorithm as specified by the section 6.8 of the [RFC2045]

**Table 1 enc attribute values**

If the enc attribute is not present, the content is assumed to have no encoding.

The implementations SHOULD NOT use other enc attribute values than specified in the [Table 1]. In case of other enc values the usage of these encodings MUST conform to the rules defined by the [RFC2045] for Content-Transfer-Encoding.

**Content model:**

```
body enc (CDATA #IMPLIED)
```

## 8.9 size

**Usage:** Specifies the size of the file object’s body

**Parent elements:** File



**Restrictions:** *int* type field as specified in section 7.4.

**Content model:**

```
size (#PCDATA)
```

## 8.10 Extension fields

### 8.10.1 Unique naming

If an extension field is required, the following naming convention **MUST** be followed in order to prevent undesirable field name collisions.

```
x-name          = "x-" vendorid "-" 1*(ALPHA / DIGIT / "-")          ;field name
vendorid        = 3*(ALPHA / DIGIT)                                ;Vendor identification
ALPHA           = %x41-5A / %x61-7A                                ; A-Z / a-z
DIGIT           = %x30-39                                          ; 0-9
```

### 8.10.2 Ext

**Usage:** Specifies the non-standard, experimental extensions supported by the device. The extensions are specified in terms of the XML element type name and the value.

**Parent Elements:** File

**Restrictions:** The Ext element type **MUST** specify the extension element name. It may also specify one or more enumerated values. Multiple non-standard extensions can be specified by specifying the Ext element type multiple times. This element type is optional.

**Content Model:**

```
Ext (XNam, XVal*)
```

**Attributes:** None.

**Example:** The following example specifies a non-standard extension, named "Cliver" for a fictitious company, Foo, which takes values of "5.0", "5.01" or "5.02".

```
<Ext>
  <XNam>x-Foo-Cliver</XNam>
  <XVal>5.0</XVal>
  <XVal>5.01</XVal>
  <XVal>5.02</XVal>
</Ext>
```

### 8.10.3 XNam

**Usage:** Specifies the name of one of the extension element types.

**Parent Elements:** Ext

**Restrictions:** The element type is required whenever an `Ext` element is present.

**Content Model:**

```
XNam (#PCDATA)
```

**Attributes:** None.

**Example:**

```
<Ext>  
  <XNam>x-Foo-Cliver</XNam>  
  <XVal>5.0</XVal>  
  <XVal>5.01</XVal>  
  <XVal>5.02</XVal>  
</Ext>
```

## 8.10.4 XVal

**Usage:** Specifies one of the valid values for an extension element type.

**Parent Elements:** `Ext`

**Restrictions:**

**Content Model:**

```
XVal (#PCDATA)
```

**Attributes:** None.

**Example:**

```
<Ext>  
  <XNam>x-Foo-Cliver</XNam>  
  <XVal>5.0</XVal>  
  <XVal>5.01</XVal>  
  <XVal>5.02</XVal>  
</Ext>
```

## 9. DTD

```
<!--
application/vnd.omads-file+xml V1.2 Document Type Definition

http://www.openmobilealliance.org/tech/DTD/OMA-DS-DataObjFile-DTD-V1_2.dtd

Copyright Open Mobile Alliance Ltd., 2002-2003
    All rights reserved
Terms and conditions of use are available from the
Open Mobile Alliance Ltd. web site at
http://www.openmobilealliance.org/useterms.html -->

<?xml version="1.0" encoding="UTF-8"?>
<!-- Root Element -->
<!ELEMENT File (name?, created?, modified?, accessed?, attributes?,
ctype?, body?, size?, Ext*)>

<!--: The supporters MUST support this property. The name does not include
any location information (URL, path, etc.). -->
<!ELEMENT name (#PCDATA)>

<!ELEMENT created (#PCDATA)>
<!ELEMENT modified (#PCDATA)>
<!ELEMENT accessed (#PCDATA)>

<!ELEMENT attributes (h?, s?, a?, d?, w?, r?, x?)>
<!ELEMENT h (#PCDATA)>
<!ELEMENT s (#PCDATA)>
<!ELEMENT a (#PCDATA)>
<!ELEMENT d (#PCDATA)>
<!ELEMENT w (#PCDATA)>
<!ELEMENT r (#PCDATA)>
```

```
<!ELEMENT x (#PCDATA)>

<!ELEMENT ctype (#PCDATA)>

<!ELEMENT body (#PCDATA)>
<!ATTLIST body enc CDATA #IMPLIED>
<!ELEMENT size (#PCDATA)>
<!ELEMENT Ext (XNam, XVal*)>
<!ELEMENT XNam (#PCDATA)>
<!ELEMENT XVal (#PCDATA)>

<!-- End of DTD Definition -->
```

## 10.SyncML Data Synchronization Usage

The following sections describe the content-specific recommendations for using the data synchronization [DSREPU] protocol with **file** data objects.

### 10.1 CTCap

Refer to [DSDEVDTD] for further details on the specification of the Device Information DTD.

```
<CTCap>
  <CTType> application/vnd.omads-file+xml</CTType>
  <Property>
    <PropName>name</PropName>
    <DataType>text</DataType>
    <MaxSize>260</MaxSize>
    <DisplayName>File name</DisplayName>
  </Property>
  <Property>
    <PropName>body</PropName>
    <DataType>bin</DataType>
    <MaxSize>65535</MaxSize>
    </NoTruncate>
    <DisplayName>File body</DisplayName>
    <PropParam>
      <ParamName>enc</ParamName>
      <ValEnum>base64</ValEnum>
      <ValEnum>quoted-printable</ValEnum>
    </PropParam>
  </Property>
  <Property>
    <PropName>created</PropName>
    <DataType>datetime</DataType>
    <DisplayName>Date created</DisplayName>
  </Property>
  <Property>
```

```
<PropName>modified</PropName>
<DataType>datetime</DataType>
<DisplayName>Date modified</DisplayName>
</Property>
<Property>
  <PropName>accessed</PropName>
  <DataType>datetime</DataType>
  <DisplayName>Date accessed</DisplayName>
</Property>
<Property>
  <PropName>ctype</PropName>
  <DataType>text</DataType>
  <DisplayName>File type</DisplayName>
</Property>
<Property>
  <PropName>attributes</PropName>
  <DataType>struct</DataType>
  <DisplayName>File Attributes</DisplayName>
  <PropParam>
    <ParamName>h</ParamName>
    <DataType>bool</DataType>
    <DisplayName>Hidden</DisplayName>
  </PropParam>
  <PropParam>
    <ParamName>a</ParamName>
    <DataType>bool</DataType>
    <DisplayName>Archived</DisplayName>
  </PropParam>
</Property>
</CTCap>
```

### 10.1.1 enc

The PropParam element type with the value of enc MUST utilise ValEnum element type to indicate the supported encoding algorithms. The example above illustrates a section of CTCap that lists the standard encoding algorithms as supported.

## 10.2 Data Sync Record and Field Level Filtering

### 10.2.1 File Media Object Filter

Filtering for file objects can be specified using both Record and Field elements. The set of recommended keywords to support are as follows:

```
ct-filter-keyword = <Any field that is defined for the
application/vnd.omads-file+xml content type in this document except for
the body field>
```

### 10.3 File object replace example

```
...
<Sync>
...
  <Replace>
    <CmdID>6</CmdID>
    <Meta>
      <Type xmlns='syncml:metinf'> application/vnd.omads-file+xml</Type>
    </Meta>
    <Item>
      <Source>
        <LocURI>123</LocURI>
      </Source>
      ...
      <Data><![CDATA[
        <File>
          <name>OMA-DataObject-File.doc</name>
          <created>20030807T231830</created>
          <modified>20030809T015500</modified>
          <attributes>
```

```
                <h>>false</h>
                <a>true</a>
            </attributes>
            <body enc="base64"> <!--!The content of the file goes here -
->
                ...
            </body>
        </File>]]>
    </Data>
</Item>
</Replace>
</Sync>
```



## Appendix A Change History

(Informative)

### A.1 Approved Version History

Reference	Date	Description
OMA-TS-DS_DataObjFile-V1_2-20060710-A	10 Jul 2006	Approved by TP ref#OMA-TP-2006-0239R03-INP_DS_V1_2_for_final_approval