



OMA DS Provisioning

Candidate Version 2.0 – 12 Feb 2009

Open Mobile Alliance
OMA-TS-DS_Provisioning-V2_0-20090212-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2009 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

Contents

1. SCOPE.....	4
2. REFERENCES	5
2.1 NORMATIVE REFERENCES	5
2.2 INFORMATIVE REFERENCES	5
3. TERMINOLOGY AND CONVENTIONS.....	6
3.1 CONVENTIONS	6
3.2 DEFINITIONS.....	6
3.3 ABBREVIATIONS	6
4. INTRODUCTION	7
5. TECHNOLOGY AGNOSTIC PROVISIONING DOCUMENT.....	8
APPENDIX A. W5 DOCUMENT FOR OMA CP	9
APPENDIX B. CHANGE HISTORY (INFORMATIVE).....	20
B.1 APPROVED VERSION HISTORY	20
B.2 DRAFT/CANDIDATE VERSION VERSION 2.0 HISTORY	20

1. Scope

This document specifies the OMA DS provisioning.

Please refer to [DSCONCEPTS] for further information on the OMA DS organization and history.

2. References

2.1 Normative References

- [DSCONCEPTS] “Data Synchronization Concepts and Definitions”, Open Mobile Alliance™, OMA-TS-DS_Concepts-V2_0,
[URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [RFC2119] “Keywords for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997,
[URL:http://www.ietf.org/rfc/rfc2119.txt](http://www.ietf.org/rfc/rfc2119.txt)

2.2 Informative References

None.

Please refer to [DSCONCEPTS] for the other Informative References.

3. Terminology and Conventions

3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

Any reference to components of the Data Synchronization XML Schema or XML snippets is specified in this typeface.

3.2 Definitions

Please refer to the [DSCONCEPTS] document.

3.3 Abbreviations

Please refer to the [DSCONCEPTS] document.

4. Introduction

This specification document's objective is to describe the minimum set of information that must be sent to provision an OMA DS 2.0 client. There is no intent to describe how the client is provisioned. OMA DS 2.0 relies on dedicated provisioning enablers (e.g. OMA CP, OM DM, etc.), that must provide, using their own provisioning information format, the set of information defined in this document. This set of information is designed to be technology agnostic and can be morphed into whatever format (e.g: w5) a provisioning enabler uses. Appendixes A and B present morphing examples for OMA CP 1.1 and OMA DM provisioning.

5. Technology agnostic provisioning document

This section defines the minimum set of information to be sent to provision OMA DS 2.0 client.

Appendix A. W5 document for OMA CP

(Note : This part is based n the OMA-TS-SyncML-W5AppChar-V1_2-20060316-C_draft.txt which was designed for OMA DS 1.2)

IDENTIFYING INFORMATION

#####

APPID: w5.

APPID type: OMNA.

Owner: OMA Data Synchronization Working Group.

Contact: OMA Data Synchrnonization Working Group <OMA-DS@MAIL.OPENMOBILEALLIANCE.ORG>.

Registration version: 1.

Registration timestamp: 2004-01-09.

Application description: Data Synchronization (DS).

Application reference:

OMA Data Synchronization 1.2 specifications,

URL:<http://www.openmobilealliance.org/tech/release.html>.

"SyncML Data Sync Protocol" specification,

"SyncML Server Alerted Notification" specification.

WELL-KNOWN PARAMETERS

#####

Characteristic/name: APPLICATION/APPID.

Status: Required.

Occurs: 1/1.

Default value: None.

Used values: w5.

Interpretation: N/A.

Characteristic/name: APPLICATION/NAME.

Status: Optional.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: User displayable name for synchronization server.

Characteristic/name: APPLICATION/TO-PROXY.

Status: Required if use of Proxy supported.

Occurs: 0/*.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: APPLICATION/TO-NAPID.

Status: Required if direct use of Network Access Point supported.

Occurs: 0/*.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: APPLICATION/PROVIDER-ID.

Status: Optional.

Occurs: 0/1.

Default value: None.

Used values: Server Identifier specified in OMA Data Synchronization 1.2 specifications.

Interpretation: Specifies the server identifier for data synchronization server used in the server alerted sync.

Characteristic/name: APPADDR/ADDR.

Status: Required.

Occurs: 1/1.

Default value: None.

Used values: Absolute URI.

Interpretation: Synchronization server address, which may differ based on the used transport binding. Also APPLICATION/ADDR can be used to specify the address, if the parameter APPADDR/ADDRTYPE is not used.

Characteristic/name: APPADDR/ADDRTYPE.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: PORT/PORTNBR.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: APPAUTH/AAUTHLEVEL.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values: "APPSRV", "CLIENT", "OBEX".

Interpretation:

When the value is omitted, the characteristic contains client credentials for HTTP or WSP authentication. The used values are described below.

Characteristic/name: APPAUTH/AAUTHTYPE.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values:

"HTTP-BASIC", "HTTP-DIGEST", "BASIC", "DIGEST", "X509", "SECUREID", "SAFWORD", "DIGIPASS".

Interpretation:

See descriptions below.

Characteristic/name: APPAUTH/AAUTHNAME.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: APPAUTH/AAUTHSECRET.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: APPAUTH/AAUTHDATA.

Status: Required.

Occurs: 0/1.

Default value: None.

Used values:

 Nonce value.

Interpretation:

 Contains the nonce value used in the OMA Data Synchronization authentication.

Characteristic/name: RESOURCE.

Status: Required.

Occurs: 1/*.

Default value: None.

Used values: N/A.

Interpretation: List of databases.

Characteristic/name: RESOURCE/AACCEPT.

Status: Required.

Occurs: 1/1.

Default value: None.

Used values: N/A.

Interpretation: Specifies the content type the database supports.

Characteristic/name: RESOURCE/URI.

Status: Required.

Occurs: 1/1.

Default value: None.

Used values: N/A.

Interpretation: Specifies the server database URI.

Characteristic/name: RESOURCE/NAME.

Status: Optional.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: Specifies the user displayable name for database.

Characteristic/name: RESOURCE/AAUTHTYPE.

Status: Required if Database level authentication is supported.

Occurs: 0/1.

Default value: None.

Used values: "HTTP-BASIC", "HTTP-DIGEST", "BASIC", "DIGEST", "X509", "SECUREID", "SAFWORD", "DIGIPASS".

Interpretation: See below.

Characteristic/name: RESOURCE/AAUTHNAME.

Status: Required if Database level authentication is supported.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: N/A.

Characteristic/name: RESOURCE/AAUTHSECRET.

Status: Required if Database level authentication is supported.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: N/A.

APPLICATION-SPECIFIC PARAMETERS

#####

Characteristic/name: RESOURCE/CLIURI.

Status: Optional.

Occurs: 0/1.

Default value: None.

Used values: N/A.

Interpretation: Specifies the client database URI.

Characteristic/name: RESOURCE/SYNCTYPE.

Status: Optional.

Occurs: 0/1.

Default value: "2".

Used values: "1", "2", "3", "4", "5", "6".

Interpretation: Specifies the type of synchronization to perform. See below.

PARAMETER VALUES

#####

Characteristic/name/parameter: RESOURCE/SYNCTYPE/1.

Status: Optional.

Interpretation: "Slow sync" done according to "SyncML Synchronization Protocol".

Characteristic/name/parameter: RESOURCE/SYNCTYPE/2.

Status: Optional.

Interpretation: "Two-way sync" done according to "SyncML Synchronization Protocol".

Characteristic/name/parameter: RESOURCE/SYNCTYPE/3.

Status: Optional.

Interpretation: "One-way sync from client only" done according to "SyncML Synchronization Protocol".

Characteristic/name/parameter: RESOURCE/SYNCTYPE/4.

Status: Optional.

Interpretation: " Refresh sync from client only" done according to "SyncML Synchronization Protocol".

Characteristic/name/parameter: RESOURCE/SYNCTYPE/5.

Status: Optional.

Interpretation: " One-way sync from server only" done according to "SyncML Synchronization Protocol".

Characteristic/name/parameter: RESOURCE/SYNCTYPE/6.

Status: Optional.

Interpretation: "Refresh sync from server only" done according to "SyncML Synchronization Protocol".

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/APPSRV.

Status: Required.

Interpretation:

 Credentials client uses to authenticate itself to the OMA DS Server at the DS protocol level.

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/CLIENT.

Status: Required.

Interpretation:

 Credentials server uses to authenticate itself to the OMA DS Client at the DS protocol level.

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/OBEX.

Status: Optional.

Interpretation: Client credentials for OBEX authentication.

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/HTTP-BASIC.

Status: Optional.

Interpretation: HTTP basic authentication done according to RFC 2617.

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/HTTP-DIGEST.

Status: Optional.

Interpretation: HTTP digest authentication done according to RFC 2617.

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/BASIC.

Status: Required.

Interpretation: OMA DS 'syncml:auth-basic' authentication as specified in "SyncML Representation Protocol".

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/DIGEST.

Status: Required.

Interpretation: OMA DS 'syncml:auth-md5' authentication as specified in "SyncML Representation Protocol".

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/X509.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-X509' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/SECURID.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-securid' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/SAFWORD.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-safeword' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: APPAUTH/AAUTHTYPE/DIGIPASS.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-digipass' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/HTTP-BASIC.

Status: Optional.

Interpretation: HTTP basic authentication done according to RFC 2617.

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/HTTP-DIGEST.

Status: Optional.

Interpretation: HTTP digest authentication done according to RFC 2617.

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/BASIC.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-basic' authentication as specified in "SyncML Representation Protocol".

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/DIGEST.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-md5' authentication as specified in "SyncML Representation Protocol".

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/X509.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-X509' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/SECURID.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-securid' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/SAFEWORD.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-safeword' authentication done according to "SyncML Representation Protocol".

Characteristic/name/parameter: RESOURCE/AAUTHTYPE/DIGIPASS.

Status: Optional.

Interpretation: OMA DS 'syncml:auth-digipass' authentication done according to "SyncML Representation Protocol".

EXAMPLE

#####

```
<characteristic type="APPLICATION">
  <parm name="APPID" value="w5"/>
  <parm name="NAME" value="Sync Server"/>
  <parm name="ADDR" value="http://www.syncserver.com:8080/sync"/>
  <parm name="TO-NAPID" value="INTERNET"/>
  <characteristic type="APPAUTH">
    <parm name="AAUTHTYPE" value="HTTP-DIGEST"/>
    <parm name="AAUTHNAME" value="name"/>
    <parm name="AAUTHSECRET" value="secret"/>
  </characteristic>
  <characteristic type="APPAUTH">
    <parm name="AAUTHLEVEL" value="APPSRV"/>
    <parm name="AAUTHTYPE" value="DIGEST"/>
    <parm name="AAUTHNAME" value="servername"/>
    <parm name="AAUTHSECRET" value="serversecret"/>
  </characteristic>
  <characteristic type="RESOURCE">
    <parm name="URI" value="./Contacts"/>
  </characteristic>
</characteristic>
```

```
<parm name="NAME" value="Contact DB"/>
<parm name="ACCEPT" value="text/x-vcard,text/vcard"/>
<parm name="AUTHTYPE" value="DIGEST"/>
<parm name="AUTHNAME" value="databasename"/>
<parm name="AUTHSECRET" value="databasesecret"/>
</characteristic>
<characteristic type="RESOURCE">
  <parm name="URI" value="./Calendar"/>
  <parm name="SYNCTYPE" value="6"/>
  <parm name="NAME" value="Calendar DB"/>
  <parm name="ACCEPT" value="text/x-vcalendar,text/vcal"/>
</characteristic>
</characteristic>
```

###END###

Appendix B. Change History (Informative)

B.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version

B.2 Draft/Candidate Version version 2.0 History

Document Identifier	Date	Sections	Description
Draft Versions OMA-TS-DS_Provisioning-V2_0	6 Dec 2007	2.1	Incorporated agreed CR: OMA-DS-DS_2_0-2007-0020R01-CR_Ref_Provisioning
	11 Dec 2008	Appendix B	Editorial changes: remove the empty lines and the empty appendix B
	30 Jan 2009	Cover page	Application of the 2009 template
Candidate Version OMA-TS-DS_Provisioning-V2_0	12 Feb 2009	n/a	Status changed to Candidate by TP TP ref # OMA-TP-2009-0074R01- INP_DS_V2_0_ERP_for_Candidate_Approval