



# WV-023 Client-Server Protocol DTD and Examples Version 1.1

Draft Version 01-10-2002

---

Open Mobile Alliance  
OMA-WV-CSP\_DTD-V1\_1-20021001-A

Continues the Technical Activities  
Originated in the Wireless Village Initiative



This document is considered confidential and may not be disclosed in any manner to any non-member of the Open Mobile Alliance™, unless there has been prior explicit Board approval.

This document is a work in process and is not an approved Open Mobile Alliance™ specification. This document is subject to revision or removal without notice. No part of this document may be used to claim conformance or interoperability with the Open Mobile Alliance specifications.

© 2002, Open Mobile Alliance Ltd. All rights reserved.

Terms and conditions of use are available from the Open Mobile Alliance™ Web site at <http://www.openmobilealliance.org/copyright.html>.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance™. The Open Mobile Alliance authorises you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services offered by you.

The Open Mobile Alliance™ assumes no responsibility for errors or omissions in this document. In no event shall the Open Mobile Alliance be liable for any special, indirect or consequential damages or any damages whatsoever arising out of or in connection with the use of this information.

This document is available online in PDF format at <http://www.openmobilealliance.org/>.

Known problems associated with this document are published at <http://www.openmobilealliance.org/>.

Comments regarding this document can be submitted to the Open Mobile Alliance™ in the manner published at <http://www.openmobilealliance.org/documents.html>.

Document History	
OMA-WV-CSP_DTD-V1_1-20021001-A	Current

# Contents

<b>1. SCOPE</b> .....	<b>7</b>
<b>2. REFERENCES</b> .....	<b>8</b>
<b>2.1 NORMATIVE REFERENCES</b> .....	<b>8</b>
<b>2.2 INFORMATIVE REFERENCES</b> .....	<b>9</b>
<b>3. TERMINOLOGY AND CONVENTIONS</b> .....	<b>11</b>
<b>3.1 CONVENTIONS</b> .....	<b>11</b>
<b>3.2 DEFINITIONS</b> .....	<b>11</b>
<b>3.3 ABBREVIATIONS</b> .....	<b>11</b>
<b>4. INTRODUCTION</b> .....	<b>12</b>
<b>5. THE DTD</b> .....	<b>13</b>
<b>6. THE TRANSACTIONCONTENT NAMESPACE</b> .....	<b>14</b>
<b>7. XML BINDING EXAMPLES</b> .....	<b>21</b>
<b>7.1 STATUS PRIMITIVE WITH DETAILS</b> .....	<b>21</b>
<b>7.2 POLLING-REQUEST PRIMITIVE</b> .....	<b>21</b>
<b>7.3 2-WAY LOGIN TRANSACTION</b> .....	<b>22</b>
7.3.1 Login-Request primitive .....	22
7.3.2 Login-Response primitive .....	22
<b>7.4 4-WAY LOGIN TRANSACTION</b> .....	<b>23</b>
7.4.1 Login-Request primitive .....	23
7.4.2 Login-Response primitive .....	24
7.4.3 Login-Request primitive .....	24
7.4.4 Login-Response primitive .....	25
<b>7.5 SERVICE NEGOTATION TRANSACTION</b> .....	<b>25</b>
7.5.1 Service-Request primitive .....	25
7.5.2 Service-Response primitive .....	26
<b>7.6 CLIENT CAPABILITY NEGOTATION TRANSACTION</b> .....	<b>27</b>
7.6.1 ClientCapability-Request primitive .....	27
7.6.2 ClientCapability-Response primitive .....	28
<b>7.7 LOGOUT TRANSACTION</b> .....	<b>29</b>
7.7.1 Logout-Request primitive .....	29
7.7.2 Disconnect primitive.....	29
<b>7.8 SERVER INITIATED LOGOUT TRANSACTION</b> .....	<b>30</b>
7.8.1 Disconnect primitive.....	30
<b>7.9 TIME-OUT RESET TRANSACTION</b> .....	<b>31</b>
7.9.1 KeepAlive-Request primitive.....	31
7.9.2 KeepAlive-Response primitive.....	31
<b>7.10 GET SERVICE PROVIDER INFO TRANSACTION</b> .....	<b>32</b>
7.10.1 GetSPInfo-Request primitive .....	32
7.10.2 GetSPInfo-Response primitive .....	32
<b>7.11 GENERAL SEARCH TRANSACTION</b> .....	<b>33</b>
7.11.1 Search-Request (1 <sup>st</sup> ) primitive .....	33
7.11.2 Search-Response (1 <sup>st</sup> ) primitive .....	33
7.11.3 Search-Request (continued) primitive .....	34
7.11.4 Search-Response (continued) primitive .....	35
7.11.5 StopSearch-Request primitive.....	35
7.11.6 Status primitive .....	36
<b>7.12 GENERAL INVITATION TRANSACTION</b> .....	<b>36</b>
7.12.1 Invite-Request primitive .....	36
7.12.2 Status primitive .....	37
7.12.3 InviteUser-Request primitive .....	38
7.12.4 Status primitive .....	38

7.12.5 InviteUser-Response primitive .....39

7.12.6 Status primitive .....39

7.12.7 Invite-Response primitive .....40

7.12.8 Status primitive .....41

**7.13 RECALL INVITATION TRANSACTION.....41**

7.13.1 CancelInvite-Request primitive .....41

7.13.2 Status primitive .....42

7.13.3 CancelInviteUser-Request primitive .....42

7.13.4 Status primitive .....43

**7.14 SUBSCRIBE/UNSUBSCRIBE PRESENCETRANSACTION.....44**

7.14.1 SubscribePresence-Request primitive .....44

7.14.2 Status primitive .....44

7.14.3 PresenceNotification-Request primitive .....45

7.14.4 Status primitive .....48

7.14.5 UnsubscribePresence-Request primitive .....48

7.14.6 Status primitive .....49

**7.15 GET WATCHER LIST TRANSACTION.....49**

7.15.1 GetWatcherList-Request primitive .....49

7.15.2 GetWatcherList-Response primitive .....50

**7.16 GET PRESENCE TRANSACTION.....50**

7.16.1 GetPresence-Request primitive.....50

7.16.2 GetPresence-Response primitive.....51

**7.17 REACTIVE PRESENCE AUTHORIZATION TRANSACTION.....56**

7.17.1 PresenceAuth-Request primitive .....56

7.17.2 Status primitive .....57

7.17.3 PresenceAuth-User primitive .....58

7.17.4 Status primitive .....58

**7.18 CANCEL PRESENCE AUTHORIZATION TRANSACTION.....59**

7.18.1 CancelAuth-Request primitive.....59

7.18.2 Status primitive .....59

**7.19 UPDATE PRESENCE TRANSACTION.....60**

7.19.1 UpdatePresence-Request primitive .....60

7.19.2 Status primitive .....60

**7.20 SEND MESSAGE TRANSACTION.....61**

7.20.1 SendMessage-Request primitive .....61

7.20.2 SendMessage-Response primitive .....62

**7.21 SET DELIVERY METHOD TRANSACTION.....63**

7.21.1 SetDeliveryMethod-Request primitive.....63

7.21.2 Status primitive .....63

**7.22 GET LIST OF UNDELIVERED MESSAGES TRANSACTION.....64**

7.22.1 GetMessageList-Request primitive .....64

7.22.2 GetMessageList-Response primitive .....64

**7.23 REJECTING A MESSAGE (NOTIFY/GET METHOD ONLY) TRANSACTION.....66**

7.23.1 RejectMessage-Request primitive .....66

7.23.2 Status primitive .....66

**7.24 MESSAGE NOTIFICATION (NOTIFY/GET METHOD ONLY) TRANSACTION.....67**

7.24.1 MessageNotification primitive.....67

7.24.2 Status primitive .....67

**7.25 RETRIEVING A MESSAGE (GET/NOTIFY METHOD) TRANSACTION.....68**

7.25.1 GetMessage-Request primitive .....68

7.25.2 GetMessage-Response primitive .....68

7.25.3 MessageDelivered primitive .....69

7.25.4 Status primitive .....70

**7.26 DELIVERING A MESSAGE (PUSH METHOD) TRANSACTION.....70**

7.26.1 NewMessage primitive.....70

7.26.2 MessageDelivered primitive .....71

**7.27 DELIVERY REPORT TRANSACTION.....72**

7.27.1 DeliveryReport-Request primitive .....72

7.27.2 Status primitive .....73

**7.28 FORWARD UNDELIVERED MESSAGE TRANSACTION.....73**

7.28.1 ForwardMessage-Request primitive .....73

7.28.2 Status primitive .....74

**7.29 GET BLOCKED USER LISTTRANSACTION.....75**

7.29.1 GetBlockedList-Request primitive.....75

7.29.2 GetBlockedList-Response primitive.....75

**7.30 BLOCK ENTITY TRANSACTION.....76**

7.30.1 BlockEntity-Request primitive .....76

7.30.2 Status primitive .....77

**7.31 GET LIST OF CONTACT LIST(S) TRANSACTION.....77**

7.31.1 GetList-Request primitive .....77

7.31.2 GetList-Response primitive .....78

**7.32 CREATE CONTACT LIST TRANSACTION.....78**

7.32.1 CreateList-Request primitive .....78

7.32.2 Status primitive .....79

**7.33 DELETE CONTACT LIST TRANSACTION.....80**

7.33.1 DeleteList-Request primitive .....80

7.33.2 Status primitive .....80

**7.34 RETRIEVE CONTACT LISTTRANSACTION.....81**

7.34.1 ListManage-Request primitive.....81

7.34.2 ListManage-Response primitive.....81

**7.35 ADD USERS TO CONTACT LIST TRANSACTION.....82**

7.35.1 ListManage-Request primitive.....82

7.35.2 ListManage-Response primitive.....83

**7.36 REMOVE USERS FROM CONTACT LIST TRANSACTIO N.....84**

7.36.1 ListManage-Request primitive.....84

7.36.2 ListManage-Response primitive.....84

**7.37 MODIFY PROPERTIES OF CONTACT LIST TRANSAC TION.....85**

7.37.1 ListManage-Request primitive.....85

7.37.2 ListManage-Response primitive.....85

**7.38 CREATE A TTRIBUTE LIST TRANSACTION.....86**

7.38.1 CreateAttributeList-Request primitive .....86

7.38.2 Status primitive .....87

**7.39 DELETE A TTRIBUTE LIST TRANSACTION.....87**

7.39.1 DeleteAttributeList-Request primitive .....87

7.39.2 Status primitive .....88

**7.40 GET A TTRIBUTE LIST TRANSACTION.....88**

7.40.1 GetAttributeList-Request primitive .....88

7.40.2 GetAttributeList-Response primitive .....89

**7.41 CREATE GROUP TRANSACTION.....90**

7.41.1 CreateGroup-Request primitive .....90

7.41.2 Status primitive .....91

**7.42 DELETE GROUP TRANSACTION.....92**

7.42.1 DeleteGroup-Request primitive .....92

7.42.2 Status primitive .....92

**7.43 JOIN GROUP TRANSACTIO N.....93**

7.43.1 JoinGroup-Request primitive .....93

7.43.2 JoinGroup-Response primitive .....93

**7.44 USER INITIATED LEAVE GROUP TRANSACTION.....94**

7.44.1 LeaveGroup-Request primitive.....94

7.44.2 LeaveGroup-Response primitive.....95

**7.45 SERVER INITIATED LEAVE GROUP TRANSACTION.....95**

7.45.1 LeaveGroup-Response primitive.....95

7.45.2 Status primitive .....96

**7.46 GET GROUP MEMBER LIST TRANSACTION.....96**

7.46.1	GetGroupMembers-Request primitive .....	96
7.46.2	GetGroupMembers-Response primitive .....	97
<b>7.47</b>	<b>ADD GROUP MEMBERS TO A GROUP TRANSACTION .....</b>	<b>98</b>
7.47.1	AddGroupMembers-Request primitive.....	98
7.47.2	Status primitive .....	98
<b>7.48</b>	<b>REMOVE GROUP MEMBERS FROM A GROUP TRANSACTION.....</b>	<b>99</b>
7.48.1	RemoveGroupMembers-Request primitive .....	99
7.48.2	Status primitive .....	99
<b>7.49</b>	<b>CHANGING ACCESS RIGHTS IN A GROUP TRANSACTION.....</b>	<b>100</b>
7.49.1	MemberAccess-Request primitive .....	100
7.49.2	Status primitive .....	101
<b>7.50</b>	<b>MODIFY GROUP PROPERTIES TRANSACTION.....</b>	<b>101</b>
7.50.1	GetGroupProps-Request primitive .....	101
7.50.2	GetGroupProps-Response primitive .....	102
7.50.3	SetGroupProps-Request primitive .....	103
7.50.4	Status primitive .....	104
<b>7.51</b>	<b>REJECT USER FROM GROUP TRANSACTION.....</b>	<b>104</b>
7.51.1	RejectList-Request primitive.....	104
7.51.2	RejectList-Response primitive .....	105
<b>7.52</b>	<b>SUBSCRIBE GROUP CHANGE NOTIFICATION TRANSACTION.....</b>	<b>106</b>
7.52.1	SubscribeGroupNotice-Request primitive (get).....	106
7.52.2	SubscribeGroupNotice-Response primitive .....	106
7.52.3	SubscribeGroupNotice-Request primitive (set).....	107
7.52.4	Status primitive .....	107
7.52.5	GroupChangeNotice primitive .....	108
7.52.6	Status primitive .....	109
<b>APPENDIX A.</b>	<b>STATIC CONFORMANCE REQUIREMENTS (NORMATIVE) .....</b>	<b>110</b>
<b>APPENDIX B.</b>	<b>CHANGE HISTORY (INFORMATIVE) .....</b>	<b>111</b>

# 1. Scope

The Wireless Village Instant Messaging and Presence Service (IMPS) includes four primary features:

- Presence
- Instant Messaging
- Groups
- Shared Content

Presence is the key enabling technology for IMPS. It includes client device availability (my phone is on/off, in a call), user status (available, unavailable, in a meeting), location, client device capabilities (voice, text, GPRS, multimedia) and searchable personal statuses such as mood (happy, angry) and hobbies (football, fishing, computing, dancing). Since presence information is personal, it is only made available according to the user's wishes - access control features put the control of the user presence information in the users' hands.

Instant Messaging (IM) is a familiar concept in both the mobile and desktop worlds. Desktop IM clients, two-way SMS and two-way paging are all forms of Instant Messaging. Wireless Village IM will enable interoperable mobile IM in concert with other innovative features to provide an enhanced user experience.

Groups or chat are a fun and familiar concept on the Internet. Both operators and end-users are able to create and manage groups. Users can invite their friends and family to chat in group discussions. Operators can build common interest groups where end-users can meet each other online.

Shared Content allows users and operators to setup their own storage area where they can post pictures, music and other multimedia content while enabling the sharing with other individuals and groups in an IM or chat session.

These features, taken in part or as a whole, provide the basis for innovative new services that build upon a common interoperable framework.

## 2. References

### 2.1 Normative References

- [CREQ] "Specification of WAP Conformance Requirements". Open Mobile Alliance™. WAP-221-CREQ. [URL:http://www.wapforum.org/](http://www.wapforum.org/) <to be replaced by an OMA ref when available>
- [CSP] "WV-022 Client-Server Protocol Session and Transactions Version 1.1". October 2002. [URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP-V1_1-20021001-A)
- [CSP SCR] "WV-028 Client-Server Protocol Static Conformance Requirement Version 1.1". Wireless Village initiative. October 2002. [URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP\\_SCR-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP_SCR-V1_1-20021001-A)
- [E.164] ITU-T Recommendation E.164 (05/97) The international public telecommunication numbering plan. [URL:http://www.itu.int/rec/recommendation.asp?type=items&lang=e&parent=T-REC-E.164-199705-I](http://www.itu.int/rec/recommendation.asp?type=items&lang=e&parent=T-REC-E.164-199705-I)
- [FeaFun] "WV-021 Features and Functions Version 1.1". October 2002. [URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-Features\\_Functions-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-Features_Functions-V1_1-20021001-A)
- [FIPS 180-1] "Secure Hash Standard", April 1995. [URL:http://csrc.nist.gov/fips/fip180-1.pdf](http://csrc.nist.gov/fips/fip180-1.pdf)
- [PA] "WV-029 Presence Attributes Version 1.1". October 2002. [URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-PA-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-PA-V1_1-20021001-A)
- [RFC1321] "The MD5 Message-Digest Algorithm", April 1992. [URL:http://www.ietf.org/rfc/rfc1321.txt?number=1321](http://www.ietf.org/rfc/rfc1321.txt?number=1321)
- [RFC2045] "Multipurpose Internet Mail Extensions (MIME) Part one: Format of Internet Message Bodies". Section 6.8 "Base64 Content-Transfer-Encoding". [URL:http://www.ietf.org/rfc/rfc2045.txt?number=2045](http://www.ietf.org/rfc/rfc2045.txt?number=2045)
- [RFC2046] Borenstein N., and N. Freed, "MIME (Multipurpose Internet Mail Extensions) Part Two: Media Types", November 1996. [URL:http://www.ietf.org/rfc/rfc2046.txt?number=2046](http://www.ietf.org/rfc/rfc2046.txt?number=2046)
- [RFC2119] "Keywords for using RFCs to Indicate Requirements levels", Bradner, S. [URL:http://www.ietf.org/rfc/rfc2119.txt?number=2119](http://www.ietf.org/rfc/rfc2119.txt?number=2119)
- [RFC2234] "Augmented BNF for Syntax Specifications: ABNF". D. Crocker, Ed., P. Overell. November 1997. [URL:http://www.ietf.org/rfc/rfc2234.txt](http://www.ietf.org/rfc/rfc2234.txt)
- [RFC2396] Uniform Resource Identifiers (URI): Generic Syntax. [URL:http://www.ietf.org/rfc/rfc2396.txt?number=2396](http://www.ietf.org/rfc/rfc2396.txt?number=2396)
- [RFC2426] vCard MIME Directory Profile. [URL:http://www.ietf.org/rfc/rfc2426.txt?number=2426](http://www.ietf.org/rfc/rfc2426.txt?number=2426)
- [RFC2445] Internet Calendaring and Scheduling Core Object Specification (iCalendar). [URL:http://www.ietf.org/rfc/rfc2445.txt?number=2445](http://www.ietf.org/rfc/rfc2445.txt?number=2445)
- [RFC2778] "A Model for Presence and Instant Messaging", February 2000. [URL:http://www.ietf.org/rfc/rfc2778.txt?number=2778](http://www.ietf.org/rfc/rfc2778.txt?number=2778)
- [RFC822] "Standard for the Format of ARPA Internet Text Messages", August 1982. [URL:http://www.ietf.org/rfc/rfc822.txt?number=822](http://www.ietf.org/rfc/rfc822.txt?number=822)



- [SSP SCR] "WV-035 SSP – Server-Server Protocol Static Conformance Requirement Version 1.1". Wireless Village initiative. October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP\\_SCR-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP_SCR-V1_1-20021001-A)
- [UUID] Steven Miller, "DEC/HP Network Computing Architecture Remote Procedure Call Run-Time Extension Specification Version OSF TX1.0.11", July 23, 1992
- [VCAL10] "vCalendar - The Electronic Calendaring and Scheduling Format", version 1.0, The Internet Mail Consortium (IMC), September 18, 1996, [URL:http://www.imc.org/pdi/vcal-10.doc](http://www.imc.org/pdi/vcal-10.doc)
- [VCARD21] "vCard - The Electronic Business Card", version 2.1, The Internet Mail Consortium (IMC), September 18, 1996, [URL:http://www.imc.org/pdi/vcard-21.doc](http://www.imc.org/pdi/vcard-21.doc)
- [WAPMMS] Wireless Application Protocol - MMS Encapsulation Protocol.  
[URL:http://www1.wapforum.org/tech/documents/WAP-209-MMSEncapsulation-20010601-a.pdf](http://www1.wapforum.org/tech/documents/WAP-209-MMSEncapsulation-20010601-a.pdf)
- [XML] "Extensible Markup Language 1.0 (Second Edition)", W3C recommendation, 6-October-2000.  
[URL:http://www.w3.org/TR/2000/REC-xml-20001006.pdf](http://www.w3.org/TR/2000/REC-xml-20001006.pdf)

## 2.2 Informative References

- [Arch] "WV-020 System Architecture Model Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-Arch-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-Arch-V1_1-20021001-A)
- [FeaFun] "WV-021 Features and Functions Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-Features\\_Functions-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-Features_Functions-V1_1-20021001-A)
- [CSP] "WV-022 Client-Server Protocol Session and Transactions Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP-V1_1-20021001-A)
- [CSP DTD] "WV-023 Client-Server Protocol DTD and Examples Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP\\_DTD-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP_DTD-V1_1-20021001-A)
- [CSP Trans] "WV-024 Client-Server Protocol Transport Bindings Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP\\_Transport-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP_Transport-V1_1-20021001-A)
- [CSP DataType] "WV-025 Client-Server Protocol Data Types ". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP\\_DataTypes-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP_DataTypes-V1_1-20021001-A)
- [CSP SMS] "WV-026 Client-Server Protocol SMS Binding Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP\\_SMS-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP_SMS-V1_1-20021001-A)
- [CSP WBXML] "WV-027 Client-Server Protocol Binary definition and Examples Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP\\_WBXML-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CSP_WBXML-V1_1-20021001-A)
- [CSP SCR] "WV-028 Client-Server Protocol Static Conformance Requirement Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-)

[CSP\\_SCR-V1\\_1-20021001-A](#)

- [PA] "WV-029 Presence Attributes Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-PA-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-PA-V1_1-20021001-A)
- [PA DTD] "WV-030 Presence Attribute DTD and Examples Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-PA\\_DTD-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-PA_DTD-V1_1-20021001-A)
- [CLP] "WV-031 Command Line Protocol Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CLP-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-CLP-V1_1-20021001-A)
- [SSP] "WV-032 SSP - Server-Server Protocol Semantics Document Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP-V1_1-20021001-A)
- [SSP Syntax] "WV-033 Server-Server Protocol XML Syntax Document Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP\\_SyntaxV1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP_SyntaxV1_1-20021001-A)
- [SSP Trans] "WV-034 SSP - Transport Binding Version 1.1". October 2002.  
[URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP\\_Transport-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP_Transport-V1_1-20021001-A)
- [SSP SCR] "WV-035 SSP – Server-Server Protocol Static Conformance Requirement Version 1.1". October 2002. [URL:http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP\\_SCR-V1\\_1-20021001-A](http://www.openmobilealliance.org/member/technicalPlenary/imps/docs/OMA-WV-SSP_SCR-V1_1-20021001-A)
- [WAPARCH] "WAP Architecture". Open Mobile Alliance™. WAP-210-WAPArch.  
[URL:http://www.wapforum.org/](http://www.wapforum.org/)

## 3. Terminology and Conventions

### 3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

### 3.2 Definitions

None

### 3.3 Abbreviations

None

## 4. Introduction

This document describes how XML is utilized to carry Wireless Village primitives and the information elements within.

The document provides the DTD and the TransactionContent namespace as well as examples of each transaction.

Binary content cannot be included in the XML document directly, because it may invalidate the document. Thus, the binary content must be encoded with the BASE64 encoding algorithm, as defined in [RFC2045].

If an optional informational element, or a conditional information element where the conditions is false, is omitted in the CSP primitive, it should be omitted from XML representation as well where applicable.

## 5. The DTD

```

<!--
WV CSP (WV-CSP) V1.1 Document Type Definition

Copyright Open Mobile Alliance Ltd., 2002
All rights reserved

WV-CSP is an XML language. Typical usage:
  <?xml version="1.0"?>
  <!DOCTYPE CSP PUBLIC "-//OMA//DTD WV-CSP 1.1//EN"
    "http://www.openmobilealliance.org/DTD/WV-CSP.XML"
    [<?oma-wv-csp-ver supported-versions="1.1"?>]>
  <WV-CSP>
    ...
  </WV-CSP>

```

Terms and conditions of use are available from the Open Mobile Alliance Ltd. web site at <http://www.openmobilealliance.org/useterms.html>

```

<?xml version="1.0" encoding="UTF-8"?>
<!ELEMENT WV-CSP-Message (Session)>
<!ATTLIST WV-CSP-Message xmlns CDATA #REQUIRED>

<!ELEMENT Session (SessionDescriptor, Transaction+)>

<!ELEMENT SessionDescriptor (SessionType, SessionID?)>
<!ELEMENT SessionType (#PCDATA)>
<!ELEMENT SessionID (#PCDATA)>

<!ELEMENT Transaction (TransactionDescriptor, TransactionContent)>
<!ELEMENT TransactionDescriptor (TransactionMode, TransactionID?,
  Poll?)>
<!ELEMENT TransactionMode (#PCDATA)>
<!ELEMENT TransactionID (#PCDATA)>
<!ELEMENT Poll (#PCDATA)>

<!ELEMENT TransactionContent (#PCDATA)>
<!ATTLIST TransactionContent xmlns CDATA #REQUIRED>

```

## 6. The TransactionContent namespace

```
<?xml version="1.0" encoding="UTF-8"?>
<!ELEMENT TransactionContent (Status | Polling-Request | Login-Request
| Login-Response | Service-Request | Service-Response |
ClientCapability-Request | ClientCapability-Response | Logout-
Request | Disconnect | KeepAlive-Request | KeepAlive-Response |
GetSPInfo-Request | GetSPInfo-Response | Search-Request | Search-
Response | StopSearch-Request | Invite-Request | Invite-Response |
InviteUser-Request | InviteUser-Response | CancelInvite-Request |
CancelInviteUser-Request | SubscribePresence-Request |
UnsubscribePresence-Request | PresenceNotification-Request |
GetWatcherList-Request | GetWatcherList-Response | GetPresence-
Request | GetPresence-Response | PresenceAuth-Request |
PresenceAuth-User | CancelAuth-Request | UpdatePresence-Request |
SendMessage-Request | SendMessage-Response | SetDeliveryMethod-
Request | GetMessageList-Request | GetMessageList-Response |
RejectMessage-Request | MessageNotification | GetMessage-Request |
GetMessage-Response | NewMessage | MessageDelivered |
DeliveryReport-Request | ForwardMessage-Request | GetBlockedList-
Request | GetBlockedList-Response | BlockEntity-Request | GetList-
Request | GetList-Response | CreateList-Request | DeleteList-
Request | ListManage-Request | ListManage-Response |
CreateAttributeList-Request | DeleteAttributeList-Request |
GetAttributeList-Request | GetAttributeList-Response | CreateGroup-
Request | DeleteGroup-Request | JoinGroup-Request | JoinGroup-
Response | LeaveGroup-Request | LeaveGroup-Response |
GetGroupMembers-Request | GetGroupMembers-Response |
AddGroupMembers-Request | RemoveGroupMembers-Request |
MemberAccess-Request | GetGroupProps-Request | GetGroupProps-
Response | SetGroupProps-Request | RejectList-Request | RejectList-
Response | SubscribeGroupNotice-Request | SubscribeGroupNotice-
Response | GroupChangeNotice)>

<!ELEMENT Status (Result, ClientID?)>
<!ELEMENT Polling-Request EMPTY>
<!ELEMENT Login-Request (UserID, ClientID, Password?, DigestBytes?,
DigestSchema?, TimeToLive?, SessionCookie)>
<!ELEMENT Login-Response (ClientID, Result, Nonce?, DigestSchema?,
SessionID?, KeepAliveTime?, CapabilityRequest?)>
<!ELEMENT Service-Request (ClientID, Functions, AllFunctionsRequest)>
<!ELEMENT Service-Response (ClientID, Functions?, AllFunctions?)>
<!ELEMENT ClientCapability-Request (ClientID, CapabilityList)>
<!ELEMENT ClientCapability-Response (ClientID, CapabilityList)>
<!ELEMENT Logout-Request EMPTY>
<!ELEMENT Disconnect (Result)>
<!ELEMENT KeepAlive-Request (TimeToLive?)>
<!ELEMENT KeepAlive-Response (Result, KeepAliveTime?)>
<!ELEMENT GetSPInfo-Request (ClientID?)>
<!ELEMENT GetSPInfo-Response (ClientID?, Name, Logo?,
Description?,URL?)>
<!ELEMENT Search-Request (SearchPairList*, SearchLimit?, SearchID?,
SearchIndex?)>
```

```
<!ELEMENT StopSearch-Request (SearchID)>
<!ELEMENT Search-Response (SearchID?, SearchFindings, CompletionFlag,
  SearchIndex, SearchResult?)>
<!ELEMENT CompletionFlag (#PCDATA)>
<!ELEMENT Invite-Request (InviteID, InviteType, Recipient, GroupID?,
  PresenceSubList?, URLList?, InviteNote?, ScreenName?, Validity?)>
<!ELEMENT Invite-Response (InviteID, Acceptance, Sender,
  ResponseNote?)>
<!ELEMENT InviteUser-Request (InviteID, InviteType, Sender, GroupID?,
  PresenceSubList?, URLList?, InviteNote?, Validity?)>
<!ELEMENT InviteUser-Response (InviteID, Acceptance, ResponseNote?,
  ScreenName?)>
<!ELEMENT CancelInvite-Request (InviteID, Recipient, InviteNote?,
  URLList?, ScreenName?)>
<!ELEMENT CancelInviteUser-Request (InviteID, Sender, InviteNote?,
  URLList?)>

<!ELEMENT SubscribePresence-Request (User*, ContactList*,
  PresenceSubList?)>
<!ELEMENT UnsubscribePresence-Request (User*, ContactList*)>
<!ELEMENT PresenceNotification-Request (Presence+)>
<!ELEMENT GetWatcherList-Request EMPTY>
<!ELEMENT GetWatcherList-Response (User*)>
<!ELEMENT GetPresence-Request ((User+ | ContactList+),
  PresenceSubList?)>
<!ELEMENT GetPresence-Response (Result, Presence*)>
<!ELEMENT PresenceAuth-Request (UserID, PresenceSubList?)>
<!ELEMENT PresenceAuth-User (UserID, Acceptance)>
<!ELEMENT CancelAuth-Request (UserID)>
<!ELEMENT UpdatePresence-Request (PresenceSubList)>

<!ELEMENT GetList-Request EMPTY>
<!ELEMENT GetList-Response (ContactList*, DefaultContactList?)>
<!ELEMENT CreateList-Request (ContactList, NickList?,
  ContactListProperties?)>
<!ELEMENT DeleteList-Request (ContactList)>
<!ELEMENT ListManage-Request (ContactList, (AddNickList |
  RemoveNickList | ContactListProperties?))>
<!ELEMENT ListManage-Response (Result, NickList?,
  ContactListProperties?)>
<!ELEMENT CreateAttributeList-Request (PresenceSubList, UserID*,
  ContactList*, DefaultList)>
<!ELEMENT DeleteAttributeList-Request (UserID*, ContactList*,
  DefaultList)>
<!ELEMENT GetAttributeList-Request (DefaultList, ContactList*, User*)>
<!ELEMENT GetAttributeList-Response (Result, DefaultAttributeList?,
  Presence*)>

<!ELEMENT SendMessage-Request (DeliveryReport, MessageInfo,
  ContentData?)>
<!ELEMENT SendMessage-Response (Result, MessageID?)>
<!ELEMENT SetDeliveryMethod-Request (DeliveryMethod,
  AcceptedContentLength?, GroupID?)>
```

```

<!ELEMENT GetMessageList-Request (GroupID?, MessageCount?)>
<!ELEMENT GetMessageList-Response (MessageInfo*)>
<!ELEMENT RejectMessage-Request (MessageID+)>
<!ELEMENT MessageNotification (MessageInfo)>
<!ELEMENT GetMessage-Request (MessageID)>
<!ELEMENT GetMessage-Response (MessageInfo, ContentData?)>
<!ELEMENT NewMessage (MessageInfo, ContentData?)>
<!ELEMENT MessageDelivered (MessageID)>
<!ELEMENT DeliveryReport-Request (Result, DeliveryTime?, MessageInfo)>
<!ELEMENT DeliveryTime (#PCDATA)>
<!ELEMENT ForwardMessage-Request (MessageID, Recipient)>
<!ELEMENT GetBlockedList-Request EMPTY>
<!ELEMENT GetBlockedList-Response (BlockList?, GrantList?)>
<!ELEMENT BlockEntity-Request (BlockList?, GrantList?)>

<!ELEMENT CreateGroup-Request (GroupID, GroupProperties, JoinGroup,
  ScreenName?, SubscribeNotification)>
<!ELEMENT DeleteGroup-Request (GroupID)>
<!ELEMENT JoinGroup-Request (GroupID, ScreenName?, JoinedRequest,
  SubscribeNotification)>
<!ELEMENT JoinGroup (#PCDATA)>
<!ELEMENT SubscribeNotification (#PCDATA)>
<!ELEMENT JoinGroup-Response (UserList?, WelcomeNote?)>
<!ELEMENT LeaveGroup-Request (GroupID)>
<!ELEMENT LeaveGroup-Response (GroupID?, Result)>
<!ELEMENT GetGroupMembers-Request (GroupID)>
<!ELEMENT GetGroupMembers-Response (Admin?, Mod?, Users?)>
<!ELEMENT AddGroupMembers-Request (GroupID, UserList)>
<!ELEMENT RemoveGroupMembers-Request (GroupID, UserList)>
<!ELEMENT MemberAccess-Request (GroupID, Admin?, Mod?, Users?)>
<!ELEMENT GetGroupProps-Request (GroupID)>
<!ELEMENT GetGroupProps-Response (GroupProperties, OwnProperties)>
<!ELEMENT SetGroupProps-Request (GroupID, GroupProperties?,
  OwnProperties?)>
<!ELEMENT RejectList-Request (GroupID, AddList?, RemoveList?)>
<!ELEMENT RejectList-Response (UserList?)>
<!ELEMENT SubscribeGroupNotice-Request (GroupID, SubscribeType)>
<!ELEMENT SubscribeGroupNotice-Response (Value)>
<!ELEMENT GroupChangeNotice (GroupID, Joined?, Left?,
  GroupProperties?, OwnProperties?)>

<!ELEMENT DigestBytes (#PCDATA)>
<!ELEMENT DigestSchema (#PCDATA)>
<!ELEMENT Password (#PCDATA)>
<!ELEMENT Nonce (#PCDATA)>
<!ELEMENT CapabilityRequest (#PCDATA)>
<!ELEMENT CapabilityList (ClientType, InitialDeliveryMethod,
  ((AnyContent, AcceptedCharSet*) | AcceptedContentType*),
  AcceptedTransferEncoding*, AcceptedContentLength, SupportedBearer*,
  MultiTrans, ParserSize, SupportedCIRMethod*, UDPPort?, TCPAddress?,
  TCPPort?, ServerPollMin?, DefaultLanguage?)>
<!ELEMENT ClientType (#PCDATA)>
<!ELEMENT InitialDeliveryMethod (#PCDATA)>

```



```
<!ELEMENT AnyContent (#PCDATA)>
<!ELEMENT AcceptedCharSet (#PCDATA)>
<!ELEMENT AcceptedContentType (#PCDATA)>
<!ELEMENT AcceptedTransferEncoding (#PCDATA)>
<!ELEMENT AcceptedContentLength (#PCDATA)>
<!ELEMENT SupportedBearer (#PCDATA)>
<!ELEMENT MultiTrans (#PCDATA)>
<!ELEMENT ParserSize (#PCDATA)>
<!ELEMENT SupportedCIRMethod (#PCDATA)>
<!ELEMENT UDPPort (#PCDATA)>
<!ELEMENT TCPAddress (#PCDATA)>
<!ELEMENT TCPPort (#PCDATA)>
<!ELEMENT ServerPollMin (#PCDATA)>
<!ELEMENT DefaultLanguage (#PCDATA)>

<!ELEMENT Result (Code, Description?, DetailedResult*)>
<!ELEMENT Code (#PCDATA)>
<!ELEMENT Description (#PCDATA)>
<!ELEMENT DetailedResult (Code, Description?, UserID*, GroupID*,
  ScreenName*, MessageID*)>

<!ELEMENT SessionCookie (#PCDATA)>
<!ELEMENT Sender (User | Group)>
<!ELEMENT Recipient (User*, Group*, ContactList*)>
<!ELEMENT User (UserID, ClientID?)>
<!ELEMENT Group (GroupID | ScreenName)>
<!ELEMENT UserID (#PCDATA)>
<!ELEMENT ClientID (URL?, MSISDN?)>
<!ELEMENT GroupID (#PCDATA)>
<!ELEMENT MessageID (#PCDATA)>
<!ELEMENT MessageURI (#PCDATA)>
<!ELEMENT ScreenName (SName, GroupID)>
<!ELEMENT NickName (Name, UserID)>
<!ELEMENT URLList (URL+)>
<!ELEMENT URL (#PCDATA)>
<!ELEMENT MSISDN (#PCDATA)>
<!ELEMENT GroupList (GroupID+)>
<!ELEMENT UserList (User*, ScreenName*)>
<!ELEMENT ContactList (#PCDATA)>
<!ELEMENT DefaultContactList (#PCDATA)>
<!ELEMENT NickList ((NickName | UserID)*)>
<!ELEMENT AddNickList ((NickName | UserID)*)>
<!ELEMENT RemoveNickList (UserID+)>
<!ELEMENT DefaultList (#PCDATA)>

<!ELEMENT SearchPairList (SearchElement, SearchString)>
<!ELEMENT SearchElement (#PCDATA)>
<!ELEMENT SearchString (#PCDATA)>
<!ELEMENT SearchLimit (#PCDATA)>
<!ELEMENT SearchID (#PCDATA)>
<!ELEMENT SearchIndex (#PCDATA)>
<!ELEMENT SearchFindings (#PCDATA)>
<!ELEMENT SearchResult (UserList?, GroupList?)>
```

```
<!ELEMENT InviteID (#PCDATA)>
<!ELEMENT InviteType (#PCDATA)>
<!ELEMENT InviteNote (#PCDATA)>
<!ELEMENT Acceptance (#PCDATA)>
<!ELEMENT ResponseNote (#PCDATA)>

<!ELEMENT DefaultAttributeList (PresenceSubList*)>
<!ELEMENT Presence ((UserID | ContactList), PresenceSubList*)>
<!ELEMENT PresenceSubList (#PCDATA)>
<!ATTLIST PresenceSubList xmlns CDATA #REQUIRED
                        xmlns:Ext CDATA #IMPLIED>

<!ELEMENT KeepAliveTime (#PCDATA)>
<!ELEMENT TimeToLive (#PCDATA)>

<!ELEMENT SName (#PCDATA)>
<!ELEMENT Name (#PCDATA)>
<!ELEMENT Value (#PCDATA)>

<!ELEMENT Validity (#PCDATA)>

<!ELEMENT MessageInfo (MessageID?, MessageURI?, ContentType?,
                        ContentEncoding?, ContentSize, Recipient, Sender, DateTime?,
                        Validity?)>
<!ELEMENT DateTime (#PCDATA)>
<!ELEMENT MessageCount (#PCDATA)>

<!ELEMENT DeliveryReport (#PCDATA)>
<!ELEMENT DeliveryMethod (#PCDATA)>

<!ELEMENT BlockList (InUse?,(EntityList| (AddList?, RemoveList?)))>
<!ELEMENT GrantList (InUse?,(EntityList| (AddList?, RemoveList?)))>
<!ELEMENT EntityList (UserID*, ScreenName*, GroupID*)>
<!ELEMENT AddList (UserID*, ScreenName*, GroupID*)>
<!ELEMENT RemoveList (UserID*, ScreenName*, GroupID*)>
<!ELEMENT InUse (#PCDATA)>

<!ELEMENT ContactListProperties (Property+)>
<!ELEMENT GroupProperties (Property+, WelcomeNote?)>
<!ELEMENT OwnProperties (Property+)>
<!ELEMENT Property (Name, Value?)>
<!ELEMENT WelcomeNote (ContentType, ContentEncoding?, ContentData)>

<!ELEMENT JoinedRequest (#PCDATA)>

<!ELEMENT Admin (UserList)>
<!ELEMENT Mod (UserList)>
<!ELEMENT Users (UserList)>

<!ELEMENT SubscribeType (#PCDATA)>
<!ELEMENT Joined (UserList)>
<!ELEMENT Left (UserList)>
```

```
<!ELEMENT Logo (ContentType, ContentSize?, ContentEncoding,
  ContentData)>
<!ELEMENT ContentType (#PCDATA)>
<!ELEMENT ContentData (#PCDATA)>
<!ELEMENT ContentSize (#PCDATA)>
<!ELEMENT ContentEncoding (#PCDATA)>

<!ELEMENT AllFunctionsRequest (#PCDATA)>
<!ELEMENT AllFunctions (WVCSPFeat)>
<!ELEMENT Functions (WVCSPFeat)>
<!ELEMENT WVCSPFeat (FundamentalFeat?, PresenceFeat?, IMFeat?,
  GroupFeat?)>

<!ELEMENT FundamentalFeat (ServiceFunc?, SearchFunc?, InviteFunc?)>
<!ELEMENT PresenceFeat (ContListFunc?, PresenceAuthFunc?,
  PresenceDeliverFunc?, AttListFunc?)>
<!ELEMENT IMFeat (IMSendFunc?, IMReceiveFunc?, IMAuthFunc?)>
<!ELEMENT GroupFeat (GroupMgmtFunc?, GroupUseFunc?, GroupAuthFunc?)>

<!ELEMENT ServiceFunc (GETSPI?)>
<!ELEMENT SearchFunc (SRCH?, STSRC?)>
<!ELEMENT InviteFunc (INVIT?, CAINV?)>

<!ELEMENT ContListFunc (GCLI?, CCLI?, DCLI?, MCLS?)>
<!ELEMENT PresenceAuthFunc (GETWL?, REACT?, CAAUT?)>
<!ELEMENT PresenceDeliverFunc (GETPR?, UPDPR?)>
<!ELEMENT AttListFunc (CALI?, DALI?, GALS?)>

<!ELEMENT IMSendFunc (MDELIV?, FWMSG?)>
<!ELEMENT IMReceiveFunc (SETD?, GETLM?, GETM?, REJCM?, NOTIF?, NEWM?)>
<!ELEMENT IMAuthFunc (GLBLU?, BLENT?)>

<!ELEMENT GroupMgmtFunc (CREAG?, DELGR?, GETGP?, SETGP?)>
<!ELEMENT GroupUseFunc (SUBGCN?, GRCHN?)>
<!ELEMENT GroupAuthFunc (GETGM?, ADDGM?, RMVGM?, MBRAC?, REJEC?)>

<!ELEMENT GETSPI EMPTY>
<!ELEMENT SRCH EMPTY>
<!ELEMENT STSRC EMPTY>
<!ELEMENT INVIT EMPTY>
<!ELEMENT CAINV EMPTY>

<!ELEMENT GCLI EMPTY>
<!ELEMENT CCLI EMPTY>
<!ELEMENT DCLI EMPTY>
<!ELEMENT MCLS EMPTY>
<!ELEMENT GETWL EMPTY>
<!ELEMENT REACT EMPTY>
<!ELEMENT CAAUT EMPTY>
<!ELEMENT GETPR EMPTY>
<!ELEMENT UPDPR EMPTY>
<!ELEMENT CALI EMPTY>
```

<!ELEMENT DALI EMPTY>  
<!ELEMENT GALS EMPTY>

<!ELEMENT MDELIV EMPTY>  
<!ELEMENT FWMSG EMPTY>  
<!ELEMENT SETD EMPTY>  
<!ELEMENT GETLM EMPTY>  
<!ELEMENT GETM EMPTY>  
<!ELEMENT REJCM EMPTY>  
<!ELEMENT NOTIF EMPTY>  
<!ELEMENT NEWM EMPTY>  
<!ELEMENT GLBLU EMPTY>  
<!ELEMENT BLENT EMPTY>

<!ELEMENT CREAG EMPTY>  
<!ELEMENT DELGR EMPTY>  
<!ELEMENT GETGP EMPTY>  
<!ELEMENT SETGP EMPTY>  
<!ELEMENT SUBGCN EMPTY>  
<!ELEMENT GRCHN EMPTY>  
<!ELEMENT GETGM EMPTY>  
<!ELEMENT ADDGM EMPTY>  
<!ELEMENT RMVGM EMPTY>  
<!ELEMENT MBRAC EMPTY>  
<!ELEMENT REJEC EMPTY>

## 7. XML Binding Examples

### 7.1 Status primitive with details

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>201</Code>
            <Description>Partially successful.</Description>
            <DetailedResult>
              <Code>531</Code>
              <Description>Unknown user.</Description>
              <UserID>wv:bad_user1@im.com</UserID>
              <UserID>wv:bad_user2@im.com</UserID>
            </DetailedResult>
            <DetailedResult>
              <Code>532</Code>
              <Description>Blocked.</Description>
              <UserID>wv:bad_user3@im.com</UserID>
              <UserID>wv:bad_user4@im.com</UserID>
            </DetailedResult>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.2 Polling-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>

```

```

    <TransactionMode>Request</TransactionMode>
    <TransactionID/>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <Polling-Request/>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.3 2-way Login transaction

### 7.3.1 Login-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Login-Request>
          <UserID>wv:user@im.com</UserID>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
          <Password>1my2pass3word</Password>
          <TimeToLive>120</TimeToLive>
          <SessionCookie>im.user.com#20011224#328746293
          </SessionCookie>
        </Login-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.3.2 Login-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>

```

```

    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <Login-Response>
      <ClientID>
        <URL>http://206.226.10.25:80/IMPSAPP</URL>
      </ClientID>
      <Result>
        <Code>200</Code>
        <Description>Successfully logged in.</Description>
      </Result>
      <SessionID>im.user.com#48815@server.com</SessionID>
      <KeepAliveTime>120</KeepAliveTime>
      <CapabilityRequest>T</CapabilityRequest>
    </Login-Response>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.4 4-way Login transaction

### 7.4.1 Login-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Login-Request>
          <UserID>wv:user@im.com</UserID>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
          <DigestSchema>PWD,SHA,MD4,MD5,MD6</DigestSchema>
          <SessionCookie>im.user.com#20011224#328746293
          </SessionCookie>
        </Login-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.4.2 Login-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Login-Response>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
          <Result>
            <Code>200</Code>
            <Description>Successfully logged in.</Description>
          </Result>
          <Nonce>92387rhf934fho3fh9fkn309fn3pfun304ufn3</Nonce>
          <DigestSchema>MD6</DigestSchema>
          <CapabilityRequest>F</CapabilityRequest>
        </Login-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.4.3 Login-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Login-Request>
          <UserID>wv:user@im.com</UserID>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
        </Login-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```



```

    <DigestBytes>alkkuayfdsAKDSJfsdf jhksadhlkasdlkfgsal
  </DigestBytes>
  <TimeToLive>120</TimeToLive>
  <SessionCookie>im.user.com#20011224#328746293
  </SessionCookie>
</Login-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.4.4 Login-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Login-Response>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
          <Result>
            <Code>200</Code>
            <Description>Successfully logged in.</Description>
          </Result>
          <SessionID>im.user.com#48815@server.com</SessionID>
          <KeepAliveTime>120</KeepAliveTime>
          <CapabilityRequest>T</CapabilityRequest>
        </Login-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.5 Service negotiation transaction

### 7.5.1 Service-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>

```

```

    <SessionID>im.user.com#48815@server.com</SessionID>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Request</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Service-Request>
        <ClientID>
          <URL>http://206.226.10.25:80/IMPSAPP</URL>
        </ClientID>
        <Functions>
          <WCSPFeat>
            <FundamentalFeat/>
            <PresenceFeat/>
            <IMFeat/>
          </WCSPFeat>
        </Functions>
        <AllFunctionsRequest>T</AllFunctionsRequest>
      </Service-Request>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.5.2 Service-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Service-Response>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
          <Functions>
            <WCSPFeat>
              <FundamentalFeat>
                <SearchFunc/>
              </FundamentalFeat>

```

```

    </WVCSPFeat>
  </Functions>
<AllFunctions>
  <WVCSPFeat/>
</AllFunctions>
</Service-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.6 Client capability negotiation transaction

### 7.6.1 ClientCapability-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
  </Session>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Request</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <ClientCapability-Request>
        <ClientID>
          <URL>http://206.226.10.25:80/IMPSAPP</URL>
        </ClientID>
        <CapabilityList>
          <ClientType>MOBILE_PHONE</ClientType>
          <InitialDeliveryMethod>P</InitialDeliveryMethod>
          <AcceptedContentType>text/plain; charset=us-ascii
</AcceptedContentType>
          <AcceptedContentType>application/x-sms
</AcceptedContentType>
          <AcceptedContentType>text/x-vCard; charset=us-ascii
</AcceptedContentType>
          <AcceptedContentType>
            text/x-vCalendar; charset=us-ascii
          </AcceptedContentType>
          <AcceptedTransferEncoding>BASE64
</AcceptedTransferEncoding>
          <AcceptedContentLength>32767</AcceptedContentLength>
          <SupportedBearer>SMS</SupportedBearer>
          <SupportedBearer>WSP</SupportedBearer>
          <SupportedBearer>HTTP</SupportedBearer>
          <MultiTrans>1</MultiTrans>
          <ParserSize>32767</ParserSize>
        </CapabilityList>
      </ClientCapability-Request>
    </TransactionContent>
  </Transaction>
</WV-CSP-Message>

```

```

        <SupportedCIRMethod>WAPSMS</SupportedCIRMethod>
        <SupportedCIRMethod>WAPUDP</SupportedCIRMethod>
        <SupportedCIRMethod>SUDP</SupportedCIRMethod>
        <SupportedCIRMethod>STCP</SupportedCIRMethod>
        <UDPPort>91</UDPPort>
        <ServerPollMin>2</ServerPollMin>
    </CapabilityList>
</ClientCapability-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.6.2 ClientCapability-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
    </SessionDescriptor>
    <SessionID>im.user.com#48815@server.com</SessionID>
  </Session>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Response</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      <Poll>F</Poll>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <ClientCapability-Response>
        <ClientID>
          <URL>http://206.226.10.25:80/IMPSAPP</URL>
        </ClientID>
        <CapabilityList>
          <ClientType>MOBILE_PHONE</ClientType>
          <InitialDeliveryMethod>P</InitialDeliveryMethod>
          <AcceptedContentType>text/plain; charset=us-ascii
</AcceptedContentType>
          <AcceptedContentType>application/x-sms
</AcceptedContentType>
          <AcceptedContentType>text/x-vCard; charset=us-ascii
</AcceptedContentType>
          <AcceptedContentType>
            text/x-vCalendar; charset=us-ascii
          </AcceptedContentType>
          <AcceptedTransferEncoding>BASE64
</AcceptedTransferEncoding>
          <AcceptedContentLength>32767</AcceptedContentLength>
          <SupportedBearer>SMS</SupportedBearer>
          <SupportedBearer>WSP</SupportedBearer>
          <SupportedBearer>HTTP</SupportedBearer>
          <MultiTrans>1</MultiTrans>
        </CapabilityList>
      </ClientCapability-Response>
    </TransactionContent>
  </Transaction>
</WV-CSP-Message>

```

```

    <ParserSize>32767</ParserSize>
    <SupportedCIRMethod>WAPSMS</SupportedCIRMethod>
    <SupportedCIRMethod>WAPUDP</SupportedCIRMethod>
    <SupportedCIRMethod>SUDP</SupportedCIRMethod>
    <SupportedCIRMethod>STCP</SupportedCIRMethod>
    <UDPPort>91</UDPPort>
    <TCPAddress>100.100.100.100</TCPAddress>
    <TCPPort>98</TCPPort>
    <ServerPollMin>3</ServerPollMin>
  </CapabilityList>
</ClientCapability-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.7 Logout transaction

### 7.7.1 Logout-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Logout-Request/>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.7.2 Disconnect primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>

```

```

    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <Disconnect>
      <Result>
        <Code>200</Code>
      </Result>
    </Disconnect>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.8 Server initiated logout transaction

### 7.8.1 Disconnect primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Disconnect>
          <Result>
            <Code>601</Code>
            <Description>
              Updating server software. All services offline for 3
hours.
            </Description>
          </Result>
        </Disconnect>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.9 Time-out reset transaction

### 7.9.1 KeepAlive-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <KeepAlive-Request>
          <TimeToLive>20</TimeToLive>
        </KeepAlive-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.9.2 KeepAlive-Response primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <KeepAlive-Response>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
          <KeepAliveTime>120</KeepAliveTime>
        </KeepAlive-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## 7.10 Get service provider info transaction

### 7.10.1 GetSPInfo-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetSPInfo-Request>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
        </GetSPInfo-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.10.2 GetSPInfo-Response primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetSPInfo-Response>
          <ClientID>
            <URL>http://206.226.10.25:80/IMPSAPP</URL>
          </ClientID>
          <Name>Fake Chocholate Co.</Name>
          <Logo>
            <ContentType>application/vnd.wap.mms-message
          </ContentType>
          <ContentSize>1234</ContentSize>
        </GetSPInfo-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```



```

        <ContentEncoding>BASE64</ContentEncoding>
        <ContentData>Base64EncodedDataHere</ContentData>
    </Logo>
    <Description>We make the fakest chocholate in the world!
    </Description>
    <URL>http://www.fake-chocholate.co.uk</URL>
</GetSPInfo-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.11 General search transaction

### 7.11.1 Search-Request (1<sup>st</sup>) primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Search-Request>
          <SearchPairList>
            <SearchElement>USER_LAST_NAME</SearchElement>
            <SearchString>Smith</SearchString>
          </SearchPairList>
          <SearchPairList>
            <SearchElement>USER_ONLINE_STATUS</SearchElement>
            <SearchString>T</SearchString>
          </SearchPairList>
          <SearchLimit>5</SearchLimit>
        </Search-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.11.2 Search-Response (1<sup>st</sup>) primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>

```

```

    <SessionID>im.user.com#48815@server.com</SessionID>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Response</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      <Poll>F</Poll>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Search-Response>
        <SearchID>0x23829381</SearchID>
        <SearchFindings>7</SearchFindings>
        <CompletionFlag>F</CompletionFlag>
        <SearchIndex>5</SearchIndex>
        <SearchResult>
          <UserList>
            <User><UserID>wv:he@there.com</UserID></User>
            <User><UserID>wv:she@there.com</UserID></User>
            <User>
              <UserID>wv:matthias@salamander.com</UserID>
            </User>
            <User><UserID>wv:francisco@don.com</UserID></User>
            <User><UserID>wv:john@smith.com</UserID></User>
          </UserList>
        </SearchResult>
      </Search-Response>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

### 7.11.3 Search-Request (continued) primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Search-Request>
          <SearchID>0x23829381</SearchID>
          <SearchIndex>6</SearchIndex>
        </Search-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    </Transaction>
  </Session>
</WV-CSP-Message>

```

#### 7.11.4 Search-Response (continued) primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Search-Response>
          <SearchID>0x23829381</SearchID>
          <SearchFindings>7</SearchFindings>
          <CompletionFlag>T</CompletionFlag>
          <SearchIndex>7</SearchIndex>
          <SearchResult>
            <UserList>
              <User><UserID>wv:mary@site.com</UserID></User>
              <User><UserID>wv:anna@server.com</UserID></User>
            </UserList>
          </SearchResult>
        </Search-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

#### 7.11.5 StopSearch-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
      </TransactionDescriptor>

```

```

    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <StopSearch-Request>
        <SearchID>0x23829381</SearchID>
      </StopSearch-Request>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.11.6 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.12 General invitation transaction

### 7.12.1 Invite-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>

```

```

<TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
  <Invite-Request>
    <InviteID>0x38382025</InviteID>
    <InviteType>GR</InviteType>
    <Recipient>
      <User><UserID>wv:he@there.com</UserID></User>
      <User><UserID>wv:she@there.com</UserID></User>
      <Group>
        <ScreenName>
          <SName>Johnny</SName>
          <GroupID>wv:john/partygroup@there.com</GroupID>
        </ScreenName>
      </Group>
    </Recipient>
    <GroupID>wv:john/partygroup@there.com</GroupID>
    <InviteNote>Come to party! You have 10 minutes!
    </InviteNote>
    <ScreenName>
      <SName>WV</SName>
      <GroupID>wv:john/partygroup@there.com</GroupID>
    </ScreenName>
    <Validity>600</Validity>
  </Invite-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.12.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.12.3 InviteUser-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <InviteUser-Request>
          <InviteID>0x38382025</InviteID>
          <InviteType>GR</InviteType>
          <Sender>
            <Group>
              <ScreenName>
                <SName>WV</SName>
                <GroupID>wv:john/partygroup@there.com</GroupID>
              </ScreenName>
            </Group>
          </Sender>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <InviteNote>Come to party!</InviteNote>
          <Validity>600</Validity>
        </InviteUser-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.12.4 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>

```

```

    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
          <Description>Successfully completed.</Description>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

### 7.12.5 InviteUser-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <InviteUser-Response>
          <InviteID>0x38382025</InviteID>
          <Acceptance>T</Acceptance>
          <ResponseNote>OK, just a sec!</ResponseNote>
          <ScreenName>
            <SName>Johnny</SName>
            <GroupID>wv:john/partygroup@there.com</GroupID>
          </ScreenName>
        </InviteUser-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.12.6 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>

```

```

<TransactionDescriptor>
  <TransactionMode>Response</TransactionMode>
  <TransactionID>IMApp01#12347@NOK5110</TransactionID>
  <Poll>F</Poll>
</TransactionDescriptor>
<TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
  <Status>
    <Result>
      <Code>200</Code>
      <Description>Successfully completed.</Description>
    </Result>
  </Status>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.12.7 Invite-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12348@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Invite-Response>
          <InviteID>0x38382025</InviteID>
          <Acceptance>T</Acceptance>
          <Sender>
            <Group>
              <ScreenName>
                <SName>WV</SName>
                <GroupID>wv:john/partygroup@there.com</GroupID>
              </ScreenName>
            </Group>
          </Sender>
          <ResponseNote>OK, just a sec!</ResponseNote>
        </Invite-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```



## 7.12.8 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12348@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## 7.13 Recall invitation transaction

### 7.13.1 CancellInvite-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <CancelInvite-Request>
          <InviteID>0x38382025</InviteID>
          <Recipient>
            <User><UserID>wv:he@there.com</UserID></User>
            <User><UserID>wv:she@there.com</UserID></User>
          <Group>
            <ScreenName>
              <SName>Johnny</SName>
            <GroupID>wv:john/partygroup@there.com</GroupID>
          </Group>
        </Recipient>
      </CancelInvite-Request>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>
```

```

        </ScreenName>
      </Group>
    </Recipient>
    <InviteNote>Time is up!</InviteNote>
    <ScreenName>
      <SName>WV</SName>
      <GroupID>wv:john/partygroup@there.com</GroupID>
    </ScreenName>
  </CancelInvite-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.13.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.13.3 CancelInviteUser-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>

```

```

    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12346@NOK5110</TransactionID>
    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <CancelInviteUser-Request>
      <InviteID>0x38382025</InviteID>
      <Sender>
        <Group>
          <ScreenName>
            <SName>WV</SName>
            <GroupID>wv:john/partygroup@there.com</GroupID>
          </ScreenName>
        </Group>
      </Sender>
      <InviteNote>Time is up!</InviteNote>
    </CancelInviteUser-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

#### 7.13.4 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.14 Subscribe/unsubscribe presence transaction

### 7.14.1 SubscribePresence-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <SubscribePresence-Request>
          <ContactList>wv:john/ContactList-5@smith.com
</ContactList>
          <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
            <OnlineStatus/>
            <Registration/>
            <ClientInfo/>
            <TimeZone/>
            <GeoLocation/>
            <Address/>
            <FreeTextLocation/>
            <PLMN/>
            <CommCap/>
            <UserAvailability/>
            <PreferredContacts/>
            <PreferredLanguage/>
            <StatusText/>
            <StatusMood/>
            <Alias/>
            <StatusContent/>
            <ContactInfo/>
          </PresenceSubList>
        </SubscribePresence-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.14.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>

```

```

    <SessionID>im.user.com#48815@server.com</SessionID>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Response</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      <Poll>F</Poll>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
          <Description>Successfully completed.</Description>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

### 7.14.3 PresenceNotification-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <PresenceNotification-Request>
          <Presence>
            <UserID>wv:he@there.com</UserID>
            <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
              <OnlineStatus>
                <Qualifier>T</Qualifier>
                <PresenceValue>T</PresenceValue>
              </OnlineStatus>
              <Registration>
                <Qualifier>T</Qualifier>
                <PresenceValue>T</PresenceValue>
              </Registration>
              <ClientInfo>
                <Qualifier>T</Qualifier>

```

```

    <ClientType>MOBILE_PHONE</ClientType>
    <DevManufacturer>ABC Company</DevManufacturer>
    <Model>xyz200</Model>
    <Language>fin</Language>
  </ClientInfo>
  <TimeZone>
    <Qualifier>T</Qualifier>
    <Zone>+02</Zone>
  </TimeZone>
  <GeoLocation>
    <Qualifier>T</Qualifier>
    <Longitude>35 24 15.652W</Longitude>
    <Latitude>12 36 22.5N</Latitude>
    <Accuracy>200</Accuracy>
  </GeoLocation>
  <Address>
    <Qualifier>T</Qualifier>
    <Country>GB</Country>
    <City>London</City>
  </Address>
  <FreeTextLocation>
    <Qualifier>T</Qualifier>
    <PresenceValue>At home</PresenceValue>
  </FreeTextLocation>
  <PLMN>
    <Qualifier>T</Qualifier>
    <PresenceValue>Sonera</PresenceValue>
  </PLMN>
  <CommCap>
    <Qualifier>T</Qualifier>
    <CommC>
      <Cap>CALL</Cap>
      <Status>OPEN</Status>
      <Contact>+35804123123</Contact>
      <Note>I am using this phone during office hours
    </Note>
    </CommC>
    <CommC>
      <Cap>CALL</Cap>
      <Status>CLOSED</Status>
      <Contact>+35805456456</Contact>
      <Note>
        I am using this phone outside office hours
      </Note>
    </CommC>
    <CommC>
      <Cap>IM</Cap>
      <Status>OPEN</Status>
      <Contact>he@there.com</Contact>
      <Note>My IM-application is now online</Note>
    </CommC>
  </CommCap>
</UserAvailability>

```

```
<Qualifier>T</Qualifier>
  <PresenceValue>AVAILABLE</PresenceValue>
</UserAvailability>
<PreferredContacts>
  <Qualifier>T</Qualifier>
  <AddrPref>
    <PrefC>CALL</PrefC>
    <Caddr>+35804123123</Caddr>
    <Cstatus>OPEN</Cstatus>
    <Cname>Home Phone</Cname>
    <Cpriority>10</Cpriority>
  </AddrPref>
  <AddrPref>
    <PrefC>SMS</PrefC>
    <Caddr>+35804123123</Caddr>
    <Cstatus>OPEN</Cstatus>
    <Cname>Home Messaging</Cname>
    <Cpriority>20</Cpriority>
  </AddrPref>
  <AddrPref>
    <PrefC>IM</PrefC>
    <Caddr>ari@im.com</Caddr>
    <Cstatus>CLOSED</Cstatus>
    <Cname>Private IM</Cname>
    <Cpriority>30</Cpriority>
  </AddrPref>
</PreferredContacts>
<PreferredLanguage>
  <Qualifier>T</Qualifier>
  <PresenceValue>fin</PresenceValue>
</PreferredLanguage>
<StatusText>
  <Qualifier>T</Qualifier>
  <PresenceValue>Busy editing a document
  </PresenceValue>
</StatusText>
<StatusMood>
  <Qualifier>T</Qualifier>
  <PresenceValue>SLEEPY</PresenceValue>
</StatusMood>
<Alias>
  <Qualifier>T</Qualifier>
  <PresenceValue>He</PresenceValue>
</Alias>
<StatusContent>
  <Qualifier>T</Qualifier>
  <ReferredContent>http://www.foo.com/MyLogo
  </ReferredContent>
</StatusContent>
<ContactInfo>
  <Qualifier>T</Qualifier>
  <ReferredvCard>http://www.foo.com/MyCard
  </ReferredvCard>
```

```

        </ContactInfo>
      </PresenceSubList>
    </Presence>
  </PresenceNotification-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

#### 7.14.4 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

#### 7.14.5 UnsubscribePresenceRequest primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <UnsubscribePresence-Request>

```



```

        <ContactList>wv:john/ContactList-5@smith.com
        </ContactList>
    </UnsubscribePresence-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.14.6 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.15 Get watcher list transaction

### 7.15.1 GetWatcherList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>

```

```

    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <GetWatcherList-Request/>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.15.2 GetWatcherList-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetWatcherList-Response>
          <User><UserID>wv:he@there.com</UserID></User>
          <User><UserID>wv:she@there.com</UserID></User>
        </GetWatcherList-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.16 Get presence transaction

### 7.16.1 GetPresence-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetPresence-Request>

```

```

    <User><UserID>wv:he@there.com</UserID></User>
    <User><UserID>wv:she@there.com</UserID></User>
    <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
      <OnlineStatus/>
      <Registration/>
      <ClientInfo/>
      <TimeZone/>
      <GeoLocation/>
      <Address/>
      <FreeTextLocation/>
      <PLMN/>
      <CommCap/>
      <UserAvailability/>
      <PreferredContacts/>
      <PreferredLanguage/>
      <StatusText/>
      <StatusMood/>
      <Alias/>
      <StatusContent/>
      <ContactInfo/>
    </PresenceSubList>
  </GetPresence-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.16.2 GetPresence-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetPresence-Response>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
          <Presence>
            <UserID>wv:he@there.com</UserID>

```

```
<PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
  <OnlineStatus>
    <Qualifier>T</Qualifier>
    <PresenceValue>T</PresenceValue>
  </OnlineStatus>
  <Registration>
    <Qualifier>T</Qualifier>
    <PresenceValue>T</PresenceValue>
  </Registration>
  <ClientInfo>
    <Qualifier>T</Qualifier>
    <ClientType>MOBILE_PHONE</ClientType>
    <DevManufacturer>ABC Company</DevManufacturer>
    <Model>xyz200</Model>
    <Language>fin</Language>
  </ClientInfo>
  <TimeZone>
    <Qualifier>T</Qualifier>
    <Zone>+02</Zone>
  </TimeZone>
  <GeoLocation>
    <Qualifier>T</Qualifier>
    <Longitude>35 24 15.652W</Longitude>
    <Latitude>12 36 22.5N</Latitude>
    <Accuracy>200</Accuracy>
  </GeoLocation>
  <Address>
    <Qualifier>T</Qualifier>
    <Country>GB</Country>
    <City>London</City>
  </Address>
  <FreeTextLocation>
    <Qualifier>T</Qualifier>
    <PresenceValue>At home</PresenceValue>
  </FreeTextLocation>
  <PLMN>
    <Qualifier>T</Qualifier>
    <PresenceValue>Sonera</PresenceValue>
  </PLMN>
  <CommCap>
    <Qualifier>T</Qualifier>
    <CommC>
      <Cap>CALL</Cap>
      <Status>OPEN</Status>
      <Contact>+35804123123</Contact>
      <Note>I am using this phone during office hours
      </Note>
    </CommC>
    <CommC>
      <Cap>CALL</Cap>
      <Status>CLOSED</Status>
      <Contact>+35805456456</Contact>
```

```

    <Note>
      I am using this phone outside office hours
    </Note>
  </CommC>
  <CommC>
    <Cap>IM</Cap>
    <Status>OPEN</Status>
    <Contact>he@there.com</Contact>
    <Note>My IM-application is now online</Note>
  </CommC>
  <CommC>
    <Cap>IM</Cap>
    <Status>OPEN</Status>
    <Contact>he@there.com</Contact>
    <Note>My IM-application is now online</Note>
  </CommC>
</CommCap>
<UserAvailability>
  <Qualifier>T</Qualifier>
  <PresenceValue>AVAILABLE</PresenceValue>
</UserAvailability>
<PreferredContacts>
  <Qualifier>T</Qualifier>
  <AddrPref>
    <PrefC>CALL</PrefC>
    <Caddr>+35804123123</Caddr>
    <Cstatus>OPEN</Cstatus>
    <Cname>Home Phone</Cname>
    <Cpriority>10</Cpriority>
  </AddrPref>
  <AddrPref>
    <PrefC>SMS</PrefC>
    <Caddr>+35804123123</Caddr>
    <Cstatus>OPEN</Cstatus>
    <Cname>Home Messaging</Cname>
    <Cpriority>20</Cpriority>
  </AddrPref>
  <AddrPref>
    <PrefC>IM</PrefC>
    <Caddr>ari@im.com</Caddr>
    <Cstatus>CLOSED</Cstatus>
    <Cname>Private IM</Cname>
    <Cpriority>30</Cpriority>
  </AddrPref>
</PreferredContacts>
<PreferredLanguage>
  <Qualifier>T</Qualifier>
  <PresenceValue>fin</PresenceValue>
</PreferredLanguage>
<StatusText>
  <Qualifier>T</Qualifier>
  <PresenceValue>Busy editing a document
</PresenceValue>

```

```

</StatusText>
<StatusMood>
  <Qualifier>T</Qualifier>
  <PresenceValue>SLEEPY</PresenceValue>
</StatusMood>
<Alias>
  <Qualifier>T</Qualifier>
  <PresenceValue>He</PresenceValue>
</Alias>
<StatusContent>
  <Qualifier>T</Qualifier>
  <ReferredContent>http://www.foo.com/MyLogo
  </ReferredContent>
</StatusContent>
<ContactInfo>
  <Qualifier>T</Qualifier>
  <ReferredvCard>http://www.foo.com/MyCard
  </ReferredvCard>
</ContactInfo>
</PresenceSubList>
</Presence>
<Presence>
  <UserID>wv:she@there.com</UserID>
  <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
    <OnlineStatus>
      <Qualifier>T</Qualifier>
      <PresenceValue>T</PresenceValue>
    </OnlineStatus>
    <Registration>
      <Qualifier>T</Qualifier>
      <PresenceValue>T</PresenceValue>
    </Registration>
    <ClientInfo>
      <Qualifier>T</Qualifier>
      <ClientType>MOBILE_PHONE</ClientType>
      <DevManufacturer>ABC Company</DevManufacturer>
      <Model>xyz200</Model>
      <Language>fin</Language>
    </ClientInfo>
    <TimeZone>
      <Qualifier>T</Qualifier>
      <Zone>+02</Zone>
    </TimeZone>
    <GeoLocation>
      <Qualifier>T</Qualifier>
      <Longitude>35 24 15.652W</Longitude>
      <Latitude>12 36 22.5N</Latitude>
      <Accuracy>200</Accuracy>
    </GeoLocation>
    <Address>
      <Qualifier>T</Qualifier>
      <Country>GB</Country>

```

```

    <City>London</City>
  </Address>
  <FreeTextLocation>
    <Qualifier>T</Qualifier>
    <PresenceValue>At home</PresenceValue>
  </FreeTextLocation>
  <PLMN>
    <Qualifier>T</Qualifier>
    <PresenceValue>Sonera</PresenceValue>
  </PLMN>
  <CommCap>
    <Qualifier>T</Qualifier>
    <CommC>
      <Cap>CALL</Cap>
      <Status>OPEN</Status>
      <Contact>+35804123123</Contact>
      <Note>I am using this phone during office hours
      </Note>
    </CommC>
    <CommC>
      <Cap>CALL</Cap>
      <Status>CLOSED</Status>
      <Contact>+35805456456</Contact>
      <Note>
        I am using this phone outside office hours
      </Note>
    </CommC>
    <CommC>
      <Cap>IM</Cap>
      <Status>OPEN</Status>
      <Contact>she@there.com</Contact>
      <Note>My IM-application is now online</Note>
    </CommC>
  </CommCap>
  <UserAvailability>
    <Qualifier>T</Qualifier>
    <PresenceValue>AVAILABLE</PresenceValue>
  </UserAvailability>
  <PreferredContacts>
    <Qualifier>T</Qualifier>
    <AddrPref>
      <PrefC>CALL</PrefC>
      <Caddr>+35804123123</Caddr>
      <Cstatus>OPEN</Cstatus>
      <Cname>Business Phone</Cname>
      <Cpriority>10</Cpriority>
    </AddrPref>
    <AddrPref>
      <PrefC>SMS</PrefC>
      <Caddr>+35804123123</Caddr>
      <Cstatus>OPEN</Cstatus>
      <Cname>Business Messaging</Cname>
      <Cpriority>20</Cpriority>
    </AddrPref>
  </PreferredContacts>

```

```

    <AddrPref>
      <PrefC>IM</PrefC>
      <Caddr>ari@im.com</Caddr>
      <Cstatus>CLOSED</Cstatus>
      <Cname>Private IM</Cname>
      <Cpriority>30</Cpriority>
    </AddrPref>
  </PreferredContacts>
  <PreferredLanguage>
    <Qualifier>T</Qualifier>
    <PresenceValue>fin</PresenceValue>
  </PreferredLanguage>
  <StatusText>
    <Qualifier>T</Qualifier>
    <PresenceValue>Busy editing a document
  </PresenceValue>
  </StatusText>
  <StatusMood>
    <Qualifier>T</Qualifier>
    <PresenceValue>SLEEPY</PresenceValue>
  </StatusMood>
  <Alias>
    <Qualifier>T</Qualifier>
    <PresenceValue>She</PresenceValue>
  </Alias>
  <StatusContent>
    <Qualifier>T</Qualifier>
    <DirectContent>
      BASE64EncodedDataHere
    </DirectContent>
  </StatusContent>
  <ContactInfo>
    <Qualifier>T</Qualifier>
    <ContainedvCard>
      vCardDataHere
    </ContainedvCard>
  </ContactInfo>
</PresenceSubList>
</Presence>
</GetPresence-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.17 Reactive presence authorization transaction

### 7.17.1 PresenceAuth-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>

```



```

    <SessionType>Outband</SessionType>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Request</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      <Poll>F</Poll>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <PresenceAuth-Request>
        <UserID>wv:matthias@salamander.com</UserID>
        <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
          <OnlineStatus/>
          <Registration/>
          <ClientInfo/>
          <TimeZone/>
          <GeoLocation/>
          <Address/>
          <FreeTextLocation/>
          <PLMN/>
          <CommCap/>
          <UserAvailability/>
          <PreferredContacts/>
          <PreferredLanguage/>
          <StatusText/>
          <StatusMood/>
          <Alias/>
          <StatusContent/>
          <ContactInfo/>
        </PresenceSubList>
      </PresenceAuth-Request>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

### 7.17.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>

```

```

    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

### 7.17.3 PresenceAuth-User primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <PresenceAuth-User>
          <UserID>wv:matthias@salamander.com</UserID>
          <Acceptance>T</Acceptance>
        </PresenceAuth-User>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.17.4 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>

```

```

    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.18 Cancel presence authorization transaction

### 7.18.1 CancelAuth-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <CancelAuth-Request>
          <UserID>wv:matthias@salamander.com</UserID>
        </CancelAuth-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.18.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>

```

```

    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
          <Description>Successfully completed.</Description>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.19 Update presence transaction

### 7.19.1 UpdatePresence-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <UpdatePresence-Request>
          <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
            <StatusText>
              <Qualifier>T</Qualifier>
              <PresenceValue>on the way home</PresenceValue>
            </StatusText>
            <StatusMood>
              <Qualifier>T</Qualifier>
              <PresenceValue>HAPPY</PresenceValue>
            </StatusMood>
          </PresenceSubList>
        </UpdatePresence-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.19.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">

```

```

<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Response</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <Status>
      <Result>
        <Code>200</Code>
        <Description>Successfully completed.</Description>
      </Result>
    </Status>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.20 Send message transaction

### 7.20.1 SendMessage-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <SendMessage-Request>
      <DeliveryReport>T</DeliveryReport>
      <MessageInfo>
        <ContentType>text/plain</ContentType>
        <ContentEncoding>None</ContentEncoding>
        <ContentSize>58</ContentSize>
        <Recipient>
          <User>
            <UserID>wv:he@there.com</UserID>
          </User>
          <Group>

```

```

        <ScreenName>
            <SName>Wicked Vicky</SName>
            <GroupID>wv:john/chatgroup@there.com</GroupID>
        </ScreenName>
    </Group>
    <ContactList>wv:john/My_friends@smith.com
    </ContactList>
</Recipient>
<Sender>
    <User>
        <UserID>wv:john@smith.com</UserID>
    </User>
</Sender>
<DateTime>20010925T1340Z</DateTime>
<Validity>600</Validity>
</MessageInfo>
<ContentData>
    Hurry up; they are ringing the bells in the WV already...
</ContentData>
</SendMessage-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.20.2 SendMessage-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
    <Session>
        <SessionDescriptor>
            <SessionType>Inband</SessionType>
            <SessionID>im.user.com#48815@server.com</SessionID>
        </SessionDescriptor>
        <Transaction>
            <TransactionDescriptor>
                <TransactionMode>Response</TransactionMode>
                <TransactionID>IMApp01#12345@NOK5110</TransactionID>
                <Poll>F</Poll>
            </TransactionDescriptor>
            <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
                <SendMessage-Response>
                    <Result>
                        <Code>200</Code>
                        <Description>Successfully completed.</Description>
                    </Result>
                    <MessageID>0x0000f132</MessageID>
                </SendMessage-Response>
            </TransactionContent>
        </Transaction>
    </Session>
</WV-CSP-Message>

```

## 7.21 Set delivery method transaction

### 7.21.1 SetDeliveryMethod-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <SetDeliveryMethod-Request>
          <DeliveryMethod>P</DeliveryMethod>
          <AcceptedContentLength>2048</AcceptedContentLength>
          <GroupID>wv:/chatgroup@server.com</GroupID>
        </SetDeliveryMethod-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.21.2 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

```

    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.22 Get list of undelivered messages transaction

### 7.22.1 GetMessageList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetMessageList-Request>
          <GroupID>wv:john/chatgroup@there.com</GroupID>
          <MessageCount>5</MessageCount>
        </GetMessageList-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.22.2 GetMessageList-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetMessageList-Response>
          <MessageInfo>
            <MessageID>0x0000f132</MessageID>
            <ContentType>text/plain</ContentType>
            <ContentEncoding>None</ContentEncoding>
          </MessageInfo>
        </GetMessageList-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```



```
<ContentSize>41</ContentSize>
<Recipient>
  <Group>
    <ScreenName>
      <SName>Johnnie</SName>
      <GroupID>wv:john/chatgroup@there.com</GroupID>
    </ScreenName>
  </Group>
</Recipient>
<Sender>
  <Group>
    <ScreenName>
      <SName>Wicked Vicky</SName>
      <GroupID>wv:john/chatgroup@there.com</GroupID>
    </ScreenName>
  </Group>
</Sender>
<DateTime>20010925T1340Z</DateTime>
<Validity>600</Validity>
</MessageInfo>
<MessageInfo>
  <MessageID>0x0000f133</MessageID>
  <ContentType>text/plain</ContentType>
  <ContentEncoding>None</ContentEncoding>
  <ContentSize>20</ContentSize>
  <Recipient>
    <Group>
      <ScreenName>
        <SName>Johnnie</SName>
        <GroupID>wv:john/chatgroup@there.com</GroupID>
      </ScreenName>
    </Group>
  </Recipient>
  <Sender>
    <Group>
      <ScreenName>
        <SName>Wicked Vicky</SName>
        <GroupID>wv:john/chatgroup@there.com</GroupID>
      </ScreenName>
    </Group>
  </Sender>
  <DateTime>20010925T1342Z</DateTime>
  <Validity>600</Validity>
</MessageInfo>
</GetMessageList-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>
```

## 7.23 Rejecting a message (notify/get method only) transaction

### 7.23.1 RejectMessage-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <RejectMessage-Request>
          <MessageID>0x0000f132</MessageID>
        </RejectMessage-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.23.2 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## 7.24 Message notification (notify/get method only) transaction

### 7.24.1 MessageNotification primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <MessageNotification>
          <MessageInfo>
            <MessageID>0x0000f132</MessageID>
            <ContentType>text/plain</ContentType>
            <ContentEncoding>None</ContentEncoding>
            <ContentSize>189</ContentSize>
            <Recipient>
              <Group>
                <ScreenName>
                  <SName>Johnnie</SName>
                  <GroupID>wv:john/chatgroup@there.com</GroupID>
                </ScreenName>
              </Group>
            </Recipient>
            <Sender>
              <Group>
                <ScreenName>
                  <SName>Wicked Vicky</SName>
                  <GroupID>wv:john/chatgroup@there.com</GroupID>
                </ScreenName>
              </Group>
            </Sender>
            <DateTime>20010925T1340Z</DateTime>
            <Validity>600</Validity>
          </MessageInfo>
        </MessageNotification>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.24.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">

```

```

<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Response</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <Status>
      <Result>
        <Code>200</Code>
        <Description>Successfully completed.</Description>
      </Result>
    </Status>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.25 Retrieving a message (get/notify method) transaction

### 7.25.1 GetMessage-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <GetMessage-Request>
      <MessageID>0x0000f132</MessageID>
    </GetMessage-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.25.2 GetMessage-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">

```

```

<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Response</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <GetMessage-Response>
      <MessageInfo>
        <MessageID>0x0000f132</MessageID>
        <ContentType>text/plain</ContentType>
        <ContentEncoding>None</ContentEncoding>
        <ContentSize>41</ContentSize>
        <Recipient>
          <Group>
            <ScreenName>
              <SName>Johnnie</SName>
              <GroupID>wv:john/chatgroup@there.com</GroupID>
            </ScreenName>
          </Group>
        </Recipient>
        <Sender>
          <Group>
            <ScreenName>
              <SName>Wicked Vicky</SName>
              <GroupID>wv:john/chatgroup@there.com</GroupID>
            </ScreenName>
          </Group>
        </Sender>
        <DateTime>20010925T1340Z</DateTime>
        <Validity>600</Validity>
      </MessageInfo>
      <ContentData>Hi guys, just arrived... How is it going?
      </ContentData>
    </GetMessage-Response>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.25.3 MessageDelivered primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>

```

```

    <SessionID>im.user.com#48815@server.com</SessionID>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Response</TransactionMode>
      <TransactionID>IMApp01#12346@NOK5110</TransactionID>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <MessageDelivered>
        <MessageID>0x0000f132</MessageID>
      </MessageDelivered>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.25.4 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.26 Delivering a message (push method) transaction

### 7.26.1 NewMessage primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>

```

```

    <SessionType>Inband</SessionType>
    <SessionID>im.user.com#48815@server.com</SessionID>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Request</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      <Poll>F</Poll>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <NewMessage>
        <MessageInfo>
          <MessageID>0x0000f132</MessageID>
          <ContentType>text/plain</ContentType>
          <ContentEncoding>None</ContentEncoding>
          <ContentSize>41</ContentSize>
          <Recipient>
            <Group>
              <ScreenName>
                <SName>Johnnie</SName>
                <GroupID>wv:john/chatgroup@there.com</GroupID>
              </ScreenName>
            </Group>
          </Recipient>
          <Sender>
            <Group>
              <ScreenName>
                <SName>Wicked Vicky</SName>
                <GroupID>wv:john/chatgroup@there.com</GroupID>
              </ScreenName>
            </Group>
          </Sender>
          <DateTime>20010925T1340Z</DateTime>
          <Validity>600</Validity>
        </MessageInfo>
        <ContentData>Hi guys, just arrived... How is it going?
        </ContentData>
      </NewMessage>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.26.2 MessageDelivered primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>

```

```

<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Response</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <MessageDelivered>
      <MessageID>0x0000f132</MessageID>
    </MessageDelivered>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.27 Delivery Report transaction

### 7.27.1 DeliveryReport-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <DeliveryReport-Request>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
          <DeliveryTime>20010925T1341Z</DeliveryTime>
          <MessageInfo>
            <MessageID>0x0000f132</MessageID>
            <ContentType>text/plain</ContentType>
            <ContentEncoding>None</ContentEncoding>
            <ContentSize>41</ContentSize>
            <Recipient>
              <Group>
                <ScreenName>
                  <SName>B. Billy</SName>
                  <GroupID>wv:/happy@hippie.com</GroupID>
                </ScreenName>
              </Group>
            </Recipient>
          </MessageInfo>
        </DeliveryReport-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```



```

    <Sender>
      <Group>
        <ScreenName>
          <SName>Johnnie</SName>
          <GroupID>wv:/happy@hippie.com</GroupID>
        </ScreenName>
      </Group>
    </Sender>
    <DateTime>20010925T1340Z</DateTime>
    <Validity>600</Validity>
  </MessageInfo>
</DeliveryReport-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.27.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.28 Forward undelivered message transaction

### 7.28.1 ForwardMessage-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>

```

```

    <SessionID>im.user.com#48815@server.com</SessionID>
  </SessionDescriptor>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Request</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <ForwardMessage-Request>
        <MessageID>0x0000f132</MessageID>
        <Recipient>
          <Group>
            <ScreenName>
              <SName>B. Billy</SName>
              <GroupID>wv:/happy@hippie.com</GroupID>
            </ScreenName>
          </Group>
        </Recipient>
      </ForwardMessage-Request>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.28.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.29 Get blocked user list transaction

### 7.29.1 GetBlockedList-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
  </Session>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Request</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <GetBlockedList-Request/>
    </TransactionContent>
  </Transaction>
</WV-CSP-Message>
```

### 7.29.2 GetBlockedList-Response primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
  </Session>
  <Transaction>
    <TransactionDescriptor>
      <TransactionMode>Response</TransactionMode>
      <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      <Poll>F</Poll>
    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <GetBlockedList-Response>
        <BlockList>
          <InUse>F</InUse>
          <EntityList>
            <UserID>wv:he@there.com</UserID>
            <UserID>wv:she@there.com</UserID>
            <ScreenName>
              <SName>Billyboy</SName>
              <GroupID>wv:john/chatgroup@there.com</GroupID>
            </ScreenName>
            <GroupID>wv:/boringlist@server.com</GroupID>
          </EntityList>
        </BlockList>
      </GetBlockedList-Response>
    </TransactionContent>
  </Transaction>
</WV-CSP-Message>
```

```

    <GrantList>
      <InUse>T</InUse>
      <EntityList>
        <UserID>wv:matthias@salamander.com</UserID>
        <UserID>wv:francisco@don.com</UserID>
        <ScreenName>
          <SName>WV</SName>
          <GroupID>wv:john/chatgroup@there.com</GroupID>
        </ScreenName>
        <GroupID>wv:/wireless@village.com</GroupID>
      </EntityList>
    </GrantList>
  </GetBlockedList-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.30 Block entity transaction

### 7.30.1 BlockEntity-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <BlockEntity-Request>
          <BlockList>
            <InUse>T</InUse>
            <AddList/>
            <RemoveList>
              <UserID>wv:matthias@salamander.com</UserID>
            </RemoveList>
          </BlockList>
          <GrantList>
            <InUse/>
            <AddList>
              <UserID>wv:matthias@salamander.com</UserID>
            </AddList>
            <RemoveList/>
          </GrantList>
        </BlockEntity-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.30.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Outband</SessionType>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.31 Get list of contact list(s) transaction

### 7.31.1 GetList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetList-Request/>
      </TransactionContent>
    </Transaction>
  </Session>

```

```
</WV-CSP-Message>
```

## 7.31.2 GetList-Response primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetList-Response>
          <ContactList>wv:john/My_friends@smith.com</ContactList>
          <ContactList>wv:john/My_family@smith.com</ContactList>
          <ContactList>wv:john/My_colleagues@smith.com
</ContactList>
          <ContactList>wv:john/The_WV@smith.com
</ContactList>
          <DefaultContactList>wv:john/My_enemies@smith.com
</DefaultContactList>
        </GetList-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## 7.32 Create contact list transaction

### 7.32.1 CreateList-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <CreateList-Request>
```

```

<ContactList>wv:john/My_friends@smith.com</ContactList>
<NickList>
  <NickName>
    <Name>Brainstorm</Name>
    <UserID>wv:bright@dark.com</UserID>
  </NickName>
  <NickName>
    <Name>Randall the Vandal</Name>
    <UserID>wv:randall@fairlane.com</UserID>
  </NickName>
</NickList>
<ContactListProperties>
  <Property>
    <Name>DisplayName</Name>
    <Value>My friends</Value>
  </Property>
  <Property>
    <Name>Default</Name>
    <Value>F</Value>
  </Property>
</ContactListProperties>
</CreateList-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.32.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>

```

```
</WV-CSP-Message>
```

## 7.33 Delete contact list transaction

### 7.33.1 DeleteList-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <DeleteList-Request>
          <ContactList>wv:john/My_enemies@smith.com</ContactList>
        </DeleteList-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.33.2 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```



```

</Session>
</WV-CSP-Message>

```

## 7.34 Retrieve contact list transaction

### 7.34.1 ListManage-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <ListManage-Request>
          <ContactList>wv:john/My_friends@smith.com</ContactList>
        </ListManage-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.34.2 ListManage-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <ListManage-Response>
          <Result>
            <Code>200</Code>
          </Result>
          <NickList>
            <NickName>
              <Name>Brainstrom</Name>
            </NickName>
          </NickList>
        </ListManage-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

        <UserID>wv:bright@dark.com</UserID>
    </NickName>
    <NickName>
        <Name>Randall the Vandal</Name>
        <UserID>wv:randall@fairlane.com</UserID>
    </NickName>
    <NickName>
        <Name>JLo</Name>
        <UserID>wv:jenny@logic.com</UserID>
    </NickName>
    <NickName>
        <Name>Ex</Name>
        <UserID>wv:ex@wife.com</UserID>
    </NickName>
</NickList>
<ContactListProperties>
    <Property>
        <Name>DisplayName</Name>
        <Value>My friends</Value>
    </Property>
    <Property>
        <Name>Default</Name>
        <Value>F</Value>
    </Property>
</ContactListProperties>
</ListManage-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.35 Add users to contact list transaction

### 7.35.1 ListManage-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
    <Session>
        <SessionDescriptor>
            <SessionType>Inband</SessionType>
            <SessionID>im.user.com#48815@server.com</SessionID>
        </SessionDescriptor>
    </Session>
    <Transaction>
        <TransactionDescriptor>
            <TransactionMode>Request</TransactionMode>
            <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        </TransactionDescriptor>
        <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
            <ListManage-Request>
                <ContactList>wv:john/My_friends@smith.com</ContactList>
                <AddNickList>
                    <NickName>

```

```

        <Name>Randall the Vandal</Name>
        <UserID>wv:randall@fairlane.com</UserID>
    </NickName>
    <NickName>
        <Name>JLo</Name>
        <UserID>wv:jenny@logic.com</UserID>
    </NickName>
</AddNickList>
</ListManage-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.35.2 ListManage-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <ListManage-Response>
          <Result>
            <Code>200</Code>
          </Result>
          <NickList>
            <NickName>
              <Name>Randall the Vandal</Name>
              <UserID>wv:randall@fairlane.com</UserID>
            </NickName>
            <NickName>
              <Name>JLo</Name>
              <UserID>wv:jenny@logic.com</UserID>
            </NickName>
          </NickList>
        </ListManage-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.36 Remove users from contact list transaction

### 7.36.1 ListManage-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <ListManage-Request>
          <ContactList>wv:john/My_friends@smith.com</ContactList>
          <RemoveNickList>
            <UserID>wv:randall@fairlane.com</UserID>
            <UserID>wv:jenny@logic.com</UserID>
          </RemoveNickList>
        </ListManage-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.36.2 ListManage-Response primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <ListManage-Response>
          <Result>
            <Code>200</Code>
          </Result>
          <NickList/>
        </ListManage-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

```

    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.37 Modify properties of contact list transaction

### 7.37.1 ListManage-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <ListManage-Request>
          <ContactList>wv:john/My_friends@smith.com</ContactList>
          <ContactListProperties>
            <Property>
              <Name>DisplayName</Name>
              <Value>My enemies</Value>
            </Property>
            <Property>
              <Name>Default</Name>
              <Value>T</Value>
            </Property>
          </ContactListProperties>
        </ListManage-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.37.2 ListManage-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>

```

```

    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <ListManage-Response>
      <Result>
        <Code>200</Code>
      </Result>
      <ContactListProperties>
        <Property>
          <Name>DisplayName</Name>
          <Value>My enemies</Value>
        </Property>
        <Property>
          <Name>Default</Name>
          <Value>T</Value>
        </Property>
      </ContactListProperties>
    </ListManage-Response>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.38 Create Attribute list transaction

### 7.38.1 CreateAttributeList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <CreateAttributeList-Request>
          <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
            <UserAvailability/>
            <StatusMood/>
          </PresenceSubList>
          <UserID>somebody@nowhere.com</UserID>
          <UserID>another_one@nowhere.com</UserID>
          <ContactList>wv: john/My_friends@smith.com</ContactList>
          <ContactList>wv: john/My_family@smith.com</ContactList>
          <DefaultList>T</DefaultList>
        </CreateAttributeList-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    </CreateAttributeList-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.38.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.39 Delete Attribute list transaction

### 7.39.1 DeleteAttributeList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <DeleteAttributeList-Request>

```

```

    <UserID>somebody@nowhere.com</UserID>
    <UserID>another_one@nowhere.com</UserID>
    <ContactList>wv:john/My_friends@smith.com</ContactList>
    <ContactList>wv:john/My_family@smith.com</ContactList>
    <DefaultList>T</DefaultList>
  </DeleteAttributeList-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.39.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.40 Get Attribute list transaction

### 7.40.1 GetAttributeList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>

```



```

    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <GetAttributeList-Request>
      <DefaultList>T</DefaultList>
    </GetAttributeList-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.40.2 GetAttributeList-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetAttributeList-Response>
          <Result>
            <Code>200</Code>
          </Result>
          <DefaultAttributeList>
            <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
              <UserAvailability/>
              <StatusMood/>
            </PresenceSubList>
          </DefaultAttributeList>
          <Presence>
            <UserID>somebody@nowhere.com</UserID>
            <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
              <OnlineStatus/>
              <UserAvailability/>
              <StatusText/>
              <StatusMood/>
            </PresenceSubList>
          </Presence>
          <Presence>
            <UserID>another_one@nowhere.com</UserID>

```

```

        <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
            <UserAvailability/>
            <StatusMood/>
        </PresenceSubList>
    </Presence>
    <Presence>
        <ContactList>wv:john/My_friends@smith.com
        </ContactList>
        <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
            <UserAvailability/>
            <StatusMood/>
        </PresenceSubList>
    </Presence>
    <Presence>
        <ContactList>wv:john/My_family@smith.com</ContactList>
        <PresenceSubList xmlns="http://www.wireless-
village.org/PA1.1">
            <UserAvailability/>
            <StatusMood/>
        </PresenceSubList>
    </Presence>
</GetAttributeList-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.41 Create group transaction

### 7.41.1 CreateGroup-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
    <Session>
        <SessionDescriptor>
            <SessionType>Inband</SessionType>
            <SessionID>im.user.com#48815@server.com</SessionID>
        </SessionDescriptor>
    </Session>
    <Transaction>
        <TransactionDescriptor>
            <TransactionMode>Request</TransactionMode>
            <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        </TransactionDescriptor>
        <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
            <CreateGroup-Request>
                <GroupID>wv:john/partygroup@there.com</GroupID>
                <GroupProperties>
                    <Property>
                        <Name>Name</Name>
                        <Value>Party discussion</Value>
                    </Property>
                </GroupProperties>
            </CreateGroup-Request>
        </TransactionContent>
    </Transaction>
</WV-CSP-Message>

```

```

    </Property>
  <Property>
    <Name>Accesstype</Name>
    <Value>Restricted</Value>
  </Property>
  <Property>
    <Name>PrivateMessaging</Name>
    <Value>F</Value>
  </Property>
  <Property>
    <Name>Searchable</Name>
    <Value>T</Value>
  </Property>
  <Property>
    <Name>Topic</Name>
    <Value>Party</Value>
  </Property>
  <Property>
    <Name>MaxActiveUsers</Name>
    <Value>30</Value>
  </Property>
  <WelcomeNote>
    <ContentType>text/plain</ContentType>
    <ContentData>Welcome to WV's party house
    </ContentData>
  </WelcomeNote>
</GroupProperties>
<JoinGroup>T</JoinGroup>
<ScreenName>
  <SName>Jonhhie</SName>
  <GroupID>wv:thisgroup/group@server.com</GroupID>
</ScreenName>
  <SubscribeNotification>T</SubscribeNotification>
</CreateGroup-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.41.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
          <Description>Successfully completed.</Description>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.42 Delete group transaction

### 7.42.1 DeleteGroup-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <DeleteGroup-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
        </DeleteGroup-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.42.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>

```

```

    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <Status>
      <Result>
        <Code>200</Code>
        <Description>Successfully completed.</Description>
      </Result>
    </Status>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.43 Join group transaction

### 7.43.1 JoinGroup-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <JoinGroup-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <JoinedRequest>T</JoinedRequest>
          <SubscribeNotification>T</SubscribeNotification>
        </JoinGroup-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.43.2 JoinGroup-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>

```

```

<TransactionDescriptor>
  <TransactionMode>Response</TransactionMode>
  <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  <Poll>F</Poll>
</TransactionDescriptor>
<TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
  <JoinGroup-Response>
    <UserList>
      <ScreenName>
        <SName>Johnny</SName>
        <GroupID>wv: john/partygroup@there.com</GroupID>
      </ScreenName>
      <ScreenName>
        <SName>He</SName>
        <GroupID>wv: john/partygroup@there.com</GroupID>
      </ScreenName>
      <ScreenName>
        <SName>She</SName>
        <GroupID>wv: john/partygroup@there.com</GroupID>
      </ScreenName>
      <ScreenName>
        <SName>Francisco</SName>
        <GroupID>wv: john/partygroup@there.com</GroupID>
      </ScreenName>
      <ScreenName>
        <SName>Matthias</SName>
        <GroupID>wv: john/partygroup@there.com</GroupID>
      </ScreenName>
    </UserList>
    <WelcomeNote>
      <ContentType>text/plain</ContentType>
      <ContentData>Welcome to WV's party house</ContentData>
    </WelcomeNote>
  </JoinGroup-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.44 User initiated leave group transaction

### 7.44.1 LeaveGroup-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>

```

```

    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <LeaveGroup-Request>
      <GroupID>wv:john/partygroup@there.com</GroupID>
    </LeaveGroup-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.44.2 LeaveGroup-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <LeaveGroup-Response>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <Result>
            <Code>200</Code>
            <Description>Own request.</Description>
          </Result>
        </LeaveGroup-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.45 Server initiated leave group transaction

### 7.45.1 LeaveGroup-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>

```

```

<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <LeaveGroup-Response>
      <GroupID>wv:john/partygroup@there.com</GroupID>
      <Result>
        <Code>809</Code>
        <Description>You have been rejected from this group.
        </Description>
      </Result>
    </LeaveGroup-Response>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.45.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.46 Get group member list transaction

### 7.46.1 GetGroupMembers-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">

```



```

<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <GetGroupMembers-Request>
      <GroupID>wv:john/partygroup@there.com</GroupID>
    </GetGroupMembers-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.46.2 GetGroupMembers-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
<Session>
<SessionDescriptor>
  <SessionType>Inband</SessionType>
  <SessionID>im.user.com#48815@server.com</SessionID>
</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Response</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
    <Poll>F</Poll>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <GetGroupMembers-Response>
      <Users>
        <UserList>
          <User><UserID>wv:he@there.com</UserID></User>
          <User><UserID>wv:she@there.com</UserID></User>
          <User><UserID>wv:john@smith.com</UserID></User>
          <User><UserID>wv:matthias@salamander.com</UserID></User>
          <User><UserID>wv:francisco@don.com</UserID></User>
        </UserList>
      </Users>
    </GetGroupMembers-Response>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.47 Add group members to a group transaction

### 7.47.1 AddGroupMembers-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <AddGroupMembers-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <UserList>
            <User><UserID>wv:he@there.com</UserID></User>
            <User><UserID>wv:she@there.com</UserID></User>
          </UserList>
        </AddGroupMembers-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.47.2 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

```

    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.48 Remove group members from a group transaction

### 7.48.1 RemoveGroupMembers-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <RemoveGroupMembers-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <UserList>
            <User>
              <UserID>wv:matthias@salamander.com</UserID>
            </User>
            <User><UserID>wv:john@smith.com</UserID></User>
            <User><UserID>wv:francisco@don.com</UserID></User>
            <User><UserID>wv:he@there.com</UserID></User>
            <User><UserID>wv:she@there.com</UserID></User>
          </UserList>
        </RemoveGroupMembers-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

### 7.48.2 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    </TransactionDescriptor>
    <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
      <Status>
        <Result>
          <Code>200</Code>
          <Description>Successfully completed.</Description>
        </Result>
      </Status>
    </TransactionContent>
  </Transaction>
</Session>
</WV-CSP-Message>

```

## 7.49 Changing access rights in a group transaction

### 7.49.1 MemberAccess-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <MemberAccess-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <Admin>
            <UserList>
              <User><UserID>wv:john@smith.com</UserID></User>
              <User><UserID>wv:francisco@don.com</UserID></User>
            </UserList>
          </Admin>
          <Users>
            <UserList>
              <User>
                <UserID>wv:matthias@salamander.com</UserID>
              </User>
              <User><UserID>wv:he@there.com</UserID></User>
              <User><UserID>wv:she@there.com</UserID></User>
            </UserList>
          </Users>
        </MemberAccess-Request>
      </TransactionContent>
    </Transaction>
  </Session>

```

```
</WV-CSP-Message>
```

## 7.49.2 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## 7.50 Modify group properties transaction

### 7.50.1 GetGroupProps-Request primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetGroupProps-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
        </GetGroupProps-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

```

</Session>
</WV-CSP-Message>

```

## 7.50.2 GetGroupProps-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GetGroupProps-Response>
          <GroupProperties>
            <Property>
              <Name>Name</Name>
              <Value>Party discussion</Value>
            </Property>
            <Property>
              <Name>Accesstype</Name>
              <Value>Restricted</Value>
            </Property>
            <Property>
              <Name>Type</Name>
              <Value>Private</Value>
            </Property>
            <Property>
              <Name>PrivateMessaging</Name>
              <Value>F</Value>
            </Property>
            <Property>
              <Name>Searchable</Name>
              <Value>T</Value>
            </Property>
            <Property>
              <Name>Topic</Name>
              <Value>Party</Value>
            </Property>
            <Property>
              <Name>ActiveUsers</Name>
              <Value>3</Value>
            </Property>
            <Property>
              <Name>MaxActiveUsers</Name>
              <Value>30</Value>
          </GroupProperties>
        </GetGroupProps-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    </Property>
    <WelcomeNote>
      <ContentType>text/plain</ContentType>
      <ContentData>Welcome to WV's party house</ContentData>
    </WelcomeNote>
  </GroupProperties>
  <OwnProperties>
    <Property>
      <Name>PrivateMessaging</Name>
      <Value>T</Value>
    </Property>
    <Property>
      <Name>IsMember</Name>
      <Value>T</Value>
    </Property>
    <Property>
      <Name>PrivilegeLevel</Name>
      <Value>Read</Value>
    </Property>
  </OwnProperties>
</GetGroupProps-Response>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

### 7.50.3 SetGroupProps-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <SetGroupProps-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <GroupProperties>
            <Property>
              <Name>Name</Name>
              <Value>Party house</Value>
            </Property>
            <Property>
              <Name>PrivateMessaging</Name>
              <Value>T</Value>
            </Property>
          </GroupProperties>
        </SetGroupProps-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

```

    <Property>
      <Name>MaxActiveUsers</Name>
      <Value>10</Value>
    </Property>
    <WelcomeNote>
      <ContentType>text/plain</ContentType>
      <ContentData>Welcome! Be gentle!</ContentData>
    </WelcomeNote>
  </GroupProperties>
</SetGroupProps-Request>
</TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.50.4 Status primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.51 Reject user from group transaction

### 7.51.1 RejectList-Request primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>

```



```

</SessionDescriptor>
<Transaction>
  <TransactionDescriptor>
    <TransactionMode>Request</TransactionMode>
    <TransactionID>IMApp01#12345@NOK5110</TransactionID>
  </TransactionDescriptor>
  <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
    <RejectList-Request>
      <GroupID>wv:john/partygroup@there.com</GroupID>
      <AddList>
        <UserID>wv:he@there.com</UserID>
        <UserID>wv:she@there.com</UserID>
      </AddList>
      <RemoveList>
        <UserID>wv:john@smith.com</UserID>
        <UserID>wv:matthias@salamander.com</UserID>
      </RemoveList>
    </RejectList-Request>
  </TransactionContent>
</Transaction>
</Session>
</WV-CSP-Message>

```

## 7.51.2 RejectList-Response primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <RejectList-Response>
          <UserList>
            <User><UserID>wv:he@there.com</UserID></User>
            <User><UserID>wv:she@there.com</UserID></User>
          </UserList>
        </RejectList-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.52 Subscribe group change notification transaction

### 7.52.1 SubscribeGroupNotice-Request primitive (get)

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <SubscribeGroupNotice-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <SubscribeType>G</SubscribeType>
        </SubscribeGroupNotice-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.52.2 SubscribeGroupNotice-Response primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12345@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <SubscribeGroupNotice-Response>
          <Value>F</Value>
        </SubscribeGroupNotice-Response>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.52.3 SubscribeGroupNotice-Request primitive (set)

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <SubscribeGroupNotice-Request>
          <GroupID>wv:john/partygroup@there.com</GroupID>
          <SubscribeType>S</SubscribeType>
        </SubscribeGroupNotice-Request>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

### 7.52.4 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12346@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
            <Description>Successfully completed.</Description>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## 7.52.5 GroupChangeNotice primitive

```

<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Request</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
        <Poll>F</Poll>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <GroupChangeNotice>
          <GroupID>wv: john/partygroup@there.com</GroupID>
          <Joined>
            <UserList>
              <ScreenName>
                <SName>Johnny</SName>
                <GroupID>wv: john/partygroup@there.com</GroupID>
              </ScreenName>
              <ScreenName>
                <SName>Franko</SName>
                <GroupID>wv: john/partygroup@there.com</GroupID>
              </ScreenName>
            </UserList>
          </Joined>
          <Left>
            <UserList>
              <ScreenName>
                <SName>He</SName>
                <GroupID>wv: john/partygroup@there.com</GroupID>
              </ScreenName>
              <ScreenName>
                <SName>She</SName>
                <GroupID>wv: john/partygroup@there.com</GroupID>
              </ScreenName>
            </UserList>
          </Left>
          <OwnProperties>
            <Property>
              <Name>PrivilegeLevel</Name>
              <Value>Mod</Value>
            </Property>
          </OwnProperties>
        </GroupChangeNotice>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>

```

## 7.52.6 Status primitive

```
<WV-CSP-Message xmlns="http://www.wireless-village.org/CSP1.1">
  <Session>
    <SessionDescriptor>
      <SessionType>Inband</SessionType>
      <SessionID>im.user.com#48815@server.com</SessionID>
    </SessionDescriptor>
    <Transaction>
      <TransactionDescriptor>
        <TransactionMode>Response</TransactionMode>
        <TransactionID>IMApp01#12347@NOK5110</TransactionID>
      </TransactionDescriptor>
      <TransactionContent xmlns="http://www.wireless-
village.org/TRC1.1">
        <Status>
          <Result>
            <Code>200</Code>
          </Result>
        </Status>
      </TransactionContent>
    </Transaction>
  </Session>
</WV-CSP-Message>
```

## **Appendix A. Static Conformance Requirements (Normative)**

The static conformance requirements for this specification is specified in [CSP SCR] and [SSP SCR].

**Appendix B. Change History****(Informative)**

Type of Change	Date	Section	Description
Class 0	2002-10-25		The initial version of this document.