



RESTful bindings for Parlay X Web Services – Short Messaging

Candidate Version 1.0 – 27 Apr 2010

Open Mobile Alliance
OMA-TS-ParlayREST_ShortMessaging-V1_0-20100427-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2010 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

Contents

1. SCOPE	9
2. REFERENCES	10
2.1 NORMATIVE REFERENCES	10
2.2 INFORMATIVE REFERENCES	10
3. TERMINOLOGY AND CONVENTIONS	11
3.1 CONVENTIONS	11
3.2 DEFINITIONS	11
3.3 ABBREVIATIONS	11
4. INTRODUCTION	12
4.1 VERSION 1.0	12
5. SHORT MESSAGING SERVICE (SMS) API DEFINITION	13
5.1 RESOURCES SUMMARY	13
5.2 SMS PARLAYREST API DATA STRUCTURES	19
5.2.1 Type: InboundSMSMessageList.....	19
5.2.2 Type: InboundSMSMessage	19
5.2.3 Type: InboundSMSMessageNotification.....	20
5.2.4 Type: SubscriptionList.....	20
5.2.5 Type: Subscription	20
5.2.6 Type: InboundSMSRetrieveAndDeleteMessageRequest.....	21
5.2.7 Type: OutboundSMSMessageRequestList	21
5.2.8 Type: OutboundSMSMessageRequest.....	22
5.2.9 Type: OutboundSMSTextMessage	23
5.2.10 Type: OutboundSMSLogoMessage	23
5.2.11 Type: OutboundSMSRingToneMessage	24
5.2.12 Type: DeliveryInfoList	24
5.2.13 Type: DeliveryInfoNotification	24
5.2.14 Type: DeliveryInfo.....	25
5.2.15 Type: DeliveryReceiptSubscriptionList.....	25
5.2.16 Type: DeliveryReceiptSubscription	25
5.2.17 Enumeration: DeliveryStatus	26
5.2.18 Enumeration: SmsFormat	27
5.2.19 Enumeration: RetrievalOrder.....	27
5.2.20 Values of the Link “rel” attribute.....	27
5.3 SEQUENCE DIAGRAMS	27
5.3.1 Send SMS and check the delivery status.....	27
5.3.2 Inbound SMS message delivery (push mode).....	28
5.3.3 Inbound SMS message delivery (polling mode).....	29
5.4 RESOURCE: INBOUND SMS MESSAGE REQUESTS FOR A GIVEN REGISTRATION	30
5.4.1 Request URI variables	30
5.4.2 Response Codes	31
5.4.2.1 <i>Response Codes</i>	31
5.4.2.2 <i>Exception fault codes</i>	31
5.4.3 GET.....	31
5.4.3.1 <i>Example 1: regular request (Informative)</i>	31
5.4.3.1.1 Request	31
5.4.3.1.2 Response.....	31
5.4.3.2 <i>Example 2: maxBatchSize exceeding the allowed size (Informative)</i>	32
5.4.3.2.1 Request	32
5.4.3.2.2 Response.....	32
5.4.4 PUT.....	33
5.4.5 POST.....	33
5.4.6 DELETE	33
5.5 RESOURCE: INBOUND SMS MESSAGES RETRIEVE AND DELETE USING REGISTRATION	33

- 5.5.1 Request URI variables 33
- 5.5.2 Response Codes 33
 - 5.5.2.1 Response Codes 33
 - 5.5.2.2 Exception fault codes 33
- 5.5.3 GET 34
- 5.5.4 PUT 34
- 5.5.5 POST 34
 - 5.5.5.1 Example (Informative) 34
 - 5.5.5.1.1 Request 34
 - 5.5.5.1.2 Response 34
- 5.5.6 DELETE 35
- 5.6 RESOURCE: INBOUND SMS MESSAGE FOR A GIVEN REGISTRATION 35**
- 5.6.1 Request URI variables 35
- 5.6.2 Response Codes 36
 - 5.6.2.1 HTTP Response Codes 36
- 5.6.3 GET 36
 - 5.6.3.1 Example 1: regular request (Informative) 36
 - 5.6.3.1.1 Request 36
 - 5.6.3.1.2 Response 36
 - 5.6.3.2 Example 2: invalid messageId (Informative) 36
 - 5.6.3.2.1 Request 36
 - 5.6.3.2.2 Response 37
- 5.6.4 PUT 37
- 5.6.5 POST 37
- 5.6.6 DELETE 37
 - 5.6.6.1 Example (Informative) 37
 - 5.6.6.1.1 Request 37
 - 5.6.6.1.2 Response 37
- 5.7 RESOURCE: INBOUND SMS MESSAGE SUBSCRIPTIONS 37**
- 5.7.1 Request URI variables 38
- 5.7.2 Response Codes 38
 - 5.7.2.1 HTTP Response Codes 38
 - 5.7.2.2 Exception fault codes 38
- 5.7.3 GET 38
 - 5.7.3.1 Example (Informative) 38
 - 5.7.3.1.1 Request 38
 - 5.7.3.1.2 Response 38
- 5.7.4 PUT 39
- 5.7.5 POST 39
 - 5.7.5.1 Example 1: returning a representation of created resource (Informative) 39
 - 5.7.5.1.1 Request 39
 - 5.7.5.1.2 Response 39
 - 5.7.5.2 Example 2: returning the location of created resource (Informative) 40
 - 5.7.5.2.1 Request 40
 - 5.7.5.2.2 Response 40
- 5.7.6 DELETE 40
- 5.8 RESOURCE: INDIVIDUAL INBOUND SMS MESSAGE SUBSCRIPTION 41**
- 5.8.1 Request URI variables 41
- 5.8.2 Response Codes 41
 - 5.8.2.1 HTTP Response Codes 41
 - 5.8.2.2 Exception fault codes 41
- 5.8.3 GET 41
 - 5.8.3.1 Example (Informative) 41
 - 5.8.3.1.1 Request 41
 - 5.8.3.1.2 Response 41
- 5.8.4 PUT 42
- 5.8.5 POST 42
- 5.8.6 DELETE 42
 - 5.8.6.1 Example (Informative) 42
 - 5.8.6.1.1 Request 42
 - 5.8.6.1.2 Response 42

5.9	RESOURCE: CLIENT NOTIFICATION ABOUT INBOUND SMS MESSAGE	42
5.9.1	Request URI variables	42
5.9.2	HTTP Response Codes	42
5.9.3	GET	43
5.9.4	PUT	43
5.9.5	POST	43
5.9.5.1	Example (Informative)	43
5.9.5.1.1	Request	43
5.9.5.1.2	Response	43
5.9.6	DELETE	43
5.10	RESOURCE: OUTBOUND SMS MESSAGE REQUESTS	43
5.10.1	Request URI variables	44
5.10.2	Response Codes	44
5.10.2.1	HTTP Response Codes	44
5.10.2.2	Exception fault codes	44
5.10.3	GET	44
5.10.3.1	Example (Informative)	44
5.10.3.1.1	Request	44
5.10.3.1.2	Response	44
5.10.4	PUT	45
5.10.5	POST	45
5.10.5.1	Example 1: returning representation of created resource in response (Informative)	45
5.10.5.1.1	Request	45
5.10.5.1.2	Response	46
5.10.5.2	Example 2: returning location of created resource in response (Informative)	47
5.10.5.2.1	Request	47
5.10.5.2.2	Response	47
5.10.6	DELETE	47
5.11	RESOURCE: OUTBOUND SMS MESSAGE REQUEST AND DELIVERY STATUS	47
5.11.1	Request URI variables	48
5.11.2	Response Codes	48
5.11.2.1	HTTP Response Codes	48
5.11.2.2	Exception fault codes	48
5.11.3	GET	48
5.11.3.1	Example (Informative)	48
5.11.3.1.1	Request	48
5.11.3.1.2	Response	48
5.11.4	PUT	49
5.11.5	POST	49
5.11.6	DELETE	49
5.12	RESOURCE: OUTBOUND SMS MESSAGE DELIVERY STATUS	49
5.12.1	Request URI variables	49
5.12.2	Response Codes	50
5.12.2.1	HTTP Response Codes	50
5.12.2.2	Exception fault codes	50
5.12.3	GET	50
5.12.3.1	Example (Informative)	50
5.12.3.1.1	Request	50
5.12.3.1.2	Response	50
5.12.4	PUT	51
5.12.5	POST	51
5.12.6	DELETE	51
5.13	RESOURCE: OUTBOUND SMS MESSAGE DELIVERY NOTIFICATION SUBSCRIPTIONS	51
5.13.1	Request URI variables	51
5.13.2	Response Codes	51
5.13.2.1	HTTP Response Codes	51
5.13.2.2	Exception fault codes	51
5.13.3	GET	52
5.13.3.1	Example (Informative)	52
5.13.3.1.1	Request	52

5.13.3.1.2	Response	52
5.13.4	PUT	52
5.13.5	POST	52
5.13.5.1	Example (Informative)	53
5.13.5.1.1	Request	53
5.13.5.1.2	Response	53
5.13.6	DELETE	53
5.14	RESOURCE: INDIVIDUAL OUTBOUND SMS MESSAGE DELIVERY NOTIFICATION SUBSCRIPTION	53
5.14.1	Request URI variables	54
5.14.2	HTTP Response Codes	54
5.14.2.1	HTTP Response Codes	54
5.14.2.2	Exception fault codes	54
5.14.3	GET	54
5.14.3.1	Example (Informative)	54
5.14.3.1.1	Request	54
5.14.3.1.2	Response	54
5.14.4	PUT	55
5.14.5	POST	55
5.14.6	DELETE	55
5.14.6.1	Example (Informative)	55
5.14.6.1.1	Request	55
5.14.6.1.2	Response	55
5.15	RESOURCE: CLIENT NOTIFICATION ABOUT OUTBOUND SMS MESSAGE DELIVERY STATUS	55
5.15.1	Request URI variables	55
5.15.2	HTTP Response Codes	56
5.15.3	GET	56
5.15.4	PUT	56
5.15.5	POST	56
5.15.5.1	Example (Informative)	56
5.15.5.1.1	Request	56
5.15.5.1.2	Response	56
5.15.6	DELETE	56
APPENDIX A.	CHANGE HISTORY (INFORMATIVE)	58
A.1	APPROVED VERSION HISTORY	58
A.2	DRAFT/CANDIDATE VERSION 1.0 HISTORY	58
APPENDIX B.	STATIC CONFORMANCE REQUIREMENTS (NORMATIVE)	61
B.1	SCR FOR PARLAYREST.SMS SERVER	61
B.1.1	SCR for ParlayREST.SMS.Inbound.Registration Server	61
B.1.2	SCR for ParlayREST.SMS.Inbound.Registration.RetrieveDelete Server	61
B.1.3	SCR for ParlayREST.SMS.Individual.Inbound Server	61
B.1.4	SCR for ParlayREST.SMS.Inbound.Subscr Server	62
B.1.5	SCR for ParlayREST.SMS.Inbound.Individual.Subscr Server	62
B.1.6	SCR for ParlayREST.SMS.Inbound.Notifications Server	62
B.1.7	SCR for ParlayREST.SMS.Outbound Server	62
B.1.8	SCR for ParlayREST.SMS.Outbound.MsgAndDeliveryStatus Server	63
B.1.9	SCR for ParlayREST.SMS.Outbound.DeliveryStatus Server	63
B.1.10	SCR for ParlayREST.SMS.Outbound.Subscriptions Server	63
B.1.11	SCR for ParlayREST.SMS.Individual.Outbound.Subscr Server	63
B.1.12	SCR for ParlayREST.SMS.Outbound.DeliveryStatus.Notifications Server	64
APPENDIX C.	APPLICATION/X-WWW-FORM-URLENCODED REQUEST FORMAT FOR SELECTED REST OPERATIONS	65
C.1	SEND A SMS TO A TERMINAL	65
C.1.1	Example (Informative)	66
C.1.1.1	Request	66
C.1.1.2	Response	66
C.2	REQUEST THE DELIVERY STATUS OF A SMS	67
C.2.1	Example (Informative)	67

C.2.1.1	Request.....	67
C.2.1.2	Response.....	67
C.3	RELIABLE RETRIEVAL OF RECEIVED SMS MESSAGES	68
C.3.1	Example (Informative).....	68
C.3.1.1	Request.....	68
C.3.1.2	Response.....	68
C.4	START DELIVERY RECEIPT NOTIFICATION	69
C.4.1	Example (Informative).....	69
C.4.1.1	Request.....	69
C.4.1.2	Response.....	70
C.5	NOTIFY SMS DELIVERY RECEIPT	70
C.5.1	Example (Informative).....	70
C.5.1.1	Request.....	70
C.5.1.2	Response.....	71
C.6	STOP DELIVERY RECEIPT NOTIFICATION.....	71
C.6.1	Example (Informative).....	71
C.6.1.1	Request.....	71
C.6.1.2	Response.....	71
C.7	START SMS NOTIFICATION.....	71
C.7.1	Example (Informative).....	72
C.7.1.1	Request.....	72
C.7.1.2	Response.....	72
C.8	NOTIFY SMS RECEPTION	73
C.8.1	Example (Informative).....	73
C.8.1.1	Request.....	73
C.8.1.2	Response.....	73
C.9	STOP SMS NOTIFICATION	73
C.9.1	Example (Informative).....	73
C.9.1.1	Request.....	73
C.9.1.2	Response.....	74
APPENDIX D.	JSON EXAMPLES (INFORMATIVE)	75
D.1	INBOUND MESSAGE DELIVERY (SECTION 5.4.3).....	75
D.2	MAXBATCHSIZE EXCEEDING THE ALLOWED SIZE (SECTION 5.4.3.2).....	76
D.3	RETRIEVE AND DELETE USING REGISTRATION (SECTION 5.5.5).....	76
D.4	INBOUND MESSAGES FOR A GIVEN REGISTRATION (SECTION 5.6.3.1).....	77
D.5	INVALID MESSAGEID (SECTION 5.6.3.2.1).....	77
D.6	REMOVE MESSAGE FROM GATEWAY STORAGE (SECTION 5.6.6).....	78
D.7	READ ACTIVE SUBSCRIPTIONS (SECTION 5.7.3).....	78
D.8	CREATE NEW MESSAGE SUBSCRIPTION (SECTION 5.7.5).....	79
D.9	RETURNING THE LOCATION OF CREATED RESOURCE (SECTION 5.7.5.2)	80
D.10	READ INDIVIDUAL SUBSCRIPTION (SECTION 5.8.3)	80
D.11	DELETE A SUBSCRIPTION (SECTION 5.8.6.1.1).....	81
D.12	NOTIFY CLIENT ABOUT MESSAGE ARRIVAL (SECTION 5.9.5).....	81
D.13	RETRIEVE LIST OF PENDING OUTBOUND MESSAGES (SECTION 5.10.3.1).....	81
D.14	CREATE OUTBOUND MESSAGE, RETURNING A REPRESENTATION OF CREATED RESOURCE (SECTION 5.10.5.1).....	82
D.15	CREATE OUTBOUND MESSAGE, RETURNING THE LOCATION OF CREATED RESOURCE (SECTION 5.10.5.2).....	84
D.16	GET MESSAGE DELIVERY STATUS (SECTION 5.11.3)	85
D.17	GET MESSAGE DELIVERY STATUS (SECTION 5.12.3)	85
D.18	READ DELIVERY NOTIFICATION SUBSCRIPTIONS (SECTION 5.13.3).....	86
D.19	CREATE DELIVERY NOTIFICATION SUBSCRIPTION (SECTION 5.13.5).....	86
D.20	READ DELIVERY NOTIFICATION SUBSCRIPTION (SECTION 5.14.3)	87
D.21	DELETE SUBSCRIPTION FOR A CLIENT (SECTION 5.14.6)	88
D.22	NOTIFY CLIENT ABOUT MESSAGE DELIVERY STATUS (SECTION 5.15.5).....	88

Figures

Figure 1	Resource structure defined by this specification	14
----------	--	----

Figure 1 Send SMS and check the delivery status28

Figure 2 Inbound SMS message delivery (push mode).....29

Figure 3 Inbound SMS message delivery (polling mode).....30

1. Scope

This specification defines an HTTP protocol binding for an abstract API using the REST architectural style, based on an existing OMA enabler namely the Short Messaging Service, as defined in [3GPP 29.199-4].

2. References

2.1 Normative References

- [3GPP 29.199-4] 3GPP Technical Specification, “Open Service Access (OSA); Parlay X Web Services; Part 4: Short messaging (Release 8)”, URL:<http://www.3gpp.org/>
- [REST_TS_Common] “RESTful bindings for Parlay X Web Services – Common”, Open Mobile Alliance™, OMA-TS-ParlayREST_Common-V1_0, URL:<http://www.openmobilealliance.org/>
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997, URL:<http://www.ietf.org/rfc/rfc2119.txt>
- [RFC2616] “Hypertext Transfer Protocol -- HTTP/1.1”, R. Fielding et. al, January 1999, URL:<http://www.ietf.org/rfc/rfc2616.txt>
- [RFC4234] “Augmented BNF for Syntax Specifications: ABNF”. D. Crocker, Ed., P. Overell. October 2005, URL:<http://www.ietf.org/rfc/rfc4234.txt>
- [RFC4627] “The application/json Media Type for JavaScript Object Notation (JSON)”, D. Crockford, July 2006, URL: <http://www.ietf.org/rfc/rfc4627.txt>
- [SCRRULES] “SCR Rules and Procedures”, Open Mobile Alliance™, OMA-ORG-SCR_Rules_and_Procedures, URL:<http://www.openmobilealliance.org/>
- [W3C-URLENC] W3C HTML 2.0 Specification, form-urlencoded Media Type, URL: http://www.w3.org/MarkUp/html-spec/html-spec_8.html#SEC8.2.1
- [XMLSchema1] W3C Recommendation, XML Schema Part 1: Structures Second Edition, URL: <http://www.w3.org/TR/xmlschema-1/>
- [XMLSchema2] W3C Recommendation, XML Schema Part 2: Datatypes Second Edition, URL: <http://www.w3.org/TR/xmlschema-2/>

2.2 Informative References

- [OMADICT] “Dictionary for OMA Specifications”, Version 2.7, Open Mobile Alliance™, OMA-ORG-Dictionary-V2_7, URL:<http://www.openmobilealliance.org/>
- [REST_WP] “White Paper on Guidelines for ParlayREST API specifications”, Open Mobile Alliance™, OMA-WP-Guidelines_for_ParlayREST_API_specifications, URL:<http://www.openmobilealliance.org/>

3. Terminology and Conventions

3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

3.2 Definitions

For the purpose of this TS, all definitions from the OMA Dictionary apply [OMA-DICT].

[N/A]

[N/A]

3.3 Abbreviations

API	Application Programming Interface
EMS	Enhanced Message Service
HTTP	HyperText Transfer Protocol
ISDN	Integrated Services Digital Network
JSON	JavaScript Object Notation
MSISDN	Mobile Subscriber ISDN Number
OMA	Open Mobile Alliance
PX	Parlay X
REST	REpresentational State Transfer
SCR	Static Conformance Requirements
SMS	Short Message Service
TS	Technical Specification
URI	Uniform Resource Identifier
URL	Uniform Resource Locator
WAP	Wireless Application Protocol
XML	eXtensible Markup Language
XSD	XML Schema Definition

4. Introduction

The ParlayREST Technical Specification for SMS contains the HTTP protocol binding for the Parlay X Short Messaging Web Services specification, using the REST architectural style. The specification provides resource definitions, the HTTP verbs applicable for each of these resources, and the element data structures, as well as support material including flow diagrams and examples using the various supported message body formats (i.e. XML, JSON, and form-urlencoded).

4.1 Version 1.0

Version 1.0 of the Short Messaging Service ParlayREST API specification supports the following operations:

- Send text message to a terminal
- Check delivery status of the outgoing message
- Check incoming messages (polling mode)
- Create subscriptions for notifications for inbound messages based on given criteria (online)
- Delete subscriptions for notifications for inbound messages (online)
- Create subscriptions for notifications for outbound messages based on given criteria (online)
- Delete subscriptions for notifications for outbound messages (online)
- Retrieve message content
- Confirm message retrieval by deleting message (execute delete command)

5. Short Messaging Service (SMS) API definition

This section is organized to support a comprehensive understanding of the SMS API design. It specifies the definition of all resources, definition of all data structures, and definitions of all operations permitted on the specified resources.

The terms “inbound” and “outbound” used in resource names and data structures refer to incoming, respectively outgoing messages from the client of the API perspective. The term “subscription” refers to the online creation of resources (using requests in this specification). The term “registration” refers to the offline creation of resources using mechanisms out of scope of this specification. The resources created during registrations as well as subscriptions can generate notifications, for example about the delivery status of outgoing SMSs (subscription), or about incoming messages (registration).

Common data types, naming conventions, fault definitions and namespaces are defined in [REST_TS_Common].

The remainder of this document is structured as follows:

Section 5 starts with a table listing all the resources (and their URL) used by this API, along with the data structure and the supported HTTP verbs (section 5.1). In addition, for each supported resource/verb combination, the table lists the Parlay X equivalent operation, where applicable. What follows are the data structures (section 5.2). A sample of typical use cases is included in section 5.3, described as high level flow diagrams.

The remaining subsections in section 5 contain the detailed specification for each of the resources. Each such subsection defines the resource, the request URI variables that are common for all HTTP commands, the possible HTTP response codes, and the supported HTTP verbs. For each supported HTTP verb, a description of the functionality is provided, along with an example of a request and an example of a response. For each unsupported HTTP verb, the returned HTTP error status is specified, as well as what should be returned in the Allow header.

All examples in section 5 use XML as the format for the message body. Form-urlencoded examples are provided in Appendix C, while JSON examples are provided in Appendix D. Appendix B provides the Static Conformance Requirements (SCR).

Note: Throughout this document client and application can be used interchangeably.

5.1 Resources Summary

This section summarizes all the resources used by the SMS API. The resources are defined with the goal of supporting unified messaging, to allow their re-use by other APIs.

The figure below visualizes the resource structure defined by this specification. Note that those nodes in the resource tree which have associated HTTP methods defined in this specification are depicted by solid boxes.




Figure 1 Resource structure defined by this specification

The following table gives a detailed overview of the resources defined in this specification, the data type of their representation and the allowed HTTP methods. The “PX“ row indicates the Parlay X SOAP equivalent operation. When the row indicates ‘Partial PX Equivalent’, further explanations are included in the chapter that details the associated Resource Operation.

Purpose: Inbound messages for periodic polling (based on a provisioning step configuration)

Resource	URL Base URL: http://{serverRoot}/{apiVersion}/smsmessaging	Data Structures	HTTP verbs			
			GET	POST	PUT	DELETE
Inbound SMS messages requests for a given registration Note: Used by clients that periodically poll for incoming messages. Retrieval criteria have to be provisioned in advance.	/inbound/registrations/{registrationId}/messages	InboundSMSMessageList	read one or more messages from gateway storage	no	no	no
			Partial PX equivalent			
Inbound SMS messages Retrieve and Delete using registration	/inbound/registrations/{registrationId}/retrieveAndDeleteMessages	InboundSMSMessageList InboundSMSMessageRetrieveAndDeleteRequest	no	pops one or more messages from the gateway storage (removes it if successful)	no	no
				PX: GetReceivedSMS		
Inbound SMS message for a given registration	/inbound/registrations/{registrationId}/messages/{messageId}	InboundSMSMessage	read one message from gateway storage	no	no	delete one message from gateway storage Note: Messages are automatically deleted after a certain time.
			PX: GetReceivedSMS			Partial PX equivalent

Purpose: Subscriptions Management for Inbound Messages

Resource	URL Base URL: http://{serverRoot}/{apiVersion}/smsmessaging	Data Structures	HTTP verbs			
			GET	POST	PUT	DELETE
Inbound SMS message subscriptions	/inbound/subscriptions	SubscriptionList	read all active subscriptions	create new message subscription	no	no
			No PX equivalent	PX: StartSmsNotification		
Individual inbound SMS message subscription	/inbound/subscriptions/{subscriptionId}	Subscription	read individual subscription	no	no	removes subscription and stops corresponding message notifications
			No PX equivalent			PX: StopSmsNotification

Purpose: Callback notifications for Inbound messages

Resource	URL <specified by the client>	Data Structures	HTTP verbs			
			GET	POST	PUT	DELETE
Client notification about inbound SMS message	<specified by the client when subscription is created or during provisioning process>	InboundSMSMessageNotification	no	notifies client about new inbound message	no	no
				PX: NotifySmsReception		

Purpose: Sending SMS and obtaining the Delivery Status

Resource	URL Base URL: http://{serverRoot}/{apiVersion}/smsmessaging	Data Structures	HTTP verbs			
			GET	POST	PUT	DELETE
Outbound SMS message requests	/outbound/{senderAddress}/requests	OutboundSMSMessageRequest OutboundSMSMessageRequestList	read all pending outbound message requests	create new outbound messages request	no	no
			No PX equivalent	PX: SendSMS		
Outbound SMS message request and delivery status	/outbound/{senderAddress}/requests/{requestId}	OutboundSMSMessageRequest	read a certain sent SMS message, including the deliveryStatus	no	no	no
			No PX equivalent			
Outbound SMS message delivery status	/outbound/{senderAddress}/requests/{requestId}/deliveryInfos	DeliveryInfoList	read delivery status for the individual outbound message	no	no	no
			PX: GetSmsDeliveryStatus			

Purpose: Subscription Management for Outbound Message Delivery Status

Resource	URL Base URL: http://{serverRoot}/{apiVersion}/smsmessaging	Data Structures	HTTP verbs			
			GET	POST	PUT	DELETE
Outbound SMS message delivery notification subscriptions	/outbound/{senderAddress}/subscriptions	DeliveryReceiptSubscriptionList DeliveryReceiptSubscription	read all outbound SMS subscriptions	create new delivery receipt subscription	no	no
			No PX equivalent	PX: StartDeliveryReceiptNotification		
Individual outbound SMS message delivery notification subscription	/outbound/{senderAddress}/subscriptions/{subscriptionId}	DeliveryReceiptSubscription	read an individual outbound SMS subscription	no	no	remove subscription and stop corresponding delivery receipt notifications
			No PX equivalent			PX: StopDeliveryReceiptNotification

Purpose: Callback notifications for Outbound Message Delivery Status

Resource	URL <specified by the client>	Data Structures	HTTP verbs			
			GET	POST	PUT	DELETE
Client notification about outbound SMS message delivery status	<specified by the client when outbound request is submitted>	DeliveryInfoNotification	no	Notifies client about delivery status of outgoing requests	no	no
				PX: NotifySMSDeliveryReceipt		

5.2 SMS ParlayREST API Data Structures

The namespace for the ShortMessaging data types is:

urn:oma:xml:rest:sms:1

The 'xsd' namespace is used in the present document to refer to the XML Schema data types defined in XML Schema [XMLSchema1, XMLSchema2]. The 'common' namespace is used in the present document to refer to the data types defined in [REST_TS_Common]. The use of the names 'xsd' and 'common' is not semantically significant.

5.2.1 Type: InboundSMSMessageList

List of received SMS.

Element	Type	Optional	Description
inboundSMSMessage	InboundSMSMessage [0..unbounded]	Yes	It may contain an array of messages received according to the specified {registrationId}.
totalNumberOfPendingMessages	xsd:int	Yes	Total number of messages in the gateway storage waiting for retrieval at the time of the request
numberOfMessagesInThisBatch	xsd:int	Yes	Number of the messages included in the response (part of the totalNumberOfPendingMessages)
resourceURL	xsd:anyURI	No	Self referring URL

A root element named inboundSMSMessageList of type InboundSMSMessageList is allowed in request and/or response bodies.

5.2.2 Type: InboundSMSMessage

Individual incoming SMS.

Element	Type	Optional	Description
destinationAddress	xsd:anyURI	No	Number associated with the invoked Message service, i.e. the destination address used by the terminal to send the message.
senderAddress	xsd:anyURI	No	Indicates message senderAddress.
message	xsd:string	No	Text of the message
dateTime	xsd:dateTime	Yes	Time when message was received by operator
resourceURL	xsd:anyURI	Yes	Self referring URL

link	common:Link[0..unbounded]	Yes	Links to other resources that are in relationship with the resource
messageId	xsd:string	Yes	OPTIONAL server-generated message Identifier

A root element named inboundSMSMessage of type InboundSMSMessage is allowed in request and/or response bodies.

5.2.3 Type: InboundSMSMessageNotification

Element	Type	Optional	Description
callbackData	xsd:string	Yes	CallbackData as passed by the application during the associated Send SMS operation. See [REST_TS_Common], section 6.2.4.
inboundSMSMessage	InboundSMSMessage	No	SMS message
link	common:Link[0..unbounded]	Yes	Link to other resources. For example we can have a link to the original outbound message request.

A root element named inboundSMSMessageNotification of type InboundSMSMessageNotification is allowed in request and/or response bodies.

5.2.4 Type: SubscriptionList

Element	Type	Optional	Description
subscription	Subscription[0..unbounded]	Yes	It may contain an array of Subscription
resourceURL	xsd:anyURI	Yes	Self referring URL

A root element named subscriptionList of type SubscriptionList is allowed in request and/or response bodies.

5.2.5 Type: Subscription

Element	Type	Optional	Description
callbackReference	common:CallbackReference	No	Client's Notification URL and OPTIONAL callbackData
destinationAddress	xsd:anyURI [1..unbounded]	No	the destination address of the short message
criteria	xsd:string	Yes	The text to match against to determine the application to receive

			the notification. This text is matched against the first word, as defined as the initial characters after discarding any leading Whitespace and ending with a Whitespace or end of the string. The matching shall be case-insensitive.
clientCorrelator	xsd:string	Yes	A correlator that the client MAY use to tag this particular resource representation during a request to create a resource on the server. In case the field is present, the server SHALL not alter its value, and SHALL provide it as part of the representation of this resource. In case the field is not present, the server SHALL NOT generate it.
resourceURL	xsd:anyURI	Yes	Self referring URL
link	common:Link[0..unbounded]	Yes	Links to other resources that are in relationship with the resource

A root element named subscription of type Subscription is allowed in request and/or response bodies.

Note that the clientCorrelator is used for purposes of error recovery as specified in section 5.6.1 of [REST_TS_Common], and internal client purposes. The server is NOT REQUIRED to use the clientCorrelator value in any form in the creation of the URL of the resource. Section 5.6.1 of [REST_TS_Common] provides a recommendation regarding the generation of the value of this field.

5.2.6 Type: InboundSMSRetrieveAndDeleteMessageRequest

Element	Type	Optional	Description
retrievalOrder	RetrievalOrder	Yes	Specifies order in which messages should be retrieved if there are more than one pending
maxBatchSize	xsd:int	Yes	Specifies maximum number of messages to be returned in the response

A root element named_inboundSMSRetrieveAndDeleteMessageRequest of type InboundSMSRetrieveAndDeleteMessageRequest is allowed in request and/or response bodies.

5.2.7 Type: OutboundSMSMessageRequestList

Element	Type	Optional	Description
outboundSMSMessageRequest	OutboundSMSMessageRequest [0..unbounded]	Yes	The messages that have been sent by the API Consumer and still exist

			in the server (and hence the messages that can be accessed by the API Consumer). Messages exist in the server for a little time after reaching their final Delivery Status
resourceURL	xsd:anyURI	Yes	Self referring URL

A root element named `outboundSMSMessageRequestList` of type `OutboundSMSMessageRequestList` is allowed in request and/or response bodies.

5.2.8 Type: OutboundSMSMessageRequest

Element	Type	Optional	Description
address	xsd:anyURI [1..unbounded]	No	Destination addresses for the Message.
senderAddress	xsd:anyURI	No	User Identity of the Sender of the message. The associated MSISDN will appear in the receiver terminal, unless a senderName is specified. This parameter shall match the User's Identity included in the Authorization header.
senderName	xsd:string	Yes	Name of the sender to appear on the user's terminal as the originator of the message. If this parameter is used, a set of allowed values shall be set during provisioning each sender (i.e.: for each User provisioned in the System).
charging	common:Charging Information	Yes	Charging to apply to this message.
receiptRequest	common:CallbackReference	Yes	It defines the application endpoint and OPTIONAL callbackData that will be used to notify the application when the message has been delivered to terminal or if delivery is impossible.
outboundSMSTextMessage	OutboundSMSTextMessage	Choice	Included if a SMSText is being Sent.
outboundSMSLogoMessage	OutboundSMSLogoMessage	Choice	Included if a SMSLogo is being Sent.
outboundSMSRingToneMessage	OutboundSMSRingToneMessage	Choice	Included if a SMSRingtone is being Sent.

clientCorrelator	xsd:string	Yes	<p>A correlator that the client can use to tag this particular resource representation during a request to create a resource on the server.</p> <p>This field SHOULD be present. Note: this allows the client to recover from communication failures during resource creation and therefore avoids re-sending the message in such situations.</p> <p>In case the field is present, the server SHALL not alter its value, and SHALL provide it as part of the representation of this resource. In case the field is not present, the server SHALL NOT generate it.</p>
resourceURL	xsd:anyURI	Yes	Self referring URL
link	common:Link[0..unbounded]	Yes	Links to other resources that are in relationship with the resource
deliveryInfoList	DeliveryInfoList	Yes	The Delivery Information (filled in by the server)

XSD modelling use a “choice” to select either a SMSText, a SMSLogo or a SMSRingTone.

A root element named outboundSMSMessageRequest of type OutboundSMSMessageRequest is allowed in request and/or response bodies.

Note that the clientCorrelator is used for purposes of error recovery as specified in section 5.6.1 of [REST_TS_Common], and internal client purposes. The server is NOT REQUIRED to use the clientCorrelator value in any form in the creation of the URL of the resource. Section 5.6.1 of [REST_TS_Common] provides a recommendation regarding the generation of the value of this field.

5.2.9 Type: OutboundSMSTextMessage

Element	Type	Optional	Description
message	xsd:string	No	Short message content.

5.2.10 Type: OutboundSMSLogoMessage

Element	Type	Optional	Description
image	xsd:base64Binary	No	The image in jpeg, gif or png format. The image will be scaled to the proper format

smsFormat	SMSFormat	No	Conversion to be applied to the message prior to delivery. Possible values are: 'Ems' or 'SmartMessaging'
-----------	-----------	----	---

5.2.11 Type: OutboundSMSRingToneMessage

Element	Type	Optional	Description
ringTone	xsd:string	No	The ring tone in RTX format. Note: In the RTX Ring tone Specification, an RTX file is a text file, containing the ring tone name, a control subclause and a subclause containing a comma separated sequence of ring tone commands.
smsFormat	SmsFormat	No	Conversion to be applied to the message prior to delivery. Possible values are: 'Ems' or 'SmartMessaging'

5.2.12 Type: DeliveryInfoList

Element	Type	Optional	Description
resourceURL	xsd:anyURI	No	Self referring URL
link	common:Link[0..unbounded]	Yes	Links to other resources that are in relationship with the resource.
deliveryInfo	DeliveryInfo[1...unbounded]	No	Delivery Information

A root element named deliveryInfoList of type DeliveryInfoList is allowed in request and/or response bodies.

5.2.13 Type: DeliveryInfoNotification

Element	Type	Optional	Description
callbackData	xsd:string	Yes	CallbackData if passed by the application in the receiptRequest element during the associated Send SMS operation. See [REST_TS_Common], section 6.2.4.
deliveryInfo	DeliveryInfo[1...unbounded]	No	Delivery Information
link	common:Link[0..unbounded]	Yes	Links to other resources that are in relationship to the current

			resource. For example we can have a link to the original outbound message request.
--	--	--	--

A root element named deliveryInfoNotification of type DeliveryInfoNotification is allowed in request and/or response bodies.

5.2.14 Type: DeliveryInfo

Element	Type	Optional	Description
address	xsd:anyURI	No	Outbound message destination address
deliveryStatus	DeliveryStatus	No	Indicates the delivery result for the destination address.
description	xsd:string	Yes	Used together with Delivery Status (e.g.DeliveryImpossible) to provide additional information.
link	common:Link[0..unbounded]	Yes	Links to other resources that are in relationship with the resource. For example we can have a link to the original outbound message request.

5.2.15 Type: DeliveryReceiptSubscriptionList

Element	Type	Optional	Description
resourceURL	xsd:anyURI	No	Self referring URL
link	common:Link[0..unbounded]	Yes	Link to other resources that are in relationship with the resource
deliveryReceiptSubscription	DeliveryReceiptSubscription[0...unbounded]	Yes	Delivery Subscription Information

A root element named deliveryReceiptSubscriptionList of type DeliveryReceiptSubscriptionList is allowed in request and/or response bodies.

5.2.16 Type: DeliveryReceiptSubscription

Element	Type	Optional	Description
---------	------	----------	-------------

callbackReference	common:CallbackReference	No	Notification endpoint definition
filterCriteria	xsd:string	No	The FilterCriteria will allow the service to filter flexibly. One example would be for the Service Provider to filter based on first 4 digits in MSISDN. This however is implementation specific and will be left to the Service Provider.
clientCorrelator	xsd:string	Yes	A correlator that the client MAY use to tag this particular resource representation during a request to create a resource on the server. In case the field is present, the server SHALL not alter its value, and SHALL provide it as part of the representation of this resource. In case the field is not present, the server SHALL NOT generate it.
resourceURL	xsd:anyURI	Yes	Self referring URL
link	common:Link[0..unbounded]	Yes	Link to other resources that are in relationship with the resource.

A root element named deliveryReceiptSubscription of type DeliveryReceiptSubscription is allowed in request and/or response bodies.

Note that the clientCorrelator is used for purposes of error recovery as specified in section 5.6.1 of [REST_TS_Common], and internal client purposes. The server is NOT REQUIRED to use the clientCorrelator value in any form in the creation of the URL of the resource. Section 5.6.1 of [REST_TS_Common] provides a recommendation regarding the generation of the value of this field.

5.2.17 Enumeration: DeliveryStatus

Enumeration	Description
DeliveredToTerminal	Successful delivery to Terminal.
DeliveryUncertain	Delivery status unknown: e.g. because it was handed off to another network.
DeliveryImpossible	Unsuccessful delivery; the message could not be delivered before it expired.
MessageWaiting	The message is still queued for delivery. This is a temporary state, pending transition to one of the preceding states.
DeliveredToNetwork	Successful delivery to the network enabler responsible for distributing the short message further in the network.
DeliveryNotificationNotSupported	Unable to provide delivery receipt notification. NotifyMessageDeliveryReceipt function will provide DeliveryNotificationNotSupported to indicate that delivery receipt for the specified address in a SendMessageRequest is not supported.

5.2.18 Enumeration: SmsFormat

Enumeration	Description
Ems	EMS conversion
SmartMessaging	SmartMessaging conversion

5.2.19 Enumeration: RetrievalOrder

Enumeration	Description
OldestFirst	Retrieve in the order from oldest to newest
NewestFirst	Retrieve in the order from newest to oldest

5.2.20 Values of the Link “rel” attribute

The “rel” attribute of the Link element is a free string set by the server implementation, to indicate a relationship between the current resource and an external resource. The following are possible strings (list is non-exhaustive, and can be extended):

- InboundSMSMessage
- InboundSMSMessageList
- Subscription
- SubscriptionList
- OutboundSMSMessageRequest
- OutboundSMSMessageRequestList
- DeliveryInfoList
- DeliveryReceiptSubscription
- DeliveryReceiptSubscriptionList

These values indicate the kind of resource that the link points to.

5.3 Sequence Diagrams

5.3.1 Send SMS and check the delivery status

This figure below shows a scenario for sending a short message and get the delivery status of the message.

The resources:

- To send a short message, create new resource under
http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests
- To get the delivery status of the message, do either a or b:

- a. read the newly created resource including the delivery status of the message
http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}
- b. directly read the resource
http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}/deliveryInfos




Figure 2 Send SMS and check the delivery status

Outline of the flows:

1. An application initiates the creation of new outbound SMS request using POST and receives the created request resource with a resource URL containing the requestId.
2. The application requests the resource of the sent message with the given resource URL (containing the requestId) using GET and optionally gets the delivery status, or
3. The application requests the delivery status of the sent message with the given delivery info list URL using GET and gets the status.

5.3.2 Inbound SMS message delivery (push mode)

This figure below shows a scenario for starting notification of inbound SMS with specific criteria on-line and receiving it when the message having the specified criteria arrives.

The resources:

- To start subscription to notifications for inbound SMS messages, create new resource under
http://{serverRoot} /{apiVersion}/smsmessaging/inbound/subscriptions

- To notify the application about the message arrival, POST a notification to the client supplied notifyURL
- To stop the subscription to notifications, delete the resource

http://{serverRoot} /{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}




Figure 3 Inbound SMS message delivery (push mode)

Outline of the flows:

1. An application subscribes to notifications for inbound messages using POST and receives the resulting resourceURL containing the subscriptionId.
2. When the message which satisfies the specified criteria arrives, the REST service notifies the application of the incoming message using POST so that the application receives the message.
3. The application stops the notification subscription using DELETE with a resource URL containing the subscriptionId.

5.3.3 Inbound SMS message delivery (polling mode)

This figure below shows a scenario for checking for incoming messages using retrieval criteria that are set up offline, and deleting one message from the gateway storage.

The resources:

- To retrieve incoming messages satisfying the criteria set up in advance, get the resource
http://{serverRoot} /{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages
- To remove one message from the storage, delete the resource

http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}




Figure 4 Inbound SMS message delivery (polling mode)

Outline of the flows:

1. In advance, the notification of SMS reception with specific criteria is registered offline.
2. An application requests the list of the incoming messages fulfilling specified criteria using GET with a resource URL containing the registrationId and receives the messages.
3. The application removes one of the messages from gateway storage using DELETE with a resource URL containing the messageId .

5.4 Resource: Inbound SMS message requests for a given registration

The resource used is:

http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages

This resource is used for checking for incoming messages using a retrieval criterion that is setup in advance for a particular client (offline - during provisioning process: sms short codes, etc).

5.4.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
------	-------------

serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API clients want to use (e.g. 1 for version 1.x)
registrationId	reference to the off-line retrieval criteria provisioned in advance and known to the client application. Analogous to ParlayX registrationIdentifier

5.4.2 Response Codes

5.4.2.1 Response Codes

For HTTP response codes, see [REST_TS_Common].

5.4.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.4.3 GET

This operation is used for reliable inbound message delivery for the particular client. Messages will remain on the server until client will confirm successful retrieval by executing DELETE command for each individual message (see DELETE on Inbound SMS message).

Note: ParlayX SOAP equivalent is GetReceivedSms, but not quite the same because DELETE of individual message is required for confirmation of successful retrieval (see DELETE on Inbound SMS message).

Request URL parameters are:

Name	Type/Values	Optional	Description
maxBatchSize	xsd:int	Yes	Specifies maximum number of messages to be returned in the response
retrievalOrder	RetrievalOrder	Yes	Specifies order in which messages should be retrieved is there are more then one pending

5.4.3.1 Example 1: regular request

(Informative)

5.4.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=2 HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.4.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
```

```

Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:inboundSMSMessageList xmlns:sms="urn:oma:xml:rest:sms:1">
  <inboundSMSMessage>
    <destinationAddress>MSISDN1</destinationAddress>
    <senderAddress>MSISDN2</senderAddress>
    <message>First simple message</message>
    <dateTime>2009-11-19T12:00:00</dateTime>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId1}
    </resourceURL>
    <messageId>{messageId1}</messageId>
  </inboundSMSMessage>
  <inboundSMSMessage>
    <destinationAddress>MSISDN1</destinationAddress>
    <senderAddress>MSISDN3</senderAddress>
    <message>Second simple message</message>
    <dateTime>2009-11-19T12:00:00</dateTime>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId2}
    </resourceURL>
    <messageId>{messageId2}</messageId>
  </inboundSMSMessage>
  <!-- further instances of InboundSMSMessage if needed -->
  <totalNumberOfPendingMessages>20</totalNumberOfPendingMessages>
  <numberOfMessagesInThisBatch>2</numberOfMessagesInThisBatch>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages</resourceURL>
</sms:inboundSMSMessageList>

```

5.4.3.2 Example 2: maxBatchSize exceeding the allowed size (Informative)

5.4.3.2.1 Request

```

GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=5000 HTTP/1.1
Accept: application/xml
Host: example.com:80

```

5.4.3.2.2 Response

```

HTTP/1.1 400 Bad Request
Content-Type: application/xml
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<common:requestError xmlns:common="urn:oma:xml:rest:common:1">
  <link rel="InboundSMSMessageList"
    href="http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=5000" />
  <policyException>
    <messageId>POL0001</messageId>
    <text>A policy error occurred. Error code is maxBatchSize exceeded. The maximum allowed maxBatchSize is %1.</text>
    <variables>20</variables>
  </policyException>
</common:requestError>

```

```
</policyException>
</common:requestError>
```

5.4.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.4.5 POST

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.4.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.5 Resource: Inbound SMS messages Retrieve and Delete using registration

The resource used is:

http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/retrieveAndDeleteMessages

This resource is used for retrieving and deleting incoming messages using retrieval criteria that is setup in advance (offline - during provisioning process: sms short codes, etc) for a particular client.

5.5.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API clients want to use (e.g. 1 for version 1.x)
registrationId	reference to the off-line retrieval criteria provisioned in advance and known to the client application. Analogous to ParlayX registrationIdentifier

5.5.2 Response Codes

5.5.2.1 Response Codes

For HTTP response codes, see [REST_TS_Common].

5.5.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.5.3 GET

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: POST' field in the response as per section 14.7 of [RFC 2616].

5.5.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: POST' field in the response as per section 14.7 of [RFC 2616].

5.5.5 POST

This operation retrieves one or more messages from the gateway storage for a particular client. If retrieval is successful, it will delete message from gateway.

Notes: POST is used because resource state would be altered as result of the execution. GET is not a good fit here because it has to be idempotent. Client guidelines:

- 1) Should NOT be used for reliable message delivery (see GET for reliable delivery). This is an optional alternative to the use of GET and DELETE on the .../inbound/registrations resource.
- 2) Default number of messages that would be returned in one batch is controlled by server configuration.
- 3) Messages would be automatically deleted from gateway storage following a successful POST, after a maximum time interval as defined by a service policy.

Note: ParlayX SOAP equivalent is GetReceivedSMS.

Parameters are passed in the request body using the InboundSMSRetrieveAndDeleteMessageRequest data structure.

5.5.5.1 Example

(Informative)

5.5.5.1.1 Request

```
POST .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/retrieveAndDeleteMessages HTTP/1.1
Accept: application/xml
Content-Length: nnn
Content-Type: application/xml; charset=UTF-8
Host: example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:inboundSMSRetrieveAndDeleteMessageRequest xmlns:sms="urn:oma.xml:rest:sms:1">
<retrievalOrder>OldestFirst</retrievalOrder>
<maxBatchSize>3</maxBatchSize>
</sms:inboundSMSRetrieveAndDeleteMessageRequest>
```

5.5.5.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: nnnn
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
```

```

<sms:inboundSMSMessageList xmlns:sms="urn:oma:xml:rest:sms:1">
  <!-- SMS -->
  <inboundSMSMessage>
    <destinationAddress>{shortCode1}</destinationAddress>
    <senderAddress>{MSISDN1}</senderAddress>
    <message>First simple message</message>
    <messageId>{messageId1}</messageId>
    <!-- no message resourceURL because SMS will be deleted from server immediately after operation is completed -->
  </inboundSMSMessage>
  <!-- SMS -->
  <inboundSMSMessage>
    <destinationAddress>{shortCode2}</destinationAddress>
    <senderAddress>{MSISDN2}</senderAddress>
    <message>Second simple message</message>
    <messageId>{messageId2}</messageId>
    <!-- no message resourceURL because SMS will be deleted from server immediately after operation is completed -->
  </inboundSMSMessage>
  <totalNumberOfPendingMessages>200</totalNumberOfPendingMessages>
  <numberOfMessagesInThisBatch>2</numberOfMessagesInThisBatch>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}</resourceURL>
</sms:inboundSMSMessageList>

```

5.5.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: POST’ field in the response as per section 14.7 of [RFC 2616].

5.6 Resource: Inbound SMS message for a given registration

The resource used is:

http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}

This resource provides access to individual inbound SMS message stored by gateway. Combination of GET/DELETE is used by clients that are polling incoming messages and require reliable delivery. Each message would have to be deleted separately as a confirmation of successful retrieval.

5.6.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API clients want to use (e.g. 1 for version 1.x)
registrationId	reference to the off-line retrieval criteria provisioned in advance and known to the client application. Analogous to ParlayX registrationIdentifier
messageId	unique message Identifier generated by server

5.6.2 Response Codes

5.6.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.6.3 GET

Read one message from gateway storage. Message is not deleted. Delete command need to be executed to confirm delivery and free resources occupied by the message and associated attachments.

Note: No equivalent ParlayX SOAP API for SMS.

5.6.3.1 Example 1: regular request

(Informative)

5.6.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}?resFormat=XML HTTP/1.1
Host: example.com:80
```

The sample request above also illustrates the use of the “resFormat” parameter.

5.6.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:inboundSMSMessage xmlns:sms="urn:oma:xml:rest:sms:1">
  <destinationAddress>MSISDN1</destinationAddress>
  <senderAddress>MSISDN2</senderAddress>
  <message>First simple message</message>
  <dateTime>2009-11-19T12:00:00</dateTime>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}
</resourceURL>
  <messageId>{messageId}</messageId>
</sms:inboundSMSMessage>
```

5.6.3.2 Example 2: invalid messageId

(Informative)

5.6.3.2.1 Request

```
GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId} HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.6.3.2.2 Response

HTTP/1.1 400 Bad Request
 Content-Type: application/xml
 Content-Length: 12345
 Date: Thu, 04 Jun 2009 02:51:59 GMT

```
<?xml version="1.0" encoding="UTF-8"?>
<common:requestError xmlns:common="urn:oma:xml:rest:common:1">
  <link rel="InboundSMSMessage"
    href="http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}" />
  <serviceException>
    <messageId>SVC0002</messageId>
    <text>Invalid input value. The requested messageId %1 is not valid.</text>
    <variables>{messageId1}</variables>
  </serviceException>
</common:requestError>
```

5.6.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: GET, DELETE’ field in the response as per section 14.7 of [RFC 2616].

5.6.5 POST

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: GET, DELETE’ field in the response as per section 14.7 of [RFC 2616].

5.6.6 DELETE

Confirms message delivery and removes the message from the storage on the gateway.

5.6.6.1 Example

(Informative)

5.6.6.1.1 Request

```
DELETE .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId} HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.6.6.1.2 Response

HTTP/1.1 204 No content
 Date: Thu, 04 Jun 2009 02:51:59 GMT

5.7 Resource: Inbound SMS message subscriptions

The resource used is: <http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions>

This resource gives access to inbound subscriptions for a particular client.

5.7.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API clients want to use (e.g. 1 for version 1.x)

5.7.2 Response Codes

5.7.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.7.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.7.3 GET

This operation is used to read active subscriptions for the particular client.

5.7.3.1 Example

(Informative)

5.7.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.7.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:subscriptionList xmlns:sms="urn:oma:xml:rest:sms:1">
  <subscription>
    <callbackReference>
      <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
      <callbackData>12345</callbackData>
    </callbackReference>
    <destinationAddress>680180999</destinationAddress>
    <criteria>Urgent*</criteria>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId1}</resourceURL>
  </subscription>
</subscriptionList>
```

```

<callbackReference>
  <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
  <callbackData>54321</callbackData>
</callbackReference>
<destinationAddress>80999</destinationAddress>
<criteria>Urgent*</criteria>
<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}</resourceURL>
</subscription>
</sms:subscriptionList>

```

5.7.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET, POST' field in the response as per section 14.7 of [RFC 2616].

5.7.5 POST

This operation is used to create a new inbound message subscription for the particular client.

ParlayX SOAP equivalent is startSmsNotification.

5.7.5.1 Example 1: returning a representation of created resource (Informative)

5.7.5.1.1 Request

```

POST .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:subscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
    <callbackData>12345</callbackData>
  </callbackReference>
  <destinationAddress>+34680180999</destinationAddress>
  <criteria>Urgent*</criteria>
</sms:subscription>

```

5.7.5.1.2 Response

```

HTTP/1.1 201 Created
Content-Type: application/xml
Location: http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}
Content-Length: 254
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:subscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>

```

```

<notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
<callbackData>12345</callbackData>
</callbackReference>
<destinationAddress>+34680180999</destinationAddress>
<criteria>Urgent*</criteria>
<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId1}</resourceURL>
</sms:subscription>

```

5.7.5.2 Example 2: returning the location of created resource (Informative)

5.7.5.2.1 Request

```

POST .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:subscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
    <callbackData>12345</callbackData>
  </callbackReference>
  <destinationAddress>+34680180999</destinationAddress>
  <criteria>Urgent*</criteria>
</sms:subscription>

```

5.7.5.2.2 Response

```

HTTP/1.1 201 Created
Content-Type: application/xml
Location: http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId1}
Content-Length: 254
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<common:resourceReference xmlns:common="urn:oma:xml:rest:common:1">
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId1}</resourceURL>
</common:resourceReference>

```

5.7.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET, POST' field in the response as per section 14.7 of [RFC 2616].

5.8 Resource: Individual inbound SMS message subscription

The resource used is:

http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}

This resource controls individual subscription for inbound messages and gives access to individual subscription for a particular client.

5.8.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API client wants to use (e.g. 1 for version 1.x)
subscriptionId	identifier of the subscription

5.8.2 Response Codes

5.8.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.8.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4]

5.8.3 GET

This operation is used to read an individual subscription for the particular client.

5.8.3.1 Example

(Informative)

5.8.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.8.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: nnnn
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

```
<?xml version="1.0" encoding="UTF-8"?>
<sms:subscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
    <callbackData>12345</callbackData>
  </callbackReference>
  <destinationAddress>+34680180999</destinationAddress>
  <criteria>Urgent*</criteria>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscription/{subscriptionId}</resourceURL>
</sms:subscription>
```

5.8.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: GET, DELETE’ field in the response as per section 14.7 of [RFC 2616].

5.8.5 POST

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: GET, DELETE’ field in the response as per section 14.7 of [RFC 2616].

5.8.6 DELETE

This operation is used to delete a subscription for the particular client.

Note: ParlayX SOAP equivalent is stopSmsNotification.

5.8.6.1 Example

(Informative)

5.8.6.1.1 Request

```
DELETE .../{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.8.6.1.2 Response

```
HTTP/1.1 204 No content
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

5.9 Resource: Client notification about inbound SMS message

This resource is a client provided callback URL for notification about incoming messages. ParlayREST does not make any assumption about the structure of this URL.

5.9.1 Request URI variables

Client provided.

5.9.2 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.9.3 GET

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: .' field in the response as per section 14.7 of [RFC 2616].

5.9.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: POST' field in the response as per section 14.7 of [RFC 2616].

5.9.5 POST

This operation is used to notify client about message arrival.

Note: ParlayX SOAP equivalent is NotifySMSReception.

5.9.5.1 Example

(Informative)

5.9.5.1.1 Request

```
POST /notifications/DeliveryInfoNotification HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Content-Length: nnnn
Host: application.example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:inboundSMSMessageNotification xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackData>12345</callbackData>
  <inboundSMSMessage>
    <destinationAddress>MSISDN</destinationAddress>
    <senderAddress>sender name</senderAddress>
    <message>First simple message</message>
    <dateTime>2009-11-19T12:00:00</dateTime>
    <messageId>{messageId1}</messageId>
  </inboundSMSMessage>
</sms:inboundSMSMessageNotification>
```

5.9.5.1.2 Response

```
HTTP/1.1 204 No Content
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

5.9.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405

5.10 Resource: Outbound SMS message requests

The resource used is: <http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests>

This resource is used for sending outbound messages.

5.10.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API client wants to use (e.g. 1 for version 1.x)
senderAddress	identifies client application. Typically SMS SHORT CODE [REST_TS_Common]

5.10.2 Response Codes

5.10.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.10.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.10.3 GET

This operation is used to retrieve the list of "pending" outgoing requests.

5.10.3.1 Example

(Informative)

5.10.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.10.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:outboundSMSMessageRequestList xmlns:sms="urn:oma:xml:rest:sms:1">
  <outboundSMSMessageRequest>
    <address>tel:+1350000001</address>
    <senderAddress>tel:+1350000512</senderAddress>
    <outboundSMSTextMessage>
      <message>Let's have a REST.</message>
    </outboundSMSTextMessage>
    <clientCorrelator>67891</clientCorrelator>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}</resourceURL>
    <deliveryInfoList>
```

```

<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId1}/deliveryInfos
</resourceURL>
<deliveryInfo>
  <address>tel:+1350000001</address>
  <deliveryStatus>DeliveredToNetwork</deliveryStatus>
</deliveryInfo>
</deliveryInfoList>
</outboundSMSMessageRequest>
<outboundSMSMessageRequest>
  <address>tel:+1350000991</address>
  <address>tel:+1350000992</address>
  <senderAddress>tel:+1350000512</senderAddress>
  <outboundSMSTextMessage>
    <message>Let's have a REST.</message>
  </outboundSMSTextMessage>
  <clientCorrelator>67892</clientCorrelator>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId2}</resourceURL>
  <deliveryInfoList>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId2}/deliveryInfos
    </resourceURL>
    <deliveryInfo>
      <address>tel:+1350000991</address>
      <deliveryStatus>DeliveredToTerminal</deliveryStatus>
    </deliveryInfo>
    <deliveryInfo>
      <address>tel:+1350000992</address>
      <deliveryStatus>DeliveredToNetwork</deliveryStatus>
    </deliveryInfo>
  </deliveryInfoList>
</outboundSMSMessageRequest>

```

5.10.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET, POST' field in the response as per section 14.7 of [RFC 2616].

5.10.5 POST

This operation is used to create outgoing message request.

Note: ParlayX SOAP equivalent is SendSmsRequest.

5.10.5.1 Example 1: returning representation of created resource in response (Informative)

5.10.5.1.1 Request

```

POST .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:outboundSMSMessageRequest xmlns:sms="urn:oma:xml:rest:sms:1">

```

```

<address>tel:+1350000001</address>
<address>tel:+1350000999</address>
<senderAddress>tel:+1351111999</senderAddress>
<senderName>MyName</senderName>
<receiptRequest> <!-- this is optional -->
  <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
</receiptRequest>
<outboundSMSTextMessage>
  <message>Example Text Message </message>
</outboundSMSTextMessage>
<clientCorrelator>67893</clientCorrelator>
</sms:outboundSMSMessageRequest>

```

5.10.5.1.2 Response

```

HTTP/1.1 201 Created
Content-Type: application/xml
Location: http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

```

```

<?xml version="1.0" encoding="UTF-8"?>
<sms:outboundSMSMessageRequest xmlns:sms="urn:oma:xml:rest:sms:1">
  <address>tel:+1350000991</address>
  <address>tel:+1350000001</address>
  <address>tel:+1350000999</address>
  <senderAddress>tel:+1351111999</senderAddress>
  <senderName>MyName</senderName>
  <receiptRequest> <!-- this is optional -->
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
  </receiptRequest>
  <outboundSMSTextMessage>
    <message>Example Text Message </message>
  </outboundSMSTextMessage>
  <clientCorrelator>67893</clientCorrelator>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}</resourceURL>
  <deliveryInfoList>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}/deliveryInfos
    </resourceURL>
    <deliveryInfo>
      <address>tel:+1350000001</address>
      <deliveryStatus>MessageWaiting</deliveryStatus>
    </deliveryInfo>
    <deliveryInfo>
      <address>tel:+1350000999</address>
      <deliveryStatus>MessageWaiting</deliveryStatus>
    </deliveryInfo>
  </deliveryInfoList>
</sms:outboundSMSMessageRequest>

```

5.10.5.2 Example 2: returning location of created resource in response (Informative)

5.10.5.2.1 Request

```
POST .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:outboundSMSMessageRequest xmlns:sms="urn:oma:xml:rest:sms:1">
  <address>tel:+1350000001</address>
  <address>tel:+1350000999</address>
  <senderAddress>tel:+1351111999</senderAddress>
  <senderName>MyName</senderName>
  <receiptRequest> <!-- this is optional -->
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
  </receiptRequest>
  <outboundSMSTextMessage>
    <message>Example Text Message </message>
  </outboundSMSTextMessage>
  <clientCorrelator>67893</clientCorrelator>
</sms:outboundSMSMessageRequest>
```

5.10.5.2.2 Response

```
HTTP/1.1 201 Created
Content-Type: application/xml
Location: http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<common:resourceReference xmlns:common="urn:oma:xml:rest:common:1">
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}</resourceURL>
</common:resourceReference>
```

5.10.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: GET, POST’ field in the response as per section 14.7 of [RFC 2616].

5.11 Resource: Outbound SMS message request and delivery status

The resource used is: **http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}**

This resource is used to request an outbound SMS request including the message delivery status.

5.11.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API client wants to use (e.g. 1 for version 1.x)
senderAddress	identifies client application. Typically SMS SHORT CODE [REST_TS_Common]
requestId	outbound message request Id generated by server

5.11.2 Response Codes

5.11.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.11.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.11.3 GET

This operation is used to retrieve an outbound SMS request including the message delivery status.

5.11.3.1 Example

(Informative)

5.11.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId} HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.11.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:outboundSMSMessageRequest xmlns:sms="urn:oma:xml:rest:sms:1">
  <address>tel:+1350000001</address>
  <address>tel:+1350000999</address>
  <senderAddress>tel:+1351111999</senderAddress>
  <senderName>MyName</senderName>
  <!-- this is optional -->
  <receiptRequest>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
```

```

</receiptRequest>
<outboundSMSTextMessage>
  <message>"sent message"</message>
</outboundSMSTextMessage>
<clientCorrelator>67893</clientCorrelator>
<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}</resourceURL>
<deliveryInfoList>
  <!-- this is optional -->
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}/deliveryInfos
</resourceURL>
  <deliveryInfo>
    <address>tel:+1350000001</address>
    <deliveryStatus>MessageWaiting</deliveryStatus>
  </deliveryInfo>
  <deliveryInfo>
    <address>tel:+1350000999</address>
    <deliveryStatus>MessageWaiting</deliveryStatus>
  </deliveryInfo>
</deliveryInfoList>
</sms:outboundSMSMessageRequest>

```

5.11.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.11.5 POST

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.11.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.12 Resource: Outbound SMS message delivery status

The resource used is: <http://{serverRoot}/{apiVersion}/smsmessaging/outbound/requests/{requestId}/deliveryInfos>

This resource is used to request outbound message delivery status.

5.12.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example:

	http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API client wants to use (e.g. 1 for version 1.x)
requestId	outbound message request Id generated by server

5.12.2 Response Codes

5.12.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.12.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.12.3 GET

This operation is used to retrieve outgoing message delivery status.

Note: ParlayX SOAP equivalent is GetSmsDeliveryStatus.

5.12.3.1 Example

(Informative)

5.12.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/outbound/requests/{requestId}/deliveryInfos HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.12.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryInfoList xmlns:sms="urn:oma:xml:rest:sms:1">
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/requests/{requestId}/deliveryInfos</resourceURL>
  <deliveryInfo>
    <address>tel:+1350000001</address>
    <deliveryStatus>MessageWaiting</deliveryStatus>
  </deliveryInfo>
  <deliveryInfo>
    <address>tel:+1350000999</address>
    <deliveryStatus>MessageWaiting</deliveryStatus>
  </deliveryInfo>
</sms:deliveryInfoList>
```

5.12.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.12.5 POST

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.12.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET' field in the response as per section 14.7 of [RFC 2616].

5.13 Resource: Outbound SMS message delivery notification subscriptions

The resource used is:

http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions

This resource gives access to outbound SMS subscriptions for a particular client.

5.13.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API clients want to use (e.g. 1 for version 1.x)
senderAddress	identifies client application. Typically SMS SHORT CODE [REST_TS_Common]

5.13.2 Response Codes

5.13.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.13.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.13.3 GET

This operation is used to read all outbound SMS delivery notification subscriptions for the particular client.

Note: no equivalent ParlayX SOAP API.

5.13.3.1 Example

(Informative)

5.13.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.13.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryReceiptSubscriptionList xmlns:sms="urn:oma:xml:rest:sms:1">
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/</resourceURL>
  <deliveryReceiptSubscription>
    <callbackReference>
      <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
      <callbackData>12345</callbackData>
    </callbackReference>
    <filterCriteria>0102</filterCriteria>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}</resourceURL>
  </deliveryReceiptSubscription>
  <deliveryReceiptSubscription>
    <callbackReference>
      <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
      <callbackData>54321</callbackData>
    </callbackReference>
    <filterCriteria>0103</filterCriteria>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}</resourceURL>
  </deliveryReceiptSubscription>
</sms:deliveryReceiptSubscriptionList>
```

5.13.4 PUT

Method not supported by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET, POST' field in the response as per section 14.7 of [RFC 2616].

5.13.5 POST

This operation is used to create a new outbound SMS delivery notification subscription for the particular client.

ParlayX SOAP equivalent is StartDeliveryReceiptNotification.

5.13.5.1 Example

(Informative)

5.13.5.1.1 Request

```
POST .../{apiVersion}/smsmessaging/outbound/subscriptions HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryReceiptSubscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
    <callbackData>12345</callbackData>
  </callbackReference>
  <filterCriteria>0102</filterCriteria>
</sms:deliveryReceiptSubscription>
```

Note that this subscription does not use the clientCorrelator but provides callbackData.

5.13.5.1.2 Response

```
HTTP/1.1 201 Created
Content-Type: application/xml
Location:http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryReceiptSubscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL> http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
    <callbackData>12345</callbackData>
  </callbackReference>
  <filterCriteria>0102</filterCriteria>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}</resourceURL>
</sms:deliveryReceiptSubscription>
```

5.13.6 DELETE

Method not supported by the resource. The returned HTTP error status is 405. The server should also include the ‘Allow: GET, POST’ field in the response as per section 14.7 of [RFC 2616].

5.14 Resource: Individual outbound SMS message delivery notification subscription

The resource used is:

http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId}

This resource controls individual subscription for SMS delivery notification and gives access to individual subscription for a particular client.

5.14.1 Request URI variables

The following request URI variables are common for all HTTP commands:

Name	Description
serverRoot	server base url: hostname+port+base path. Example: http://example.com:80/ParlayREST
apiVersion	version of the ParlayREST API client wants to use (e.g. 1 for version 1.x)
senderAddress	identifies client application. Typically SMS SHORT CODE [REST_TS_Common]
subscriptionId	identifier of the subscription

5.14.2 HTTP Response Codes

5.14.2.1 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.14.2.2 Exception fault codes

For Policy Exception and Service Exception fault codes applicable to Short Messaging, see [3GPP 29.199-4].

5.14.3 GET

This operation is used to read an individual outbound SMS delivery notification subscription for the particular client.

Note: no equivalent ParlayX SOAP API.

5.14.3.1 Example

(Informative)

5.14.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/xml
Host: example.com:80
```

5.14.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryReceiptSubscription xmlns:sms="urn:oma:xml:rest:sms:1">
```

```

<callbackReference>
  <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
  <callbackData>12345</callbackData>
</callbackReference>
<filterCriteria>0102</filterCriteria>
<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}</resourceURL>
</sms:deliveryReceiptSubscription>

```

5.14.4 PUT

Method not supported by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET, DELETE' field in the response as per section 14.7 of [RFC 2616].

5.14.5 POST

Method not supported by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: GET, DELETE' field in the response as per section 14.7 of [RFC 2616].

5.14.6 DELETE

This operation is used to delete a subscription for the particular client.

Note: ParlayX SOAP equivalent is StopDeliveryReceiptNotification.

5.14.6.1 Example

(Informative)

5.14.6.1.1 Request

```

DELETE .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/xml
Host: example.com:80

```

5.14.6.1.2 Response

```

HTTP/1.1 204 No Content
Date: Thu, 04 Jun 2009 02:51:59 GMT

```

5.15 Resource: Client notification about outbound SMS message delivery status

This resource is a client provided callback URL for client notification about outbound message delivery status. ParlayREST does not make any assumption about the structure of this URL.

5.15.1 Request URI variables

Client provided.

5.15.2 HTTP Response Codes

For HTTP response codes, see [REST_TS_Common].

5.15.3 GET

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: POST' field in the response as per section 14.7 of [RFC 2616].

5.15.4 PUT

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: POST' field in the response as per section 14.7 of [RFC 2616].

5.15.5 POST

This operation is used to notify the client about message delivery status.

Note: ParlayX SOAP equivalent is NotifySMSDeliveryReceipt.

5.15.5.1 Example

(Informative)

5.15.5.1.1 Request

```
POST /notifications/DeliveryInfoNotification HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: application.example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryInfoNotification xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackData>12345</callbackData>
  <deliveryInfo>
    <address>tel:+1350000001</address>
    <deliveryStatus>DeliveredToNetwork</deliveryStatus>
  </deliveryInfo>
  <link rel="DeliveryReceiptSubscription"
    href="http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId}"/>
</sms:deliveryInfoNotification>
```

5.15.5.1.2 Response

```
HTTP/1.1 204 No Content
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

5.15.6 DELETE

Method not allowed by the resource. The returned HTTP error status is 405. The server should also include the 'Allow: POST' field in the response as per section 14.7 of [RFC 2616].

Appendix A. Change History (Informative)

A.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version –or- No previous version within OMA

A.2 Draft/Candidate Version 1.0 History

Document Identifier	Date	Sections	Description
Draft Version: OMA-TS-ParlayREST-ShortMessaging-V1_0	24 Jun 2009	All	Baseline uploaded as per agreed OMA-ARC-REST-2009-0008-INP_ParlayREST_SMS Editorial updates: versioning and history box fixed
	12 Nov 2009	4.1, 5	As agreed in CC 10 November 2009, Update from OMA-ARC-REST-2009-0041R02-CR_ParlayREST_SMS_API-edits.doc
	25 Nov 2009	all	Document clean-up
	1 Dec 2009	5.1	Added OMA-ARC-REST-2009-0075R01-CR_SMS_API_Optionality and OMA-ARC-REST-2009-0094R01-CR_Equivalent_PX_SOAP_to_SMS_TS and OMA-ARC-REST-2009-0090R01-CR_FlowDiagrams_to_SMS_TS
	1 Dec 2009	App. A	Added OMA-ARC-REST-2009-0069R02-CR_Vodafone_comments_on_SMS_API.doc
	2 Dec 2009	5+	Added OMA-ARC-REST-2009-0096-CR_Adding_Resources_to_SMS_TS
	2 Dec 2009	5+	Added OMA-ARC-REST-2009-0098R03-CR_Changes_to_SMS_API.doc and merged OMA-TS-ParlayREST_ShortMessaging-V1_0-20091112-D-changedbyCR0098R02.doc
	3 Dec 2009		Updated selfURL to resourceURL and added Link
	3 Dec 2009	4	Updated from OMA-ARC-REST-2009-0113-INP_SMS_Intro_section.
	3 Dec 2009	2	Updated from OMA-ARC-REST-2009-0114-INP_SMS_TS_Reference_Section
	3 Dec 2009	3	Updated from OMA-ARC-REST-2009-0115R01-INP_SMS_TS_Section_3.doc
	3 Dec 2009	5	Update from OMA-ARC-REST-2009-0127R01-CR_Fix_retrievalOrder,
	7 Dec 2009	4, App	Added OMA-ARC-REST-2009-0118R01-CR_Outline_for_request_response_examples.doc
	11 Dec 2009	all	Update after final CC, see OMA-ARC-REST-2009-0170-MINUTES_11Dec2009_CC for details
	15 Dec 2009	all	Last corrections added
	16 Dec 2009	All	Editorial fixes: styles as per template
	26 Jan 2010	All	CONRR editorial comments applied, G005, G007, G008, B002, B006, B042, B059, B060
	02 Feb 2010	All	Added OMA-ARC-REST-2010-0003R01 Added OMA-ARC-REST-2010-0006R02, closing B009, B010, B012 Added OMA-ARC-REST-2010-0007R03, closing B003, B013
	03 Feb 2010	All	Applied G001, G002, G004
	04 Feb 2010	All	Added OMA-ARC-REST-2009-177R01 Added OMA-ARC-REST-2010-0041 B017, B018, B019, B022, B023, B024, B025, B026, B027, B028 B029, B030, B031, B032, B033, B034, B035, B036, B037, B038, B039, B040, B041, B043, B044, B045, B047, B048 B049, B050, B051, B052, B053, B054, B055, B056, B057, B058 B061, B062, B063, B065, B066, B069, B071, B073, B074, B076, B077, B078
09 Feb 2010	Many	Fixed the implementation of G002 and B027 which were only partially implemented. Clericals	

Document Identifier	Date	Sections	Description
	22 Feb 2010	Many	<p>Editorial fixes</p> <ul style="list-style-type: none"> - case convention (MESSAGE ID → messageId) - alignments (messageRequestId, requestId → requestId) - fonts, typos <p>Inclusion of latest validated XML examples, closing B005, B017, B018</p> <p>Comments implemented: B004, B007, B014, B067, B068</p> <p>Comments implementation fixed and/or validated: G006, B070</p> <p>Structure of Examples sections aligned with TSs Payment and TerminalLocation (comment D018)</p> <p>History Box fixed</p>
	23 Feb 2010	Many	<p>CRs implemented</p> <ul style="list-style-type: none"> - OMA-ARC-REST-2010-0077 - OMA-ARC-REST-2010-0052R01 (closing B021) - OMA-ARC-REST-2010-0056 (closing B062) - OMA-ARC-REST-2010-0038R01 (closing B008)
	24 Feb 2010	Many	<p>Editorial: Fixed mistake in implementation of CR 38R01</p> <p>Editorial: Fixed references in SCR tables (changed from Appendix A to Appendix C)</p> <p>Removed some occurrences of “online” and “offline” that were overlooked when implementing B004</p> <p>Removed some occurrences of “Request” that remained after implementing D018</p> <p>Fixed some typos</p>
	07 Mar 2010	Many	<p>CRs implemented</p> <p>OMA-ARC-REST-2010-0111R01-INP_editorial_alignments</p> <p>OMA-ARC-REST-2010-0108-CR_SMS_TS_SCR_Corrections</p> <p>OMA-ARC-REST-2010-0100-CR_Inconsistent_retrieval_DeliveryStatus_for_SMS</p> <p>OMA-ARC-REST-2010-0089-CR_Closing_echoing_issue_examples_SMS</p> <p>OMA-ARC-REST-2010-0087R01-CR_SMS_OutboundSubscriptions_GET_missing</p> <p>OMA-ARC-REST-2010-0084-CR_Correlator_resolution_TS_SMS_updated_examples</p> <p>OMA-ARC-REST-2010-0080R01-CR_Correlator_resolution_TS_SMS</p> <p>Editorial:</p> <p>References alphabetized</p> <p>added abbreviations</p> <p>re-arranged section 5.2 such that first all types, then all enumerations are given</p> <p>removed entry “Tables” from TOC as there are no tables with captions</p> <p>Note: this revision contains changes that do require update of the XSDs.</p>
	10 Mar 2010	Many	<p>Implemented all CRs that were agreed in REST R&A on March 10</p> <p>OMA-ARC-REST-2010-0103R01-CR_More_SMS_inconsistency_fixes</p> <p>OMA-ARC-REST-2010-0101-CR_Document_74_followup_SMS</p> <p>Note: this revision contains changes that do require update of the XSDs.</p>
	11 Mar 2010	Many	<p>Editorial fixes to eradicate remains of “campaign”.</p> <p>Editorial fixes after a walk-through.</p> <p>Note that this revision contains no changes that require update of the XSDs.</p>
	12 Mar 2010	Many	<p>Further editorial fixes</p> <p>Note that this revision contains no changes that require update of the XSDs.</p>

Document Identifier	Date	Sections	Description
	23 Mar 2010	Many	<p>Action resolved: AI REST-2010-A014: to REST all TS Editors: Remove the dot at the end of the resources throughout the documents.</p> <p>CRs implemented: OMA-ARC-REST-2010-0124-CR_TS_SMS_with_JSON_Examples OMA-ARC-REST-2010-0122-CR_Charging_Appendix_C1_SMS OMA-ARC-REST-2010-0121-CR_Fixing_wrong_example_appendix_C3_SMS</p> <p>Some editorial fixes. Note that this revision contains no changes that require update of the XSDs.</p>
	28 Mar 2010	Many	<p>CRs implemented: OMA-ARC-REST-2010-0126R01-CR_Incorrect_URL_for_client_resources_SMS OMA-ARC-REST-2010-0155-CR_Resource_restructuring_SMS OMA-ARC-REST-2010-0135R01-CR_Correction_of_section_5.3_in_SMS_TS OMA-ARC-REST-2010-0140R01-CR_Small_corrections_and_editorial_changes_SMS Download OMA-ARC-REST-2010-0142-CR_Common_prefix_SMS OMA-ARC-REST-2010-0142-CR_Common_prefix_SMS OMA-ARC-REST-2010-0146R01-CR_PX_GetSmsDeliveryStatus_SMS OMA-ARC-REST-2010-0149-CR_Message_id_optional_TS_SMS OMA-ARC-REST-2010-0152-CR_Improvements_of_section_5.3_in_SMS_TS</p> <p>Some editorial fixes: Table width alignment. Fixed HTTP header in C.4.1.2 (aligned them with the XML pendant in 5.13.5.1.2) removed remaining client-related placeholders in HTTP headers for notifications {client host} etc, and ensured client host is in the notification examples always addressed as application.example.com:80 rather than example.com:80 which is the server. This is consistent with the notifyURL (http://application.example.com/notifications/DeliveryInfoNotification) we use in the examples. See alsoe item 5 in INP OMA-ARC-REST-2010-0111R01.</p> <p>Other: Implemented outcome of action REST-2010-A010 as communicated in eMail from Michael Brenner to ARC exploder, 29th Mar 2010, 09:52 GMT Note: this revision contains changes that do require update of the XSD.</p>
	29 Mar 2010	Many	<p>Editorial: .../notifications → /notifications Note that this revision contains no changes that require update of the XSDs.</p>
Candidate Version: OMA-TS-ParlayREST_ShortMessaging-V1_0	27 Apr 2010	All	<p>Status changed to Candidate by TP: OMA-TP-2010-0186- INP_ParlayREST_V1_0_ERP_for_Candidate_Approval</p>

Appendix B. Static Conformance Requirements (Normative)

The notation used in this appendix is specified in [SCRRULES].

B.1 SCR for ParlayREST.SMS Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-SUPPORT-S-001-M	Support for the SMS REST Enabler	5	
PARLAYREST-SMS-SUPPORT-S-002-M	Support for the XML request & response format	5	
PARLAYREST-SMS-SUPPORT-S-003-M	Support for the JSON request & response format	5	
PARLAYREST-SMS-SUPPORT-S-004-O	Support for the application/form-urlencoded format	Appendix C	

B.1.1 SCR for ParlayREST.SMS.Inbound.Registration Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-INB-OFF-S-001-M	Support for reliable inbound message delivery	5.4	
PARLAYREST-SMS-INB-OFF-S-002-M	Retrieve messages from server - GET	5.4.3	

B.1.2 SCR for ParlayREST.SMS.Inbound.Registration.RetrieveDelete Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-INB-OFF-RETDEL-S-001-O	Support for inbound message delivery	5.5	PARLAYREST-SMS-INB-OFF-RETDEL-S-002-O
PARLAYREST-SMS-INB-OFF-RETDEL-S-002-O	Retrieve messages from server - POST	5.5.5 C.3	

B.1.3 SCR for ParlayREST.SMS.Individual.Inbound Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-IND-INB-S-001-M	Support for inbound individual message delivery	5.6	
PARLAYREST-SMS-IND-INB-S-002-O	Retrieve one message from server - GET	5.6.3	
PARLAYREST-SMS-IND-INB-S-003-M	Confirm and delete retrieved message from server - DELETE	5.6.6	

B.1.4 SCR for ParlayREST.SMS.Inbound.Subscr Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-INB-ONL-SUBSCR-S-001-M	Support inbound subscriptions	5.7	
PARLAYREST-SMS-INB-ONL-SUBSCR-S-002-O	Read active subscriptions - GET	5.7.3	
PARLAYREST-SMS-INB-ONL-SUBSCR-S-003-M	Create inbound message subscription - POST	5.7.5 C.5.1	

B.1.5 SCR for ParlayREST.SMS.Inbound.Individual.Subscr Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-INB-INDON-SUBSCR-S-001-M	Support for control and read access to individual inbound subscription	5.8	
PARLAYREST-SMS-INB-INDON-S-002-O	Read individual inbound subscription - GET	5.8.3	
PARLAYREST-SMS-INB-INDON-S-003-M	Update individual inbound subscriptions - DELETE	5.8.6 C.5.3	

B.1.6 SCR for ParlayREST.SMS.Inbound.Notifications Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-INB-NOTIF-S-001-M	Support for notifying application about inbound messages	5.9	
PARLAYREST-SMS-INB-NOTIF-S-002-M	Notify application about inbound message arrival - POST	5.9.5 C.5.2	

B.1.7 SCR for ParlayREST.SMS.Outbound Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-OUTB-S-001-M	Support for outbound SMS messages	5.10	
PARLAYREST-SMS-OUTB-S-002-O	Retrieve list of pending outgoing message requests - GET	5.10.3	
PARLAYREST-SMS-OUTB-S-003-M	Create outgoing message request - POST	5.10.5 C.1	

B.1.8 SCR for ParlayREST.SMS.Outbound.MsgAndDeliveryStatus Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-OUTB-MSGDELSTAT-S-001-O	Support for requesting an outbound SMS message and its delivery status	5.11	PARLAYREST-SMS-OUTB-MSGDELSTAT-S-002-O
PARLAYREST-SMS-OUTB-MSGDELSTAT-S-002-O	Retrieve Outgoing Message Delivery Status - GET	5.11.3	

B.1.9 SCR for ParlayREST.SMS.Outbound.DeliveryStatus Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-OUTB-DELSTAT-S-001-M	Support for requesting delivery status of outbound SMS messages	5.12	
PARLAYREST-SMS-OUTB-DELSTAT-S-002-M	Retrieve Outgoing Message Delivery Status - GET	5.12.3 C.2	

B.1.10 SCR for ParlayREST.SMS.Outbound.Subscriptions Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-OUTB-SUBSCR-S-001-M	Support for outbound subscriptions for a particular client	5.13	
PARLAYREST-SMS-OUTB-SUBSCR-S-002-O	Read all outbound SMS delivery notification subscriptions - GET	5.13.3	
PARLAYREST-SMS-OUTB-SUBSCR-S-003-M	Create new outbound message subscription - POST	5.13.5 C.4.1	

B.1.11 SCR for ParlayREST.SMS.Individual.Outbound.Subscr Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-IND-OUTB-IND-SUBSCR-S-001-M	Support for outbound subscriptions for a particular client	5.14	
PARLAYREST-SMS-IND-OUTB-IND-SUBSCR-S-002-O	Read individual SMS delivery notification subscription - GET	5.14.3 C.4.3	
PARLAYREST-SMS-IND-OUTB-IND-	Delete subscription for the client - DELETE	5.14.6 C.4.3	

Item	Function	Reference	Requirement
SUBSCR-S-003-M			

B.1.12 SCR for ParlayREST.SMS.Outbound.DeliveryStatus.Notifications Server

Item	Function	Reference	Requirement
PARLAYREST-SMS-OUTB-DELSTAT-NOTIF-S-001-M	Support for notifying application about delivery status of outbound messages	5.15	
PARLAYREST-SMS-OUTB-DELSTAT-NOTIF-S-002-M	Notify application about delivery status of outbound message - POST	5.15.5 C.4.2	

Appendix C. Application/x-www-form-urlencoded Request Format for Selected REST Operations

This section defines a format for SMS REST API requests where the body of the request is encoded using the application/x-www-form-urlencoded MIME type.

Note: only the request body is encoded as application/x-www-form-urlencoded, the response is still encoded as XML or JSON depending on the preference of the client and the capabilities of the server.

The following SMS REST operations are defined in this section:

- Sending a SMS to a terminal
- A polling mechanism for monitoring the delivery status of a sent SMS
- An asynchronous notification mechanism for delivery status, plus a mechanism to start and stop the notification of delivery receipts
- A polling mechanism to receive SMS
- An asynchronous notification mechanism for SMS reception, plus a mechanism to start and stop the notification of received SMS

C.1 Send a SMS to a terminal

This operation is used to create an outgoing message request.

Note: ParlayX SOAP equivalent is SendSms.

The request parameters are as follows:

Name	Type/Values	Optional	Description
address	xsd:anyURI	No	One or more addresses to which the SMS will be sent. If the address is in the form of an MSISDN, include the protocol prefix 'tel:' and '%2B' followed by the country code before the subscriber number; e.g. tel:%2B447990123456.
senderAddress	xsd:anyURI	No	The address of the sender to whom a responding SMS may be sent. If the address is in the form of an MSISDN, include the protocol prefix 'tel:' and '%2B' followed by the country code before the subscriber number; e.g. tel:%2B447990123456.
message	xsd:string	No	The message to be sent
notifyURL	xsd:anyURI	Yes	URL to notify the application for delivery receipts
callbackData	xsd:string	Yes	Data the application can register with the server when subscribing to notifications, and that are passed back unchanged in each of the related notifications.
notificationFormat	common:NotificationFormat	Yes	Default: XML Application can specify format of the resource representation in notifications that are related to this subscription. The choice is between {XML, JSON}

clientCorrelator	xsd:string	Yes	A correlator that the client SHOULD use to tag this particular resource representation during a request to create a resource on the server. In case the field is present, the server SHALL not alter its value, and SHALL provide it as part of the representation of this resource. In case the field is not present, the server SHALL NOT generate it.
senderName	xsd:string	Yes	Name of the sender to appear on the terminal
chargingDescription	xsd:string [0..unbounded]	Yes	Description of charge to apply to this message. In case charging is required, this parameter MUST be present.
chargingCurrency	xsd:string	Yes	Currency of charge to apply to this message. In case chargingDescription is not present, this parameter MUST NOT be present.
chargingAmount	xsd:decimal	Yes	Charging amount to apply to this message. In case chargingDescription is not present, this parameter MUST NOT be present.
chargingCode	xsd:string	Yes	Charging code to apply to this message. In case chargingDescription is not present, this parameter MUST NOT be present.

C.1.1 Example

(Informative)

C.1.1.1 Request

```
POST .../{apiVersion}/smsmessaging/outbound/requests HTTP/1.1
Host: example.com:80
Content-Type: application/x-www-form-urlencoded
Accept: application/xml

address=tel:%2B13500000991&
address=tel:%2B13500000991&
senderAddress=tel:%2B12345678&
message=Hello%20World&
clientCorrelator=123456&
notifyURL=http://application.example.com/notifications/DeliveryInfoNotification&
notificationFormat=XML&
senderName=Bob
```

C.1.1.2 Response

```
HTTP/1.1 201 Created
Content-Type: application/xml
Location: http://{serverRoot}/{apiVersion}/smsmessaging/outbound/requests

<?xml version="1.0" encoding="UTF-8"?>
<sms:outboundSMSMessageRequest xmlns:sms="urn:oma:xml:rest:sms:1">
  <address>tel:+13500000991</address>
  <address>tel:+13500000992</address>
  <senderAddress>tel:+13500000993</senderAddress>
```

```

<receiptRequest>
  <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
  <notificationFormat>XML</notificationFormat>
</receiptRequest>
<outboundSMSTextMessage>
  <message>Hello world!</message>
</outboundSMSTextMessage>
<clientCorrelator>123456</clientCorrelator>
<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/requests/{requestId}</resourceURL>
</sms:outboundSMSMessageRequest>

```

C.2 Request the delivery status of a SMS

This operation is used to retrieve outgoing message delivery status.

Note: ParlayX SOAP equivalent is GetSmsDeliveryStatus.

If the operation was successful, it returns an HTTP Status of “200 OK” and the delivery status of each recipient.

C.2.1 Example

(Informative)

C.2.1.1 Request

```

GET .../{apiVersion}/smsmessaging/outbound/requests/{requestId}/deliveryInfos HTTP/1.1
Accept: application/xml
Host: example.com:80

```

C.2.1.2 Response

```

HTTP/1.1 200 OK
Content-Type: application/xml
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryInfoList xmlns:sms="urn:oma:xml:rest:sms:1">
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/requests/{requestId}/deliveryInfos</resourceURL>
  <deliveryInfo>
    <address>tel:+1350000001</address>
    <deliveryStatus>MessageWaiting</deliveryStatus>
  </deliveryInfo>
  <deliveryInfo>
    <address>tel:+1350000999</address>
    <deliveryStatus>MessageWaiting</deliveryStatus>
  </deliveryInfo>
</sms:deliveryInfoList>

```

C.3 Reliable retrieval of received SMS messages

This operation is used for reliable inbound message delivery for the particular client.

Note: ParlayX SOAP equivalent is GetReceivedSms, but with the difference that separate deletion of individual messages is required, by invoking the HTTP DELETE method on the resourceURL of every individual message..

Request parameters are:

Name	Type/Values	Optional	Description
maxBatchSize	xsd:unsignedInt	Yes	Specifies maximum number of messages to be returned in the response
retrievalOrder	RetrievalOrder	Yes	Specifies order in which messages should be retrieved is there are more then one pending

If the operation was successful, it returns an HTTP Status of “200 OK” and a list of the received SMS messages.

C.3.1 Example

(Informative)

C.3.1.1 Request

```
GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=2 HTTP/1.1
Host: example.com:80
Accept: application/xml
```

C.3.1.2 Response

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:inboundSMSMessageList xmlns:sms="urn:oma:xml:rest:sms:1">
  <inboundSMSMessage>
    <destinationAddress>MSISDN1</destinationAddress>
    <senderAddress>MSISDN2</senderAddress>
    <message>First simple message</message>
    <dateTime>2009-11-19T12:00:00</dateTime>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageld1}</resourceURL>
    <messageld>{messageld1}</messageld>
  </inboundSMSMessage>
  <inboundSMSMessage>
    <destinationAddress>MSISDN1</destinationAddress>
    <senderAddress>MSISDN3</senderAddress>
    <message>Second simple message</message>
    <dateTime>2009-11-19T12:00:00</dateTime>
    <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageld2}</resourceURL>
```

```

<messageId>{messageId2}</messageId>
</inboundSMSMessage>
<!-- further instances of InboundSMSMessage if needed -->
<totalNumberOfPendingMessages>20</totalNumberOfPendingMessages>
<numberOfMessagesInThisBatch>2</numberOfMessagesInThisBatch>
<resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages</resourceURL>
</sms:inboundSMSMessageList>

```

C.4 Start delivery receipt notification

This REST operation is based on the Parlay X startDeliveryReceiptNotification, notifySmsDeliveryReceipt and stopDeliveryReceiptNotification SOAP methods to enable the application to start a notification session, listen for notifications of SMS delivery status and then stop the session.

This REST method is used by the application to start the delivery receipt notifications. It MUST use the HTTP POST method.

The following parameters are defined:

Name	Type/Values	Optional	Description
filterCriteria	xsd:string	No	Provides flexibility for the application to filter on, for example, the first 4 digits of MSISDN)
notifyURL	xsd:anyURI	No	Notification endpoint definition
callbackData	xsd:string	Yes	Data the application can register with the server when subscribing to notifications, and that are passed back unchanged in each of the related notifications.
notificationFormat	common:NotificationFormat	Yes	Default: XML Application can specify format of the resource representation in notifications that are related to this subscription. The choice is between {XML, JSON}
clientCorrelator	xsd:string	Yes	A correlator that the client MAY use to tag this particular resource representation during a request to create a resource on the server. In case the field is present, the server SHALL not alter its value, and SHALL provide it as part of the representation of this resource. In case the field is not present, the server SHALL NOT generate it.

If the operation was successful, it returns an HTTP Status of “201 Created”.

C.4.1 Example

(Informative)

C.4.1.1 Request

```

POST .../{apiVersion}/smsmessaging/outbound/subscriptions HTTP/1.1
Host: example.com:80
Content-Type: application/x-www-form-urlencoded

```

Accept: application/xml

filterCriteria=0102&
 notifyURL=http://application.example.com/notifications/DeliveryInfoNotification

C.4.1.2 Response

HTTP/1.1 201 Created
 Content-Type: application/xml
 Location: http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}
 Date: Thu, 04 Jun 2009 02:51:59 GMT

```
<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryReceiptSubscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
  </callbackReference>
  <filterCriteria>0102</filterCriteria>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}</resourceURL>
</sms:deliveryReceiptSubscription>
```

C.5 Notify SMS delivery receipt

This REST method notifies the application when an SMS is delivered to a terminal or if delivery was impossible. It MUST use the HTTP POST method.

The application is expected to return a result indication. If the operation has been successful, there is no content.

C.5.1 Example

(Informative)

C.5.1.1 Request

POST /notifications/DeliveryInfoNotification HTTP/1.1
 Accept: application/xml
 Content-Type: application/xml; charset=UTF-8
 Host: application.example.com:80

```
<?xml version="1.0" encoding="UTF-8"?>
<sms:deliveryInfoNotification xmlns:sms="urn:oma:xml:rest:sms:1">
  <deliveryInfo>
    <address>tel:+1350000001</address>
    <deliveryStatus>DeliveredToNetwork</deliveryStatus>
  </deliveryInfo>
  <link rel="DeliveryReceiptSubscription"
    href="http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId}"/>
</sms:deliveryInfoNotification>
```

C.5.1.2 Response

HTTP/1.1 204 No Content

C.6 Stop delivery receipt notification

This REST method is used by the application to stop the delivery receipt notifications. It MUST use the HTTP DELETE method. This operation returns a result indicating whether the operation has been successful; there is no content.

C.6.1 Example

(Informative)

C.6.1.1 Request

DELETE .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId} HTTP/1.1
Host: example.com:80

C.6.1.2 Response

HTTP/1.1 204 No Content

C.7 Start SMS notification

These REST methods are based on the Parlay X StartSmsNotification, NotifySmsReception and StopSmsNotification SOAP methods to enable the application to start a notification session, listen for notifications of received SMS and then stop the session.

This REST method is used by the application to start the notification of received SMS. It MUST use the HTTP POST method.

The following parameters are defined:

Name	Type/Values	Optional	Description
destinationAddress	xsd:anyURI [1..unbounded]	No	Destination address of SMS
criteria	xsd:string	Yes	The text to match against to determine the application to receive the notification
notifyURL	xsd:anyURI	No	Notification endpoint definition
callbackData	xsd:string	Yes	Data the application can register with the server when subscribing to notifications, and that are passed back unchanged in each of the related notifications.
notificationFormat	common:NotificationFormat	Yes	Default: XML Application can specify format of the resource

			representation in notifications that are related to this subscription. The choice is between {XML, JSON}
clientCorrelator	xsd:string	Yes	A correlator that the client MAY use to tag this particular resource representation during a request to create a resource on the server. In case the field is present, the server SHALL not alter its value, and SHALL provide it as part of the representation of this resource. In case the field is not present, the server SHALL NOT generate it.

This operation returns a result indicating whether the operation has been successful.

C.7.1 Example

(Informative)

C.7.1.1 Request

Note that this example also illustrates the use of “callbackData”.

```
POST .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Host: example.com:80
Content-Type: application/x-www-form-urlencoded
Accept: application/xml

destinationAddress=81771
criteria=Vote&
notifyURL=http://application.example.com/notifications/DeliveryInfoNotification&
callbackData=12345
```

C.7.1.2 Response

```
HTTP/1.1 201 Created
Content-Type: application/xml
Location: http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}
Content-Length: 254
Date: Thu, 04 Jun 2009 02:51:59 GMT

<?xml version="1.0" encoding="UTF-8"?>
<sms:subscription xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackReference>
    <notifyURL>http://application.example.com/notifications/DeliveryInfoNotification</notifyURL>
    <callbackData>12345</callbackData>
  </callbackReference>
  <destinationAddress>+34680180999</destinationAddress>
  <criteria>Urgent*</criteria>
  <resourceURL>http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}</resourceURL>
</sms:subscription>
```

C.8 Notify SMS reception

This REST method notifies the application when a SMS is received. It MUST use the HTTP POST method.

The application is expected to return a result indication. If the operation has been successful, there is no content.

C.8.1 Example

(Informative)

C.8.1.1 Request

```
POST /notifications/DeliveryInfoNotification HTTP/1.1
Accept: application/xml
Content-Type: application/xml; charset=UTF-8
Host: application.example.com:80

<?xml version="1.0" encoding="UTF-8"?>
<sms:inboundSMSMessageNotification xmlns:sms="urn:oma:xml:rest:sms:1">
  <callbackData>12345</callbackData>
  <inboundSMSMessage>
    <destinationAddress>MSISDN</destinationAddress>
    <senderAddress>sender name</senderAddress>
    <message>First simple message</message>
    <dateTime>2009-11-19T12:00:00</dateTime>
    <messageId>messageId1</messageId>
  </inboundSMSMessage>
</sms:inboundSMSMessageNotification>
```

C.8.1.2 Response

```
HTTP/1.1 204 No Content
```

C.9 Stop SMS notification

This REST method is used by the application to stop the delivery receipt notifications. It MUST use the HTTP DELETE method.

Note: ParlayX SOAP equivalent is StopSmsNotification.

This operation returns a result indicating whether the operation has been successful; there is no content.

C.9.1 Example

(Informative)

C.9.1.1 Request

```
DELETE .../{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId} HTTP/1.1
Host: example.com:80
```

C.9.1.2 Response

HTTP/1.1 204 No Content

Appendix D. JSON examples (Informative)

JSON (JavaScript Object Notation) is a lightweight, text-based, language-independent data interchange format. It provides a simple means to represent basic name-value pairs, arrays and objects. JSON is relatively trivial to parse and evaluate using standard JavaScript libraries, and hence is suited for Parlay REST invocations from browsers or other processors with JavaScript engines. Further information on JSON can be found at [RFC 4627].

The following examples show the request or response for various operations using a JSON binding. The examples follow the XML to JSON serialization guidelines in [REST_WP]. A JSON response may be obtained by following the content negotiation guidelines section of [REST_WP].

For full details on the operations themselves please refer to the section number indicated.

D.1 Inbound message delivery (section 5.4.3)

Request:

```
GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=2 HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"inboundSMSMessageList": {
  "inboundSMSMessage": [
    {
      "dateTime": "2009-11-19T12:00:00",
      "destinationAddress": "MSISDN1",
      "messageId": "{messageId1}",
      "message": "First simple message",
      "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId1}",
      "senderAddress": "MSISDN2"
    },
    {
      "dateTime": "2009-11-19T12:00:00",
      "destinationAddress": "MSISDN1",
      "messageId": "{messageId2}",
      "message": "Second simple message",
      "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId2}",
      "senderAddress": "MSISDN3"
    }
  ],
  "numberOfMessagesInThisBatch": "2",
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages",
  "totalNumberOfPendingMessages": "20"
}}
```

D.2 maxBatchSize exceeding the allowed size (section 5.4.3.2)

Request:

```
GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=5000 HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 400 Bad Request
Content-Type: application/json
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"requestError": {
  "link": {
    "href": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages?maxBatchSize=5000",
    "rel": "InboundSMSMessageList"
  },
  "policyException": {
    "messageId": "POL0001",
    "text": "A policy error occurred. Error code is maxBatchSize exceeded. The maximum allowed maxBatchSize is %1.",
    "variables": "20"
  }
}}
```

D.3 Retrieve and delete using registration (section 5.5.5)

Request:

```
POST .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/retrieveAndDeleteMessages HTTP/1.1
Accept: application/json
Content-Length: nnn
Content-Type: application/json; charset=UTF-8
Host: example.com:80
```

```
{"inboundSMSRetrieveAndDeleteMessageRequest": {
  "maxBatchSize": "3",
  "retrievalOrder": "OldestFirst"
}}
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: nnnn
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"inboundSMSMessageList": {
  "inboundSMSMessage": [
    {
      "destinationAddress": "{shortCode1}",
```

```

    "messageId": "{messageId1}",
    "message": "First simple message",
    "senderAddress": "{MSISDN1}"
  },
  {
    "destinationAddress": "{shortCode2}",
    "messageId": "{messageId2}",
    "message": "Second simple message",
    "senderAddress": "{MSISDN2}"
  }
],
"numberOfMessagesInThisBatch": "2",
"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}",
"totalNumberOfPendingMessages": "200"
}}

```

D.4 Inbound messages for a given registration (section 5.6.3.1)

Request:

```

GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}?resFormat=JSON HTTP/1.1
Host: example.com:80

```

Response:

```

HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"inboundSMSMessage": {
  "dateTime": "2009-11-19T12:00:00",
  "destinationAddress": "MSISDN1",
  "messageId": "{messageId1}",
  "message": "First simple message",
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId1}",
  "senderAddress": "MSISDN2"
}}

```

D.5 Invalid messageId (section 5.6.3.2.1)

Request:

```

GET .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId} HTTP/1.1
Accept: application/json
Host: example.com:80

```

Response:

```

HTTP/1.1 400 Bad Request

```

```
Content-Type: application/json
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"requestError": {
  "link": {
    "href": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId}",
    "rel": "InboundSMSMessage"
  },
  "serviceException": {
    "messageId": "SVC0002",
    "text": "Invalid input value. The requested messageId %1 is not valid.",
    "variables": "{messageId1}"
  }
}}
```

D.6 Remove message from gateway storage (section 5.6.6)

Request:

```
DELETE .../{apiVersion}/smsmessaging/inbound/registrations/{registrationId}/messages/{messageId} HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 204 No content
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

D.7 Read active subscriptions (section 5.7.3)

Request:

```
GET .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"subscriptionList": {"subscription": [
  {
    "callbackReference": {
      "callbackData": "12345",
      "notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
    },
    "criteria": "Urgent**",
```

```

"destinationAddress": "680180999",
"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId1}"
},
{
"callbackReference": {
"callbackData": "54321",
"notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
},
"criteria": "Urgent*",
"destinationAddress": "80999",
"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId2}"
}
}}

```

D.8 Create new message subscription (section 5.7.5)

Request:

```

POST .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Host: example.com:80

{"subscription": {
"callbackReference": {
"callbackData": "12345",
"notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
},
"criteria": "Urgent*",
"destinationAddress": "+34680180999"
}}

```

Response:

```

HTTP/1.1 201 Created
Content-Type: application/json
Location: http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId1}
Content-Length: 254
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"subscription": {
"callbackReference": {
"callbackData": "12345",
"notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
},
"criteria": "Urgent*",
"destinationAddress": "+34680180999",
"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions{subscriptionId1}"
}}

```

D.9 Returning the location of created resource (section 5.7.5.2)

Request:

```
POST .../{apiVersion}/smsmessaging/inbound/subscriptions HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Host: example.com:80

{"subscription": {
  "callbackReference": {
    "callbackData": "12345",
    "notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
  },
  "criteria": "Urgent*",
  "destinationAddress": "+34680180999"
}}
```

Response:

```
HTTP/1.1 201 Created
Content-Type: application/json
Location: http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}
Content-Length: 254
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"resourceReference": {"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId}"}}
```

D.10 Read individual subscription (section 5.8.3)

Request:

```
GET .../{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: nnnn
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"subscription": {
  "callbackReference": {
    "callbackData": "12345",
    "notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
  },
  "criteria": "Urgent*",
  "destinationAddress": "+34680180999",
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/inbound/subscription/{subscriptionId}"
}}
```

D.11 Delete a subscription (section 5.8.6.1.1)

Request:

```
DELETE .../{apiVersion}/smsmessaging/inbound/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 204 No content
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

D.12 Notify client about message arrival (section 5.9.5)

Request:

```
POST /notifications/DeliveryInfoNotification HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Content-Length: nnnn
Host: application.example.com:80
```

```
{"inboundSMSMessageNotification": {
  "callbackData": "12345",
  "inboundSMSMessage": {
    "dateTime": "2009-11-19T12:00:00",
    "destinationAddress": "MSISDN",
    "messageId": "{messageId1}",
    "message": "First simple message",
    "senderAddress": "sender name"
  }
}}
```

Response:

```
HTTP/1.1 204 No Content
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

D.13 Retrieve list of pending outbound messages (section 5.10.3.1)

Request:

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```

HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"outboundSMSMessageRequestList": {"outboundSMSMessageRequest": [
  {
    "address": "tel:+1350000001",
    "clientCorrelator": "67891",
    "deliveryInfoList": {
      "deliveryInfo": {
        "address": "tel:+1350000001",
        "deliveryStatus": "DeliveredToNetwork"
      }
    },
    "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId1}/deliveryInfos",
    "outboundSMSTextMessage": {"message": "Let's have a REST."},
    "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId1}",
    "senderAddress": "tel:+1350000512"
  },
  {
    "address": [
      "tel:+1350000991",
      "tel:+1350000992"
    ],
    "clientCorrelator": "67892",
    "deliveryInfoList": {
      "deliveryInfo": [
        {
          "address": "tel:+1350000991",
          "deliveryStatus": "DeliveredToTerminal"
        },
        {
          "address": "tel:+1350000992",
          "deliveryStatus": "DeliveredToNetwork"
        }
      ]
    },
    "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId2}/deliveryInfos",
    "outboundSMSTextMessage": {"message": "Let's have a REST."},
    "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId2}",
    "senderAddress": "tel:+1350000512"
  }
]}

```

D.14 Create outbound message, returning a representation of created resource (section 5.10.5.1)

Request:

```

POST .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Host: example.com:80

```

```
{
  "outboundSMSMessageRequestList": {
    "outboundSMSMessageRequest": [
      {
        "address": "tel:+1350000001",
        "clientCorrelator": "67891",
        "deliveryInfoList": {
          "deliveryInfo": {
            "address": "tel:+1350000001",
            "deliveryStatus": "DeliveredToNetwork"
          }
        },
        "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId1}/deliveryInfos"
      },
      {
        "outboundSMSTextMessage": {
          "message": "Let's have a REST."
        },
        "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId1}",
        "senderAddress": "tel:+1350000512"
      }
    ]
  },
  {
    "address": [
      "tel:+1350000991",
      "tel:+1350000992"
    ],
    "clientCorrelator": "67892",
    "deliveryInfoList": {
      "deliveryInfo": [
        {
          "address": "tel:+1350000991",
          "deliveryStatus": "DeliveredToTerminal"
        },
        {
          "address": "tel:+1350000992",
          "deliveryStatus": "DeliveredToNetwork"
        }
      ]
    },
    "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId2}/deliveryInfos"
  },
  {
    "outboundSMSTextMessage": {
      "message": "Let's have a REST."
    },
    "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId2}",
    "senderAddress": "tel:+1350000512"
  }
}
]]}
```

Response:

```
HTTP/1.1 201 Created
Content-Type: application/json
Location: http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

```
{
  "outboundSMSMessageRequest": {
    "address": [
      "tel:+1350000991",
      "tel:+1350000001",
      "tel:+1350000999"
    ],
    "clientCorrelator": "67893",
```

```

"deliveryInfoList": {
  "deliveryInfo": [
    {
      "address": "tel:+1350000001",
      "deliveryStatus": "MessageWaiting"
    },
    {
      "address": "tel:+1350000999",
      "deliveryStatus": "MessageWaiting"
    }
  ],
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}/deliveryInfos"
},
"outboundSMSTextMessage": {"message": "Example Text Message "},
"receiptRequest": {"notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"},
"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}",
"senderAddress": "tel:+1351111999",
"senderName": "MyName"
}}

```

D.15 Create outbound message, returning the location of created resource (section 5.10.5.2)

Request:

```

POST .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Host: example.com:80

{"outboundSMSMessageRequest": {
  "address": [
    "tel:+1350000001",
    "tel:+1350000999"
  ],
  "clientCorrelator": "67893",
  "outboundSMSTextMessage": {"message": "Example Text Message "},
  "receiptRequest": {"notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"},
  "senderAddress": "tel:+1351111999",
  "senderName": "MyName"
}}

```

Response:

```

HTTP/1.1 201 Created
Content-Type: application/json
Location: http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"resourceReference": {"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}"}}

```

D.16 Get message delivery status (section 5.11.3)

Request:

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId} HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 12345
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"outboundSMSMessageRequest": {
  "address": [
    "tel:+1350000001",
    "tel:+1350000999"
  ],
  "clientCorrelator": "67893",
  "deliveryInfoList": {
    "deliveryInfo": [
      {
        "address": "tel:+1350000001",
        "deliveryStatus": "MessageWaiting"
      },
      {
        "address": "tel:+1350000999",
        "deliveryStatus": "MessageWaiting"
      }
    ]
  },
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}/deliveryInfos"
},
"outboundSMSTextMessage": {"message": "\"sent message\""},
"receiptRequest": {"notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"},
"resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/requests/{requestId}",
"senderAddress": "tel:+1351111999",
"senderName": "MyName"
}}
```

D.17 Get message delivery status (section 5.12.3)

Request:

```
GET .../{apiVersion}/smsmessaging//outbound/requests/{requestId}/deliveryInfos HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

```
{
  "deliveryInfoList": {
    "deliveryInfo": [
      {
        "address": "tel:+1350000001",
        "deliveryStatus": "MessageWaiting"
      },
      {
        "address": "tel:+1350000999",
        "deliveryStatus": "MessageWaiting"
      }
    ]
  },
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/requests/{requestId}/deliveryInfos"
}
```

D.18 Read delivery notification subscriptions (section 5.13.3)

Request:

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"deliveryReceiptSubscriptionList": {
  "deliveryReceiptSubscription": [
    {
      "callbackReference": {
        "callbackData": "12345",
        "notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
      },
      "filterCriteria": "0102",
      "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}"
    },
    {
      "callbackReference": {
        "callbackData": "54321",
        "notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
      },
      "filterCriteria": "0103",
      "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}"
    }
  ],
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/"
}
```

D.19 Create delivery notification subscription (section 5.13.5)

Request:

```
POST .../{apiVersion}/smsmessaging/outbound/subscriptions HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Host: example.com:80

{"deliveryReceiptSubscription": {
  "callbackReference": {
    "callbackData": "12345",
    "notifyURL": " http://application.example.com/notifications/DeliveryInfoNotification"
  },
  "filterCriteria": "0102"
}}
```

Response:

```
HTTP/1.1 201 Created
Content-Type: application/json
Location:http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"deliveryReceiptSubscription": {
  "callbackReference": {
    "callbackData": "12345",
    "notifyURL": " http://application.example.com/notifications/DeliveryInfoNotification"
  },
  "filterCriteria": "0102",
  "resourceURL": " http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId} "
}}
```

D.20 Read delivery notification subscription (section 5.14.3)

Request:

```
GET .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT

{"deliveryReceiptSubscription": {
  "callbackReference": {
    "callbackData": "12345",
    "notifyURL": "http://application.example.com/notifications/DeliveryInfoNotification"
  },
  "filterCriteria": "0102",
  "resourceURL": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/subscriptions/{subscriptionId}"
}}
```

D.21 Delete subscription for a client (section 5.14.6)

Request:

```
DELETE .../{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId} HTTP/1.1
Accept: application/json
Host: example.com:80
```

Response:

```
HTTP/1.1 204 No Content
Date: Thu, 04 Jun 2009 02:51:59 GMT
```

D.22 Notify client about message delivery status (section 5.15.5)

Request:

```
POST /notifications/DeliveryInfoNotification HTTP/1.1
Accept: application/json
Content-Type: application/json; charset=UTF-8
Host: application.example.com:80

{"deliveryInfoNotification": {
  "callbackData": "12345",
  "deliveryInfo": {
    "address": "tel:+1350000001",
    "deliveryStatus": "DeliveredToNetwork"
  },
  "link": {
    "href": "http://{serverRoot}/{apiVersion}/smsmessaging/outbound/{senderAddress}/subscriptions/{subscriptionId}",
    "rel": "DeliveryReceiptSubscription"
  }
}}
```

Response:

```
HTTP/1.1 204 No Content
Content-Type: application/json
Date: Thu, 04 Jun 2009 02:51:59 GMT
```