



# **Resource List Server (RLS) XDM Specification**

Candidate Version 1.0 – 15 Apr 2005

---

**Open Mobile Alliance**  
OMA-TS-Presence\_SIMPLE\_RLS\_XDM-V1\_0-20050415-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2005 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

# Contents

1. SCOPE .....	4
2. REFERENCES .....	5
2.1 NORMATIVE REFERENCES .....	5
2.2 INFORMATIVE REFERENCES .....	5
3. TERMINOLOGY AND CONVENTIONS .....	6
3.1 CONVENTIONS .....	6
3.2 DEFINITIONS .....	6
3.3 ABBREVIATIONS .....	6
4. INTRODUCTION .....	7
5. RLS XDM APPLICATION USAGES .....	8
5.1 PRESENCE LIST .....	8
5.1.1 Structure .....	8
5.1.2 Application Unique ID .....	8
5.1.3 Default Namespace .....	8
5.1.4 XML Schema .....	8
5.1.5 MIME Type .....	8
5.1.6 Validation constraints .....	8
5.1.7 Data Semantics .....	8
5.1.8 Naming conventions .....	8
5.1.9 Global documents .....	9
5.1.10 Resource interdependencies .....	9
5.1.11 Authorization policies .....	9
6. SUBSCRIBING TO CHANGES IN THE XML DOCUMENTS .....	9
APPENDIX A. STATIC CONFORMANCE REQUIREMENTS (NORMATIVE) .....	10
A.1 RLS XDM SERVER APPLICATION USAGES .....	10
A.2 XDM CLIENT FOR RLS APPLICATION USAGES .....	11
A.3 SUBSCRIBING TO CHANGES IN THE XML DOCUMENTS .....	11
APPENDIX B. EXAMPLES (INFORMATIVE) .....	12
B.1 MANIPULATING PRESENCE LISTS .....	12
B.1.1 Obtaining Presence Lists .....	12
B.1.2 Service URI negotiation .....	13
APPENDIX C. CHANGE HISTORY (INFORMATIVE) .....	15
C.1 APPROVED VERSION HISTORY .....	15
C.2 CANDIDATE VERSION 1.0 HISTORY .....	15

## Figures

Figure B.1- XDM Client obtains Presence Lists .....	12
Figure B.2 - RLS XDMS negotiates a Service URI .....	13

# 1. Scope

The Resource List Server XDMS (RLS XDMS) specific data formats and XCAP application usages are described in this specification.

## 2. References

### 2.1 Normative References

- [IOPPROC] “OMA Interoperability Policy and Process”, Version 1.1, Open Mobile Alliance™, OMA-IOP-Process-V1\_1, URL: <http://www.openmobilealliance.org/>
- [XDMRD] “XML Document Management Requirements”, Version 1.0, Open Mobile Alliance™, OMA-RD-XDM-V1\_0, URL: <http://www.openmobilealliance.org/>
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997, URL: <http://www.ietf.org/rfc/rfc2119.txt>
- [RFC2234] “Augmented BNF for Syntax Specifications: ABNF”. D. Crocker, Ed., P. Overell. November 1997, URL: <http://www.ietf.org/rfc/rfc2234.txt>
- [XCAP] “The Extensible Markup Language (XML) Configuration Access protocol (XCAP)”, J. Rosenberg, February 7, 2005, URL: <http://www.ietf.org/internet-drafts/draft-ietf-simple-xcap-06.txt>  
Note: IETF Draft work in progress
- [XCAP\_List] “Extensible Markup Language (XML) Formats for Representing Resource Lists”, J. Rosenberg, February 7, 2005, URL: <http://www.ietf.org/internet-drafts/draft-ietf-simple-xcap-list-usage-05.txt>  
Note: IETF Draft work in progress
- [XDM\_Spec] “XML Document Management (XDM) Specification”, Version 1.0, Open Mobile Alliance™, OMA-TS-XDM\_Core-V1\_0, URL: <http://www.openmobilealliance.org/>

### 2.2 Informative References

- [XDMAD] “XML Document Management Architecture”, Version 1.0, Open Mobile Alliance™, OMA-XDM-AD-V1\_0, URL: <http://www.openmobilealliance.org/>
- [PRES\_Spec] “Presence SIMPLE Specification”, Version 1.0, Open Mobile Alliance™, OMA-TS-Presence\_SIMPLE-V1\_0, URL: <http://www.openmobilealliance.org/>
- [RFC3856] “A Presence Event Package for the Session Initiation Protocol”, IETF RFC, August 2004, URL: <http://www.ietf.org/rfc/rfc3856.txt>

## 3. Terminology and Conventions

### 3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

### 3.2 Definitions

<b>Application Unique ID</b>	A unique identifier that differentiates XCAP resources accessed by one application from XCAP resources accessed by another. (Source: [XCAP])
<b>Global Document</b>	A document placed under the XCAP global tree that applies to all users of that application usage.
<b>Global Tree</b>	A URL that represents the parent for all global documents for a particular application usage within a particular XCAP root. (Source: [XCAP])
<b>XCAP Application Usage</b>	Detailed information on the interaction of an application with an XCAP server. (Source: [XCAP])
<b>XCAP Client</b>	An HTTP client that understands how to follow the naming and validation constraints defined in [XCAP]. (Source: [XCAP])
<b>XCAP Server</b>	An HTTP server that understands how to follow the naming and validation constraints defined in [XCAP]. (Source: [XCAP])

### 3.3 Abbreviations

<b>AUID</b>	Application Unique ID
<b>HTTP</b>	Hyper Text Transfer Protocol
<b>IETF</b>	Internet Engineering Task Force
<b>OMA</b>	Open Mobile Alliance
<b>RLS</b>	Resource List Server
<b>SIP</b>	Session Initiation Protocol
<b>URI</b>	Uniform Resource Identifier
<b>XCAP</b>	XML Configuration Access Protocol
<b>XDM</b>	XML Document Management
<b>XDMS</b>	XML Document Management Server
<b>XML</b>	Extensible Markup Language

## 4. Introduction

The RLS XDMS is the repository for XML documents that define services which are associated with a list of resources. An example of such a service document is a Presence List, which is used by a RLS (see [PRES\_Spec]) to subscribe, on behalf of a watcher, to the presence status of a list of presentities.

The protocol used to access and manipulate such documents is based on the XML Configuration Access Protocol (XCAP), and described in [XDM\_Spec].

This specification provides the XCAP application usage for one type of RLS-specific XML document, the Presence List.

## 5. RLS XDM Application Usages

### 5.1 Presence List

#### 5.1.1 Structure

The Presence List document SHALL conform to the structure of the “rls-services” document described in [XCAP\_List] section 4.1, with the following clarifications:

- a. Each <service> element SHALL include the <packages> element.
- b. Each <packages> element SHALL specify at least the presence event package as defined in [RFC3856].

#### 5.1.2 Application Unique ID

The application unique ID (AUID) of a Presence List document SHALL be “rls-services” within the IETF tree, as specified in [XCAP\_List] section 4.4.1.

#### 5.1.3 Default Namespace

The default namespace SHALL conform to the default namespace “urn:ietf:params:xml:ns:rls-services” for the “rls-services” document described in [XCAP\_List] section 4.4.4.

#### 5.1.4 XML Schema

A Presence List document SHALL conform to the XML schema described in [XCAP\_List] section 4.2.

#### 5.1.5 MIME Type

The MIME type of a Presence List document SHALL be “application/rls-services+xml”, as specified in [XCAP\_List] section 4.4.2.

#### 5.1.6 Validation constraints

In addition to the XML schema, the validation constraints on a Presence List document SHALL conform to those described in [XCAP\_List] section 4.4.5, with the following clarifications:

The URI in the “uri” attribute of the <service> element (i.e. the Service URI) SHALL be a valid SIP URI. The local policy MAY impose additional constraints on the Service URI format; if so, the RLS XDMS SHALL validate that the Service URI conforms to the local policy.

Whatever the local policy on the format of the Service URI, such policies SHALL NOT violate the “uniqueness constraint” defined in [XCAP\_List] section 4.4.5.

If the Service URI does not conform to the local policy or the uniqueness constraints described above, the RLS XDMS SHALL respond with an HTTP “409 Conflict” response as described in [XCAP].

If the received HTTP “409 Conflict” response includes an “alt-value” element, the XDM Client SHOULD repeat the XCAP request using one of the Service URI provided in the received “alt-value” element.

#### 5.1.7 Data Semantics

The data semantics of a Presence List document SHALL conform to those described in [XCAP\_List] section 4.1.

#### 5.1.8 Naming conventions

The naming conventions of a Presence List document SHALL conform to those described in [XCAP\_List] section 4.4.7.



The document containing the Presence Lists for a particular user SHALL be named “index”.

**NOTE:** Any document in the user’s tree without the name “index” will not be accessible by the RLS service.

### 5.1.9 Global documents

In addition to the Present List documents that exist in the XCAP user tree, this application usage defines a single global document, “index”, created by the RLS XDMS in the XCAP global tree, as described in [XCAP\_List] section 4.4.8.

### 5.1.10 Resource interdependencies

The RLS XDMS SHALL conform to the resource interdependencies described in [XCAP\_List] section 4.4.8.

### 5.1.11 Authorization policies

The authorization policies SHALL conform to those described in [XDM\_Spec] section 6.4.3.

The RLS XDMS SHALL check that the identity of the requesting XDMS has been granted access rights to perform requested operations on the global index document

By default, the primary principal of a document in the users tree has permission to perform retrieve operations as defined in [XDMSPEC] section 6.1.1.2 to fetch that part of the global index document that has the same content as the document in the users tree.

## 6. Subscribing to Changes in the XML Documents

The RLS XDMS SHALL support subscriptions to changes in the XML documents as defined by the procedures in section 6.2.2 of [XDM\_Spec].

## Appendix A. Static Conformance Requirements (Normative)

The SCR's defined in the following tables include SCR for:

- RLS XDM Application Usages

Each SCR table identifies a list of supported features as:

**Item:** Identifier for a feature.

**Function:** Short description of the feature.

**Reference:** Section(s) of this specification with more details on the feature.

**Status:** Whether support for the feature is mandatory or optional. MUST use "M" for mandatory support and "O" for optional support in this column.

**Requirement:** This column identifies other features required by this feature. If no other features are required, this column is left empty.

This section describes the dependency grammar notation to be used in the Requirement column of the SCR and CCR tables using ABNF [RFC2234].

TerminalExpression = ScrReference / NOT TerminalExpression / TerminalExpression LogicalOperator  
TerminalExpression / (" TerminalExpression ")

ScrReference = ScrItem / ScrGroup

ScrItem = SpecScrName "-" GroupType "-" DeviceType "-" NumericId / SpecScrName "-" DeviceType  
"-" NumericId

ScrGroup = SpecScrName ":" FeatureType / SpecScrName "-" GroupType "-" DeviceType "-"  
FeatureType

SpecScrName = 1\*Character;

GroupType = 1\*Character;

DeviceType = "C" / "S"; C – client, S – server

NumericId = Number Number Number

LogicalOperator = "AND" / "OR"; AND has higher precedence than OR and OR is inclusive

FeatureType = "MCF" / "OCF" / "MSF" / "OSF"; See Section A.1.6

Character = %x41-5A ; A-Z

Number = %x30-39 ; 0-9

### A.1 RLS XDM Server Application Usages

Item	Function	Reference	Status	Requirement
RLS_XDM-AU-S-001	Presence list structure	5.1.1	M	
RLS_XDM-AU-S-002	Application Unique ID in presence list	5.1.2	M	
RLS_XDM-AU-S-003	XML schema of presence list	5.1.4	M	
RLS_XDM-AU-S-004	MIME type of presence list	5.1.5	M	

Item	Function	Reference	Status	Requirement
RLS_XDM-AU-S-005	Validation constraints, in addition to the XML schema	5.1.6	M	
RLS_XDM-AU-S-006	RLS XDMS validates that the Service URI conforms to the additional constraints of local policy.	5.1.6	M	
RLS_XDM-AU-S-007	Data semantics of presence list	5.1.7	M	
RLS_XDM-AU-S-008	Naming conventions for presence list	5.1.8	M	
RLS_XDM-AU-S-009	RLS conforms to resource interdependencies	5.1.10	M	
RLS_XDM-AU-S-010	Authorization policies	5.1.11	M	

## A.2 XDM Client for RLS Application Usages

Item	Function	Reference	Status	Requirement
RLS_XDM-CAU-C-001	XDM Client handling of HTTP “409 Conflict” response from the RLS XDMS	5.1.6	O	

## A.3 Subscribing to changes in the XML documents

Item	Function	Reference	Status	Requirement
RLS_XDM-SU-S-001	Generating a NOTIFY request	[XDM_Spec] 6.2.2.2	M	

## Appendix B. Examples

(Informative)

### B.1 Manipulating Presence Lists

#### B.1.1 Obtaining Presence Lists

Figure B.1 describes how an XDM client obtains Presence Lists.




Figure B.1- XDM Client obtains Presence Lists

The details of the flows are as follows:

- 1) The user “sip:ronald.underwood@example.com” wants to obtain the document describing his Presence Lists. For this purpose the XDMC sends an HTTP GET request to the Aggregation Proxy.

```

GET http://xcap.example.com/services/rls-services/users/sip:ronald.underwood@example.com/index/
HTTP/1.1
...
Content-Length: 0
  
```

- 2) Based on the AUID the Aggregation Proxy forwards the request to RLS XDMS.
- 3) After the RLS XDMS has performed the necessary authorisation checks on the request originator, the RLS XDMS sends an HTTP “200 OK” response including the requested document in the body.

```


HTTP/1.1 200 OK
Etag: "etuk8"
...
Content-Type: application/rls-services+xml

<?xml version="1.0" encoding="UTF-8"?>
<rls-services xmlns="urn:ietf:params:xml:ns:rls-services"
  xmlns:rl="urn:ietf:params:xml:ns:resource-lists"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <service uri="sip:mysociety@example.com">
    <resource-list>http://xcap.example.com/services/resource-
      lists/users/sip:hermione.blossom@example.com/~~/
/resource-lists/list%5bname=%22spew%22%5d</resource-list>
    <packages>
      <package>presence</package>
    </packages>
  </service>
  <service uri="sip:friends@example.com">
    <list name="friends">
      <rl:entry uri="sip:hermione.blossom@example.com"/>
      <rl:entry uri="tel:5678;phone-context="+43012349999"/>
    </list>
    <packages>
      <package>presence</package>
    </packages>
  </service>
</rls-services>
  
```

- 4) The Aggregation Proxy routes the response to the XDM Client.

## B.1.2 Service URI negotiation

Figure B.2 describes how the RLS XDMS can negotiate a Service URI.



**Figure B.2 - RLS XDMS negotiates a Service URI**

The details of the flows are as follows:

- 1) The user “sip:ronald.underwood@example.com” wants to create a Service URI “sip:wrongname@example.com”. For this purpose the XDMC sends an HTTP PUT request to the Aggregation Proxy.

```

PUT http://xcap.example.com/services/rls-services/users/sip:ronald.underwood@example.com/index/~/~/rls-services/service HTTP/1.1
...
Content-Type: application/xcap-el+xml
Content-Length: (...)

<service uri="sip:wrongname@example.com">
  <list name="family">
    <rl:entry uri="sip:vernon.keel@example.com"/>
  </list>
  <packages>
    <package>presence</package>
  </packages>
</service>
  
```

- 2) Based on the AUID the Aggregation Proxy forwards the request to RLS XDMS.
- 3) The RLS XDMS detects that the Service URI does not conform to the local policy. The RLS XDMS generates a valid Service URI “sip:correctname@example.com” and sends an HTTP “409 Conflict” response including the generated URI.

```

HTTP/1.1 409 Conflict
...
Content-Type: application/xcap-error+xml

<?xml version="1.0" encoding="UTF-8"?>
<xcap-error xmlns="urn:ietf:params:xml:ns:xcap-error">
  <uniqueness-failure>
    <exists field="service/@uri">
      <alt-value>sip:correctname@example.com</alt-value>
    </exists>
  </uniqueness-failure>
</xcap-error>
  
```

- 4) The Aggregation Proxy routes the response to the XDM Client.
- 5) The XDM Client repeats the XCAP request (sent in step 1) using the received Service URI.

```
PUT http://xcap.example.com/services/rls-services/users/sip:ronald.underwood@example.com/index/~~/rls-services/service HTTP/1.1
...
Content-Type: application/xcap-el+xml
Content-Length: (...)

<service uri="sip:correctname@example.com">
  <list name="family">
    <rl:entry uri="sip:vernon.keel@example.com"/>
  </list>
  <packages>
    <package>presence</package>
  </packages>
</service>
```

- 6) Based on the AUID the Aggregation Proxy forwards the request to RLS XDMS.
- 7) The RLS XDMS creates the requested Presence List document and sends an HTTP “201 Created” response.

```
HTTP/1.1 201 Created
Etag: "etu65"
...
Content-Length: 0
```

- 8) The Aggregation Proxy routes the response to the XDM Client.

## Appendix C. Change History

(Informative)

### C.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version

### C.2 Candidate Version 1.0 History

Document Identifier	Date	Sections	Description
Draft Version OMA-RLS_XDM_Specification-V1_0	27 Sept 2004	All	Initial version created.
	15 Oct 2004	All	Incorporates input to committee: OMA-PAG-2004-0544R02-RLS-XDM-Specification OMA-PAG-2004-0547-RLS-XDMS-MessageFlowExample
	22 Oct 2004	5.2.1, 5.3.5, Appendix B	Incorporates input to committee: OMA-PAG-2004-0559-RLS-XDMS-ServiceURINegotiation
	26 Oct 2004	5.2.1, 5.3.5	Incorporates input to committee: OMA-PAG-2004-0588R02-RLS-XDM-Specification
	1 Nov 2004	Appendix A	Incorporates input to committee: OMA-PAG-2004-0618R01-RLS-XDM-SCR
	12 Nov 2004	5.3.5	Incorporates OMA-PAG-2004-0649R02- RLS-XDMS-Uniqueness-of-URI-attribute-value
		5.1, 5.2	Incorporates OMA-PAG-2004-0686R02-RLS-XDM-functional-entity-description
	15 Nov 2004	Appendix A	Incorporates OMA-PAG-2004-0727-RLS-XDM-Spec-SCR-changes
17 Nov 2004	2, 3	Editor cleanup of references, definitions, and abbreviations	
OMA-TS- Presence_SIMPLE_RLS_XDM-V1_0	21 Feb 2005	Various	Incorporates resolutions to CONRR RLS XDM comments 3, 4, 5, 6, 7, 10, 11, 13, 14, 15, and editorials. Also incorporates OMA-PAG-2005-0015R01.
	3 Mar 2005	Various	Incorporates OMA-PAG-2005-0194.
	4 Mar 2005	5.1.11, 6, A.3	Incorporates OMA-PAG-2005-0085R01 and -0252R01.
	8 Mar 2005	Appendix A	Editor cleanup of section references.
Candidate Versions OMA-TS- Presence_SIMPLE_RSL_XDM-V1_0	17 Mar 2005		Status changed to Candidate by TP: OMA ref# OMA-TP-2005-0093R01-Presence-SIMPLE-V1_0-for-Candidate-approval
Candidate Versions OMA-TS- Presence_SIMPLE_RSL_XDM-V1_0	15 Apr 2005	2.1	Incorporates OMA-PAG-2005-0194.R01