



Standardized Connectivity Management Objects HTTP Proxy Parameters

For use with OMA Device Management
Candidate Version 1.0 – 12 Aug 2008

Open Mobile Alliance
OMA-DDS-DM_ConnMO_HTTPProxy-V1_0-20080812-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2008 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

Contents

1. SCOPE.....	4
1.1 CONNECTIVITY OBJECT – HTTP PROXY.....	4
2. REFERENCES	5
2.1 NORMATIVE REFERENCES.....	5
2.2 NORMATIVE AUTHORITIES OF REFERENCES.....	5
2.3 INFORMATIVE REFERENCES.....	5
3. TERMINOLOGY AND CONVENTIONS.....	6
3.1 CONVENTIONS.....	6
3.2 DEFINITIONS.....	6
3.3 ABBREVIATIONS.....	6
4. INTRODUCTION	7
5. JUSTIFICATION	8
5.1 STANDARDIZED CONNECTIVITY MANAGEMENT	8
5.2 APPLICATION-NEUTRAL	8
5.3 BEARER-NEUTRAL	8
6. HTTP PROXY SPECIFIC MANAGEMENT OBJECT.....	9
6.1 INTRODUCTION.....	9
6.2 DEFINITIONS RELATED TO PROXYMO.....	9
6.3 GRAPHICAL REPRESENTATION (INFORMATIVE)	9
6.4 NODE DESCRIPTIONS.....	9
7. OPERATIONAL CONSIDERATIONS	11
APPENDIX A. CHANGE HISTORY (INFORMATIVE).....	12
A.1 APPROVED VERSION HISTORY	12
A.2 DRAFT/CANDIDATE VERSION 1.0 HISTORY	12

Figures

Figure 1. HTTP Proxy specific parameters	9
--	---

Tables

Table 1: Proxy Authentication Protocol Types	9
--	---

1. Scope

1.1 Connectivity Object – HTTP Proxy

This document defines HTTP Proxy specific parameters that are used together with the standardized connectivity management object [CONNMO] in order to have a complete standardized Proxy management object for HTTP Proxy in the OMA DM management tree.

While this HTTP Proxy object is optional for any OMA DM implementation, their widespread use will simplify the management of basic HTTP Proxy parameters in mobile terminals.

The object is defined using the OMA DM Device Description Framework [DMTND]. The object has standardized points of extension to permit implementation-specific parameters to accompany the standardized parameters. This added flexibility is intended to encourage the use of the standardized object while not unnecessarily restricting individual vendor innovations.

2. References

2.1 Normative References

- [CONNMO] *Standardized Connectivity Management Objects, Version 1.0*, Open Mobile Alliance™, OMA-DDS-DM_ConnMO_V1_0-D, [URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [DMTND] *Device Management Tree and Description, Version 1.2*, Open Mobile Alliance™, OMA-TS-DM-DMTND-V1_2, [URL:http://www.openmobilealliance.org](http://www.openmobilealliance.org)
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997, [URL:http://www.ietf.org/rfc/rfc2119.txt](http://www.ietf.org/rfc/rfc2119.txt)

2.2 Normative Authorities of References

Various parameters specified in the management objects defined in this document rely on an authority outside the scope of this specification to supply the set of acceptable values and value formats. In such references to external authority, only the directly cited material is referenced, not the entire external specification. The following authorities of reference are cited in this document:

- [RFC2617] *RFC2617, HTTP Authentication: Basic and Digest Access Authentication*,
URL; <http://www.ietf.org/rfc/rfc2617.txt>

2.3 Informative References

N/A

3. Terminology and Conventions

3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

3.2 Definitions

See the DM Tree and Description [DMTND] document for definitions of terms related to the management tree.

3.3 Abbreviations

OMA Open Mobile Alliance

4. Introduction

Usually over time network protocols grow and are replaced as the market cycle plays out. Connectivity Management Object [CONNMO] is structured in such a way as to be resilient to the addition of new bearer and proxy types without requiring wholesale replacement of the object definitions. In this way, the common structure survives into future versions of the management objects thus easing the burden of transition from old bearer types to new.

This document specifies HTTP Proxy specific part of the general Proxy management object and it also allows for vendor specific extensions.

5. Justification

This Reference Release includes several Management Object definitions for use, in conjunction with the OMA Device Management Enabler, to manage data network connectivity settings for mobile terminals over common bearer and proxy types.

5.1 Standardized Connectivity Management

Providing a standardized set of management objects for configuration of data network connectivity through the OMA Device Management system will improve the usability and customer experience of mobile terminals that rely upon data services. As proposed, the management object definitions may be used in conjunction with OMA Device Management Candidate and Approved Enabler Releases over a variety of transports including: HTTP, HTTPS, OBEX over IrDA, OBEX over Bluetooth, and various forms of Smart Card.

5.2 Application-Neutral

Producing these management object definitions in an application-neutral fashion, we avoid reinvention of solutions to the same set of problems for each of new application that requires data connectivity. This reduces the connectivity parameters that an application must define to a simple reference node, ConRef (Connectivity Reference).

5.3 Bearer-Neutral

By presenting the specifications in two parts, a bearer-neutral part and bearer-specific bindings, we reinforce the OMA principle of network neutrality while providing specificity where needed but without bias for or against any particular network type.

6. HTTP Proxy Specific Management Object

6.1 Introduction

A general introduction of the connectivity management object is given in the connectivity management object document [CONNMO] as well as the needed compliance rules. This document specifies the HTTP Proxy specific MO.

6.2 Definitions related to ProxyMO

The HTTP sub tree specified in this document MUST be placed under the *ProxyParams* node in [CONNMO].

ProxyType in ProxyMO

The *ProxyType* node value specified in [CONNMO] MUST be “HTTP”.

AuthInfo/<x>/AuthType in ProxyMO

The AuthType value in the ProxyMO [ConnMO] MUST be one of them in the table below:

AuthType	Description
HTTP-BASIC	HTTP basic authentication done according to [RFC2617].
HTTP-DIGEST	HTTP digest authentication done according to [RFC2617].

Table 1: Proxy Authentication Protocol Types

6.3 Graphical Representation (Informative)

The following figure provides the structure of HTTP Proxy specific parameter sub-tree.



Figure 1. HTTP Proxy specific parameters

6.4 Node descriptions

.../ProxyParams/HTTP

Status	Occurrence	Format	Min. Access Types
Required	One	node	Get

This interior node specifies the HTTP Proxy specific management object for a *Proxy* management object. Management Object Identifier for the HTTP Proxy MO MUST be: “urn:oma:mo:oma-connmo-http:1.0”.

Ext

Status	Occurrence	Format	Min. Access Types
Optional	ZeroOrOne	node	Get

This optional interior node designates a branch of the Proxy parameters sub-tree into which vendor extensions MAY be added, permanently or dynamically. Ext sub trees, such as this one, are included at various places in the DM connectivity management objects to provide flexible points of extension for implementation-specific parameters. However, vendor extensions MUST NOT be defined outside of one of these `Ext` sub-trees.

Ext/UniqueVendorName

Status	Occurrence	Format	Min. Access Types
Optional	ZeroOrMore	node	Get

This interior node is supplied by a vendor to distinguish their extension from those of other vendors. The *UniqueVendorName* SHOULD be a trademark or company name controlled by each vendor to ensure uniqueness. The structure of any sub-tree below a *UniqueVendorName* interior node is implementation-specific.

7. Operational Considerations

ConnMO is normatively dependent on the DM 1.2 specifications. However, this normative dependency should not be seen as restricting these MO definitions only to DM clients implementing that version of the DM enabler.

For example, a management authority may exchange ConnMO data-files using means not specifically defined in the DM 1.2 enabler.

Appendix A. Change History (Informative)

A.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version

A.2 Draft/Candidate Version 1.0 History

Document Identifier	Date	Sections	Description
Draft Versions OMA-DDS-DM_ConnMO_HTTPProxy	3 Oct 2007	All	First version based on the corresponding TS
	7 Oct 2007	5	Added from the WID
	17 Oct 2007	2	Added CR: OMA-DM-ConnMO-2007-0010-CR_HTTPProxy_BugFix
		7	Added from the approved ETR
	11 Feb 2008	All	Editorial update: - New template - New node definition table
	14 Apr 2008	6	Editorial update
08 May 2008	6	Editorial update according to consistency review comment J001	
Candidate Versions OMA-DDS-DM_ConnMO_HTTPProxy	12 Aug 2008	n/a	Status changed to Candidate by TP TP ref#: OMA-TP-2008-0286- INP_Connectivity_Management_Objects_V1_0_RRP_for_Candidate_Approval