SyncML Implementation Conformance Statement Proforma

SyncML DataSync V1.1.1

Abstract

The SyncML Implementation Conformance Statement is designed to be used by vendors to show their level of conformance with SyncML specifications.

Note that if you are submitting both a client and a server, you will need to fill out two separate forms.

SyncML DataSync (V1.1.1)

2 of 20 Pages Version 1.0

2002-10-22

SyncML Initiative

The following companies are Sponsors of the SyncML Initiative:

Ericsson
IBM
Lotus
Matsushita Communication Industrial Co., Ltd.
Motorola
Nokia
Openwave
Palm, Inc.
Psion
Starfish Software
Symbian

Revision History

Revision	Date	Comments
1.0	2002-10-22	Signed off for integration into OMA.



SyncML DataSync (V1.1.1)

3 of 20 Pages

Version 1.0 2002-10-22

Copyright Notice

Copyright (c) Ericsson, IBM, Lotus, Matsushita Communication Industrial Co., LTD, Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian (2000-2002).

All Rights Reserved.

Implementation of all or part of any Specification may require licenses under third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a Supporter). The Sponsors of the Specification are not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE PROVIDED ON AN "AS IS" BASIS WITHOUT WARRANTY OF ANY KIND AND ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO. LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE AND ALL OTHER SYNCML SPONSORS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO., LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE OR ANY OTHER SYNCML SPONSOR BE LIABLE TO ANY PARTY FOR ANY LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OF DATA, INTERRUPTION OF BUSINESS, OR FOR DIRECT, INDIRECT, SPECIAL OR EXEMPLARY, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY KIND IN CONNECTION WITH THIS DOCUMENT OR THE INFORMATION CONTAINED HEREIN, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The above notice and this paragraph must be included on all copies of this document that are made.

2002-10-22





Table of Contents

1	Intro	oduction	5
2	Proc	duct Information	6
	2.1	Device and Contact Information	6
	2.2	Content Formats Supported	6
3	Synd	c Server Conformance	7
	3.1	Representation Common Use Elements	7
	3.2	Representation Message container elements	7
	3.3	Data description elements	8
	3.4	Representation Protocol command elements	8
	3.5	Device Info	9
	3.6	Meta Info	10
	3.7	Protocol	10
	3.8	Authentication	11
	3.9	MIME header types	11
4	Synd	c Client Conformance	12
	4.1	Representation Common Use Elements	12
	4.2	Representation Message container elements	12
	4.3	Data description elements	13
	4.4	Representation Protocol command elements	13
	4.5	Device Info	13
	4.6	Meta Info	14
	4.7	Protocol	15
	4.8	Authentication	15
	4.9	MIME header types	15
5	Tran	nsport Conformance	17
	5.1	HTTP Transport	
	5.2	OBEX Transport	18
	5.3	WSP Transport	18
6	Add	itional Information	19
7	Refe	erences	20
•			20

SyncML DataSync (V1.1.1)

5 of 20 Pages

Version 1.0 2002-10-22

1 Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a given SyncML specification. Such a statement is called an Implementation Conformance Statement (ICS).

The purpose of this statement is to define a methodology for showing conformance with the SyncML specifications. Vendors filling in this form will mark the items with either YES or NO, indicating whether the items are implemented or not. Mandatory items marked NO MUST have explanatory text

NOTE: Server must be able to deal with the two cases of packages 1 & 3 being sent seperately and combined.

Please use section 6 to provide any additional information with regards to your Implementation Conformance Statement. Please do not annotate the SCR items in the following sections.

2 Product Information

2.1 Device and Contact Information

Device Name & Version:	Sync Server 2.0
Company:	EVERelite
Contact Name:	Mitch Huang
Contact Phone:	+886-2-2751-7000 ext.251
Contact Email:	mitch.huang@ever.com.tw
Product is:	CLIENT[] SERVER[X]
Transports supported:	HTTP[X] WSP[] OBEX[]
OBEX support:	IrDA[] Bluetooth[]

Notes:

- The contents of the [Device Name & Version] field will appear in the List of compliant products on the SyncML web page.
- OBEX support for RS232 and USB is not defined scoped out within the SyncML bindings specifications. Devices cannot claim these transports until the specifications have been updated.


2.2 Content Formats Supported

This section contains the ICS proforma for the Statics Conformance Requirements for the Content Format as specfied in [3].

NOTE: If a server supports a data type listed below, it must also support the associated content format.

Data Type	Content Format	Supported (Y/N)
Contact	vCard 2.1	Y
	vCard 3.0 (optional)	Y
Calendar	vCalendar 1.0	Y
	iCalendar 2.0 (optional)	Y
Memos	Text/plain	Y
Tasks	vTodo 1.0	Y
Email	message/rfc822	Y
	message/rfc2822	N
	message/rfc2045	N
Other (Please specify any other supported data types)		N

Copyright © 2000-2002 Ericsson, IBM, Lotus, Matsushita Communicati on Industrial Co., Ltd., Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian. All Rights Reserved.





3 Sync Server Conformance

NOTE: Server SHOULD be able to log the XML and WBXML documents sent between the server and a client.

3.1 Representation Common Use Elements

This section contains the ICS proforma for the Static Conformance Requirements for the Representation Common Use Elements as defined in [3].

Command	Require	d of Server	Implemented in Server	
Г	Sending	Receiving	Sending	Receiving
Archive	MAY	MUST	NO	YES
Chal	MUST	MUST	YES	YES
Cmd	MUST	MUST	YES	YES
CmdID	MUST	MUST	YES	YES
CmdRef	MUST	MUST	YES	YES
Cred	MUST	MUST	YES	YES
Final	MUST	MUST	YES	YES
Lang	MAY	MAY	NO	NO
LocName	MAY	MAY	NO	YES
LocURI	MUST	MUST	YES	YES
MoreData	MUST	MUST	YES	YES
MsgID	MUST	MUST	YES	YES
MsgRef	MUST	MUST	YES	YES
NoResp	MAY	MUST	NO	YES
NoResults	MAY	MAY	NO	NO
NumberOfChanges	MAY	MUST	YES	YES
RespURI	MAY	MUST	NO	YES
SessionID*	MUST	MUST	YES	YES
SftDel	MAY	MAY	NO	NO
Source	MUST	MUST	YES	YES
SourceRef	MUST	MUST	YES	YES
Target	MUST	MUST	YES	YES
TargetRef	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
VerProto	MUST	MUST	YES	YES

^{*}The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

3.2 Representation Message container elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Message Container elements as defined in [3].

Command	Required of Server		Implemen	ted in Server
	Sending	Receiving	Sending	Receiving
SyncML	MUST	MUST	YES	YES
SyncHdr	MUST	MUST	YES	YES
SyncBody	MUST	MUST	YES	YES



3.3 Data description elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Data Description elements as defined in [3].

Command	Required of Server		Implement	ted in Server
	Sending	Receiving	Sending	Receiving
Data	MUST	MUST	YES	YES
Item	MUST	MUST	YES	YES
Meta	MUST	MUST	YES	YES

3.4 Representation Protocol command elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Protocol Command elements as defined in [3].

Command	Required of Server		Implemen	ted in Server
	Sending	Receiving	Sending	Receiving
Add	MUST	MUST	YES	YES
Alert	MUST	MUST	YES	YES
Atomic	MAY	MAY	NO	NO
Copy	MAY	MUST	NO	YES
Delete	MUST	MUST	YES	YES
Exec	MAY	SHOULD	NO	NO
Get*	MUST	MUST	YES	YES
Map	MAY	MUST	NO	YES
MapItem	MAY	MUST	NO	YES
Put*	MUST	MUST	YES	YES
Replace	MUST	MUST	YES	YES
Result*	MUST	MUST	YES	YES
Search	MAY	MAY	NO	NO
Sequence	MAY	MUST	NO	YES
Status	MUST	MUST	YES	YES
Sync	MUST	MUST	YES	YES

^{*}Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

2002-10-22



SyncML DataSync (V1.1.1)

3.5 Device Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Device Information as defined in [5].

Element Type	Required of Server		Implemen	Implemented in Server	
	Sending	Receiving	Sending	Receiving	
CTCap	SHOULD	MUST	YES	YES	
CTType	MUST	MUST	YES	YES	
DataStore	MUST	MUST	YES	YES	
DataType	MAY	MUST	NO	YES	
DevID	MUST	MUST	YES	YES	
DevInf	MUST	MUST	YES	YES	
DevTyp	MUST	MUST	YES	YES	
DisplayName	MAY	MAY	NO	NO	
DSMem	MAY	SHOULD	NO	NO	
Ext	MAY	MAY	NO	NO	
FwV	MAY	SHOULD	NO	NO	
HwV	MAY	SHOULD	NO	NO	
Man	MAY	SHOULD	NO	NO	
MaxGUIDSize	MUST NOT	MUST	NO	YES	
MaxID	MAY	SHOULD	NO	NO	
MaxMem	MAY	SHOULD	NO	NO	
Mod	MAY	MAY	NO	NO	
OEM	MAY	MAY	NO	NO	
ParamName	SHOULD	MUST	YES	YES	
PropName	SHOULD	MUST	YES	YES	
Rx	MAY	MUST	NO	YES	
Rx-Pref	MUST	MUST	YES	YES	
SharedMem	SHOULD	MAY	NO	NO	
Size	MAY	MUST	NO	YES	
SourceRef	MUST	MUST	YES	YES	
SupportLargeObjs	MUST	MUST	YES	YES	
SupportNumberOfChanges	MAY	MUST	YES	YES	
SwV	MAY	SHOULD	NO	NO	
SyncCap	MUST	MUST	YES	YES	
SyncType	MUST	MUST	YES	YES	
Tx	MAY	MUST	NO	YES	
Tx-Pref	MUST	MUST	YES	YES	
UTC	MAY	MUST	NO	YES	
ValEnum	SHOULD	MUST	YES	YES	
VerCT	MUST	MUST	YES	YES	
VerDTD	MUST	MUST	YES	YES	
Xnam	MAY	MAY	NO	NO	
Xval	MAY	MAY	NO	NO	

3.6 Meta Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Meta Information as defined in [4].

Element Type	Required of Server		Implement	ted in Server
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST	YES	YES
EMI	MAY	MAY	NO	NO
Format	MUST	MUST	YES	YES
FreeID	MAY	MUST	NO	YES
FreeMem	MAY	MUST	NO	YES
Last	MUST	MUST	YES	YES
Mark	MAY	MAY	YES	YES
MaxMsgSize	MAY	MUST	NO	YES
MaxObjSize	MUST	MUST	YES	YES
Mem	MAY	MUST	NO	YES
MetInf	MUST	MUST	YES	YES
Next	MUST	MUST	YES	YES
NextNonce	MUST	MUST	YES	YES
SharedMem	MAY	MUST	NO	YES
Size	MAY	MAY	YES	YES
Type	MUST	MUST	YES	YES
Version	MUST	MUST	YES	YES

3.7 Protocol

This section contains the ICS Proforma for the Static Conformance Requirements for the Sync Protocol as defined in [2].

Element Type	Server Ro	equirements
	Required	Implemented
Support of 'two -way sync'	MUST	YES
Support of 'slow two-way sync'	MUST	YES
Support of 'one -way sync from client only'	MAY	NO
Support of 'refresh sync from client only'	MAY	NO
Support of 'one -way sync from server only'	MAY	NO
Support of 'refresh sync from server only'	MAY	NO
Support of 'sync alert'	MAY	NO
Support of 'busy signalling'	SHOULD	YES
Support of multiple messages per package	MUST	YES
Support of combined package 1 and 3	MUST	YES
Support of 'large object handling'	MUST	YES
Support of 'number of changes'	MAY	YES

SyncML DataSync (V1.1.1)

11 of 20 Pages Version 1.0

2002-10-22

3.8 Authentication

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Authentication as defined in [2].

Authentication Type	Server Requirements	
	Required	Implemented
Basic (name and password)	MUST	YES
MD5	MUST	YES

3.9 MIME header types

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML MIME Media Types as defined in [3].

MIME Header Type	Server Requirements	
	Required	Implemented
"application/vnd.syncml+xml"	MUST	YES
"application/vnd.syncml+wbxml"	MUST	YES

Sync Client Conformance

Representation Common Use Elements

This section contains the ICS proforma for the Static Conformance Requirements for the Representation Common Use Elements as defined in [3].

Command	nmand Required of Client		Implemer	nted in Client
	Sending	Receiving	Sending	Receiving
Archive	MAY	MAY		
Chal	MAY	MUST		
Cmd	MUST	MUST		
CmdID	MUST	MUST		
CmdRef	MUST	MUST		
Cred	MUST	MUST		
Final	MUST	MUST		
Lang	MAY	MAY		
LocName	MAY	MAY		
LocURI	MUST	MUST		
MoreData	MAY	MAY		
MsgID	MUST	MUST		
MsgRef	MUST	MUST		
NoResp	MAY	MUST		
NoResults	MAY	MAY	ĺ	
NumberOfChanges	MAY	MAY		
RespURI	MAY	MUST		
SessionID*	MUST	MUST		
SftDel	MAY	MAY		
Source	MUST	MUST		
SourceRef	MUST	MUST		
Target	MUST	MUST		
TargetRef	MUST	MUST		
VerDTD	MUST	MUST		
VerProto	MUST	MUST		

^{*}The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

4.2 Representation Message container elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Message Container elements as defined in [3].

ı	Command	Required of Client		Implemen	ted in Client
		Sending	Receiving	Sending	Receiving
I	SyncML	MUST	MUST		
	SyncHdr	MUST	MUST		
	SyncBody	MUST	MUST		

4.3 Data description elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Data Description elements as defined in [3].

Command	Required of Client		Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Data	MUST	MUST		
Item	MUST	MUST		
Meta	MUST	MUST		

4.4 Representation Protocol command elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Protocol Command elements as defined in [3].

Command	Required	l of Client	Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Add	SHOULD	MUST		
Alert	MUST	MUST		
Atomic	MAY	MAY		
Copy	MAY	MAY		
Delete	MUST	MUST		
Exec	MAY	MAY		
Get*	SHOULD	MUST		
Map	MUST	MAY		
MapItem	MUST	MAY		
Put*	MUST	MUST		
Replace	MUST	MUST		
Result*	MUST	SHOULD		
Search	MAY	MAY		
Sequence	MAY	MAY		
Status	MUST	MUST		
Sync	MUST	MUST		

^{*}Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

4.5 Device Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Device Information as defined in [5].

Element Type	Requir	Required of Client		ed in Client
	Sending	Receiving	Sending	Receiving
CTCap	MUST	SHOULD		
CTType	MUST	MUST		
DataStore	MUST	MUST		
DataType	MAY	MAY		
DevId	MUST	MUST		
DevInf	MUST	MUST		
DevTyp	MUST	MUST		

Copyright © 2000-2002 Ericsson, IBM, Lotus, Matsushita Communicati on Industrial Co., Ltd., Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian. All Rights Reserved.



Version 1.0 2002-10-22

DisplayName	MAY	MAY	
DSMem	SHOULD	MAY	
Ext	MAY	MAY	
FwV	SHOULD	MAY	
HwV	SHOULD	MAY	
Man	SHOULD	MAY	
MaxGUIDSize	MUST	MUST NOT	
MaxID	SHOULD	MAY	
MaxMem	SHOULD	MAY	
Mod	MAY	MAY	
OEM	MAY	MAY	
ParamName	SHOULD	SHOULD	
PropName	MUST	SHOULD	
Rx	MAY	MUST	
Rx-Pref	MUST	MUST	
SharedMem	SHOULD	MAY	
Size	MAY	MAY	
SourceRef	MUST	MUST	
SupportLargeObjs	SHOULD	SHOULD	
SupportNumberOfChanges	MAY	MAY	
SwV	SHOULD	MAY	
SyncCap	MUST	MUST	
SyncType	MUST	MUST	
Tx	MAY	MUST	
Tx-Pref	MUST	MUST	
UTC	MAY	MAY	
ValEnum	MUST	SHOULD	
VerCT	MUST	MUST	
VerDTD	MUST	MUST	
Xnam	MAY	MAY	
Xval	MAY	MAY	

4.6 Meta Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Meta Information as defined in [4].

Element Type	Required	of Client	Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST		
EMI	MAY	MAY		
Format	MUST	MUST		
FreeID	SHOULD	MAY		
FreeMem	SHOULD	MAY		
Last	MUST	MUST		
Mark	MAY	MAY		
MaxMsgSize	MAY	MUST		
MaxObjSize	SHOULD	SHOULD		
Mem	SHOULD	MAY		
MetInf	MUST	MUST		
Next	MUST	MUST		
NextNonce	MAY	MUST		
SharedMem	SHOULD	MAY		

Copyright © 2000-2002 Ericsson, IBM, Lotus, Matsushita Communicati on Industrial Co., Ltd., Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian. All Rights Reserved.



Size	MAY	MAY	
Type	MUST	MUST	
Version	MAY	MAY	

4.7 **Protocol**

This section contains the ICS Proforma for the Static Conformance Requirements for the Sync Protocol as defined in [2].

Element Type	Client Re	equirements
	Required	Implemented
Support of 'two -way sync'	MUST	
Support of 'slow two-way sync'	MUST	
Support of 'one -way sync from client only'	MAY	
Support of 'refresh sync from client only'	MAY	
Support of 'one -way sync from server only'	MAY	
Support of 'refresh sync from server only'	MAY	
Support of 'sync alert'	MAY	
Support of multiple messages per package	MUST	
Support of combined package 1 and 3	MAY	
Support of 'large object handling'	SHOULD	
Support of 'number of changes'	MAY	

4.8 **Authentication**

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Authentication as defined in [2].

Note that authentication is only required for SyncHdr, optional for datastore.

Authentication Type	Client Requirements	
	Required Implemente	
Basic (name and password)	MUST	
MD5	MUST	

4.9 MIME header types

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML MIME Media Types as defined in [3].

NOTE: the client MUST support one of the two MIME header types.

MIME Header Type	Client Re	quirements
	Required	Implemented
"application/vnd.syncml+xml"	MUST if no wbxml	
"application/vnd.syncml+wbxml"	MUST if no xml	

Copyright © 2000-2002 Ericsson, IBM, Lotus, Matsushita Communication Industrial Co., Ltd., Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian. All Rights Reserved.



SyncML DataSync (V1.1.1)

16 of 20 Pages Version 1.0

2002-10-22

5 Transport Conformance

5.1 HTTP Transport

Vendors should fill this section out ONLY if their product uses the HTTP Transport. The specification for HTTP Transport is fully described in [6].

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	YES

General Headers	Requirements	
	Required	Implemented
Cache-Control: no-store, private	MUST	YES
Transfer-Encoding: chunked	MUST	YES

Request Headers	Req	Requirements	
	Required	Implemented	
Accept	MUST	YES	
Accept-Charset	MUST	YES	
Authorization	MUST	YES	
Proxy-Authorization	MUST if a proxy client	NO	
User-Agent	MUST	YES	

Response Headers	Requi	Requirements	
	Required	Implemented	
Authentication-Info	MUST	YES	
Proxy-Authenticate	MUST if proxy client	NO	
WWW-Authenticate	MUST	YES	



5.2 **OBEX Transport**

Vendors should fill this section out ONLY if their product uses the OBEX Transport. The specification for OBEX Transport is fully described in [7]. Note that these definitions of client and server are the OBEX definition, not the SyncML definition.

NOTE that the tables only indicate the required data.

Method	OBEX Serve	OBEX Server Requirements	
	Required	Implemented	
GET	MUST		
PUT	MUST		
CONNECT	MUST		
DISCONNECT	MUST		
ABORT	MUST		

Method	OBEX Client Requirements	
	Required	Implemented
GET	MUST	
PUT	MUST	
CONNECT	MUST	
DISCONNECT	MUST	

5.3 WSP Transport

Vendors should fill this section out ONLY if their product uses the WSP Transport. The specification for WSP Transport is fully described in [8].

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	



Version 1.0 2002-10-22

6 Additional Information

Please use this section to provide any additional information with regards to your Implementation Conformance Statement. Please do not annotate the previous sections.	



7 References

- SyncML Representation Protocol, version 1.1.1
- SyncML Sync Protocol, version 1.1.1
- SyncML Representation Protocol, Data Synchronization Usage, version 1.1.1 [3]
- [4] SyncML Meta-Information DTD, version 1.1.1
- [5] SyncML Device Information DTD, version 1.1.1
- [6] SyncML HTTP Binding, version 1.1.1
- SyncML OBEX Binding, version 1.1.1 [7]
- [8] SyncML WSP Binding, version 1.1.1